

## DUBAI CENTRAL LABORATORY DEPARTMENT DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME

### SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL15020251

**Certificate Issued To:** **HESSE GMBH & CO. KG**  
Warendorfer Strabe 21, 59075 Hamm, Germany.

**Applicable Standard Specification:** **2023 Al Sa'fat Dubai Green Building System-2nd** edition clauses [404.01] and/or [404.02], [304.01], [304.04] [304.07], [701.04] and related clauses in 2021- Dubai Building Code.

**Applicable Specific Rules:** **DM-DCLD-RD-DP21-2180-(IC)** : Certification of Low Emitting Materials as per Al Sa'fat – Dubai Green Building System & Dubai Building Code.

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
1	Water base – One pack performance coating Coatings (other than paint). (For Interior Applications)	Hesse COOL-FILL (HP 6645-9343)	VOC (Al Sa'fat-DGBS limit is Max. = 140 g/l)
		Hesse COOL-TOP, Silky gloss (HE 65096)	
		Hesse HYDRO Isolating filler (HP 6633-9343)	
		Hesse HYDRO Metallic lacquer, Silk matt (HB 65445-RAL 9006)	
2	Solvent base - One pack performance coating. Coatings (other than paint). (For Interior Applications)	Hesse UV Spray Primer (YUG 7654)	VOC (Al Sa'fat-DGBS limit is Max. = 500 g/l);
		Hesse UV Spray Primer Clear (YUG 7600)	
		Hesse UV Top Coat for Spraying Clear, Silk matt (YUU 76206)	
		Hesse UV Color Primer for Roller Coating (UP 7481-9343)	
3		Hesse HYDRO-PU Glass colour lacquer, Silk matt	VOC (Al Sa'fat-DGBS limit is

## DUBAI CENTRAL LABORATORY DEPARTMENT DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME

### SCOPE OF CERTIFICATION FOR CERTIFICATE NO. CL15020251

	Water base - Two pack reactive performance coating for specific end use such as floors Coatings (other than paint). (For Interior Applications)	(HDB 57485-RAL 9010)	Max. = 140 g/l);
		Hesse HYDRO Crosslinker (HDR 5002)	
		Hesse PURA-ONE, Silk matt (HDE 51-4); Hesse HYDRO Hardener (HDR 71)	
		Hesse PERFECT-TOP (HDE 5400X) (0-8); Hesse HYDRO Hardener (HDR 5091)	
		Hesse PERFECT-BASE (HDG 5407); Hesse HYDRO Hardener (HDR 5091)	
4	Solvent base - Two pack reactive performance coating for specific end use such as floors. Coatings (other than paint) (For Interior Applications)	Hesse SUN-CAPE PU Base Coat (DG 4716-0002); Hesse PU Hardener DR 4071	VOC (Al Sa'fat-DGBS limit is Max. = 550 g/l);
		Hesse PU Isolating Filler (DP 4784-9343) ; Hesse PU Hardener DR 4052	
		Hesse UV Basecoat for Roller Coating (YPUG 7541-0007, UZ 7378)	
		Hesse UV Top Coat for Roller Coating (YPUU 74505); UZ 7380 / UZ 7396	
		Hesse FANTASTIC-COLOR (DB 48885-Colours); Hesse PU Hardener (DR 4075)	
5	Water base – Multi colored coating. Coatings (other than paint). (For Interior Applications)	Hesse COOL-COLOR (HB 65285) Color Tone	VOC (Al Sa'fat-DGBS limit is Max. = 100 g/l)
6	Solvent base - Interior /exterior trim varnishes and wood stains, including opaque wood stain (For Interior Applications)	Proterra NATURAL-SOLID-OIL (GE 11254)	VOC (Al Sa'fat-DGBS limit is Max. = 400 g/l)

**DUBAI CENTRAL LABORATORY DEPARTMENT  
DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME**

**SCOPE OF CERTIFICATION  
FOR CERTIFICATE NO. CL15020251**

- NOTE 1: This document forms an integral part of the Certificate of Product Conformity bearing the same certificate number.
- NOTE 2: The above product shall bear the DCLD Conformity Mark.
- NOTE 3: As applicable, other properties in the product standard specification which were excluded in the specific rules as approved by the certification body authorized personnel are to be verified by the end user of the product (if needed).

**Original Issue Date : 03 – 08 - 2015**  
**Current Issue Date : 03 – 08 - 2025**  
**Valid Until : 02- 08 - 2026**



**ENG. MAJED AL SHAMSI**  
**CERTIFICATION AND QUALITY CONTROL OF PRODUCTS SECTION'S MANAGER**