



Paint Express: gloss resin solution EL 460-0028

Adding the gloss resin solution EL 460-0028 makes it possible to individually increase the gloss level of polyurethane coatings. Increasing the gloss level is possible in clear and in coloured polyurethane coating systems.

Higher gloss levels can be set locally from the existing gloss level of a polyurethane lacquer. The higher gloss level will therefore be available in a very short space of time, without waiting for delivery times.

Coloured lacquer example:

- UNA-COLOR DB 45245-(colour tone):
supplied gloss level 25, semi matt
(300 µm on test card Chromolux 700 A neutral without hardener; 60° angle)
- Mixture details for gloss level 40, silky gloss (300 µm on test card Chromolux 700 A neutral without hardener; 60° angle) = DBM 45247-(colour tone):
- 90 parts of UNA-COLOR DB 45245-(colour tone)
- 10 parts of gloss resin solution EL 460-0028

Special instructions:

- Mix the gloss resin solution well with the polyurethane lacquer.

Note:

This information is for advice and is based on the best knowledge available and careful research in line with current state of the art practice. This information cannot be held as legally binding. We also refer you to our terms and conditions of business.

The Material Safety Data Sheet according to the regulation (EC) No. 1907/2006 is available.