



Paint Express: Brushing additive EL 460-0048

Adding the Brushing additive EL 460-0048 to the normal UNA-COLOR coloured lacquer quality DB 45245-(colour tone), or to the Insulating filler DP 4791-9343, makes it possible to apply the coating systems discussed above with a brush.

By adding the brushing additive to these lacquers, a very good coverage of the substrate and a good filling of the surface is achieved when applying them by hand.

Mixture details:

- 85.0 parts UNA-COLOR DB 45245-(colour tone), or
PU Insulating filler DP 4791-9343
- 15.0 parts Brushing additive EL 460-0048

Special instructions:

- Mix the Brushing additive EL 460-0048 well with the coloured lacquer or filler and then mix the resulting product accordingly with hardener.
- Adding the brushing additive may increase the drying time and change the pot life.
- The modified lacquers should be applied up to 3 times with an application quantity of up to 150 g/m² per work step, but with a total quantity of no more than 350 g/m².

Note:

This information is for advice and is based on the best knowledge available and careful research in line with current state of the art practice. This information cannot be held as legally binding. We also refer you to our terms and conditions of business.

The Material Safety Data Sheet according to the regulation (EC) No. 1907/2006 is available.