

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse PU Glaze lacquer PEX DB 4259X-FT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	REACHSET 2001
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

	REACHSET 2003
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)	
Flam. Liq. 2	H225
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 2	H411

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

## Labelling according to regulation (EC) No 1272/2008

### Hazard pictograms



### Signal word

Danger

### Hazard statements

H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.

### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains	1-methoxy-2-propanol; Acid Yellow 220; Solvent Yellow 82; acetone
----------	---

### Supplemental information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

## 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### n-butyl acetate

CAS No.	123-86-4			
EINECS no.	204-658-1			
Registration no.	01-2119485493-29			
Concentration	>= 25	< 50	%	
Classification (Regulation (EC) No. 1272/2008)	Fam. Liq. 3	H226		
	STOT SE 3	H336		Nervous system
		EUH066		

#### 1-methoxy-2-propanol

CAS No.	107-98-2
EINECS no.	203-539-1

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Registration no. 01-2119457435-35  
Concentration  $\geq$  25 < 50 %  
Classification (Regulation (EC) No. 1272/2008)  
Flam. Liq. 3 H226  
STOT SE 3 H336 Nervous system

**acetone**

CAS No. 67-64-1  
EINECS no. 200-662-2  
Registration no. 01-2119471330-49  
Concentration  $\geq$  1 < 4 %  
Classification (Regulation (EC) No. 1272/2008)  
Flam. Liq. 2 H225  
Eye Irrit. 2 H319  
STOT SE 3 H336 Nervous system  
EUH066

**Acid Yellow 220**

CAS No. 70851-34-2  
EINECS no. 274-929-7  
Concentration  $\geq$  3 < 4 %  
Classification (Regulation (EC) No. 1272/2008)  
Eye Irrit. 2 H319  
Skin Sens. 1 H317  
Aquatic Acute 1 H400  
Aquatic Chronic 1 H410

**xylene**

CAS No. 1330-20-7  
EINECS no. 215-535-7  
Registration no. 01-2119488216-32  
Concentration  $\geq$  1 < 2 %  
Classification (Regulation (EC) No. 1272/2008)  
Flam. Liq. 3 H226  
Acute Tox. 4 H332 Route of exposure: Inhalation exposure  
Acute Tox. 4 H312 Route of exposure: Dermal exposure  
Skin Irrit. 2 H315  
Asp. Tox. 1 H304  
STOT SE 3 H335 Respiratory tract; Route of exposure: inhalative  
Eye Irrit. 2 H319

ATE Dermal exposure 2.000 mg/kg  
ATE Inhalation exposure, Dust/Mist 5 mg/l

**isobutyl acetate**

CAS No. 110-19-0  
EINECS no. 203-745-1  
Registration no. 01-2119488971-22  
Concentration  $\geq$  1 < 10 %  
Classification (Regulation (EC) No. 1272/2008)  
Flam. Liq. 2 H225

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

STOT SE 3

H336  
EUH066

Nervous system

#### Hydrocarbons, C9, aromatics

CAS No. 128601-23-0

EINECS no. 918-668-5

Registration no. 01-2119455851-35

Concentration  $\geq 1$  < 3 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226

Asp. Tox. 1 H304

Aquatic Chronic 2 H411

STOT SE 3 H335

STOT SE 3 H336 Respiratory tract

EUH066 Nervous system

#### Solvent Yellow 82

CAS No. 85029-58-9

EINECS no. 285-083-3

Registration no. 01-2120756276-48

Concentration  $\geq 0,1$  < 1 %

Classification (Regulation (EC) No. 1272/2008)

Aquatic Chronic 2 H411

Skin Sens. 1B H317

#### Solvent Red 122

CAS No. 12227-55-3

Concentration  $\geq 0,1$  < 0,3 %

Classification (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400

Aquatic Chronic 1 H410

#### toluene

CAS No. 108-88-3

EINECS no. 203-625-9

Registration no. 01-2119471310-51

Concentration  $\geq 0,1$  < 1 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225

Repr. 2 H361d

Asp. Tox. 1 H304

STOT RE 2 H373

Skin Irrit. 2 H315

STOT SE 3 H336 Nervous system

#### cellulose nitrate $\leq 12.6$ % N

CAS No. 9004-70-0

Classification (Regulation (EC) No. 1272/2008)

Expl. 1.1 H201

#### Note

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

If unconscious place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical attention. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### Other information

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Standard procedure for chemical fires.

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Storage classes

Storage class according to TRGS 510      3      Flammable liquid

#### Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

smoking. Store in accordance with the particular national regulations.

### 7.3. Specific end use(s)

See exposure scenario, if available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### 1-methoxy-2-propanol

List	Directive 2017/164 EG			
Value	375	mg/m <sup>3</sup>	100	ppm(V)
Short term exposure limit	568	mg/m <sup>3</sup>	150	ppm(V)
Skin resorption / sensibilisation: H; Status: 12/2009				

##### 1-methoxy-2-propanol

List	EH40			
Value	375	mg/m <sup>3</sup>	100	ppm(V)
Short term exposure limit	560	mg/m <sup>3</sup>	150	ppm(V)
Skin resorption / sensibilisation: Sk; Status: 01/2020				

##### acetone

List	Directive 2017/164 EG			
Value	1210	mg/m <sup>3</sup>	500	ppm(V)
Status: 12/2009				

##### acetone

List	EH40			
Value	1210	mg/m <sup>3</sup>	500	ppm(V)
Short term exposure limit	3620	mg/m <sup>3</sup>	1500	ppm(V)
Status: 01/2020				

##### n-butyl acetate

List	EH40			
Value	724	mg/m <sup>3</sup>	150	ppm(V)
Short term exposure limit	966	mg/m <sup>3</sup>	200	ppm(V)
Status: 01/2020				

##### n-butyl acetate

List	Directive 2017/164 EG			
Value	241	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	723	mg/m <sup>3</sup>	150	ppm(V)
Status: 10/2019				

##### xylene

List	Directive 2017/164 EG			
Value	221	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	442	mg/m <sup>3</sup>	100	ppm(V)
Skin resorption / sensibilisation: H; Status: 12/2009				

##### xylene

List	EH40			
Value	220	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	441	mg/m <sup>3</sup>	100	ppm(V)
Skin resorption / sensibilisation: Sk; Status: 01/2020				

#### Hydrocarbons, C9, aromatics

List	EH40			
------	------	--	--	--



Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Value 500 mg/m<sup>3</sup>

Status: 01/2020

**isobutyl acetate**

List EH40

Value 724 mg/m<sup>3</sup> 150 ppm(V)

Short term exposure limit 903 mg/m<sup>3</sup> 187 ppm(V)

Status: 01/2020

**isobutyl acetate**

List Directive 2017/164 EG

Value 241 mg/m<sup>3</sup> 50 ppm(V)

Short term exposure limit 723 mg/m<sup>3</sup> 150 ppm(V)

Status: 10/2019

**Other information**

-

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

**1-methoxy-2-propanol**

Type of value Derived No Effect Level (DNEL)

Reference group Workers (industrial)

Duration of exposure Long-term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 369 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Workers (industrial)

Duration of exposure Long-term

Route of exposure Dermal exposure

Mode of action Systemic effects

Concentration 183 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 43,9 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure Dermal exposure

Mode of action Systemic effects

Concentration 78 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure Oral exposure

Mode of action Systemic effects

Concentration 33 mg/kg/d



Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

**acetone**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1210	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	186	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	2420	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1210	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	62	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	62	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	200	mg/m <sup>3</sup>

**n-butyl acetate**

Type of value	Derived No Effect Level (DNEL)
Reference group	Workers (professional)

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	600	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	600	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	6	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Specific effects	
Concentration	2	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	Dermal exposure	
Mode of action	Specific effects	
Concentration	6	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	Dermal exposure	
Mode of action	Specific effects	
Concentration	11	mg/kg/d

**xylene**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	125	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	212	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	65,3	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	260	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	174	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	442	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	221	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	289	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	289	mg/m <sup>3</sup>

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	12,5	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Local effects	
Concentration	174	mg/kg/d

#### Hydrocarbons, C9, aromatics

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	25	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	150	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32	mg/kg

#### toluene

Type of value	Derived No Effect Level (DNEL)	
---------------	--------------------------------	--

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	343	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	384	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	192	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	192	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	384	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	226	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	226	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Concentration	56,5	mg/m <sup>3</sup>
---------------	------	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Dermal exposure
-------------------	-----------------

Mode of action	Systemic effects
----------------	------------------

Concentration	226	mg/kg/d
---------------	-----	---------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Oral exposure
-------------------	---------------

Mode of action	Systemic effects
----------------	------------------

Concentration	8,13	mg/kg/d
---------------	------	---------

**isobutyl acetate**

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Workers (professional)
-----------------	------------------------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Dermal exposure
-------------------	-----------------

Mode of action	Systemic effects
----------------	------------------

Concentration	10	mg/kg/d
---------------	----	---------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Workers (professional)
-----------------	------------------------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Systemic effects
----------------	------------------

Concentration	300	mg/m <sup>3</sup>
---------------	-----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Workers (professional)
-----------------	------------------------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	300	mg/m <sup>3</sup>
---------------	-----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Dermal exposure
-------------------	-----------------

Mode of action	Systemic effects
----------------	------------------

Concentration	5	mg/kg/d
---------------	---	---------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Systemic effects
----------------	------------------

Concentration	35,7	mg/m <sup>3</sup>
---------------	------	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------



Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	600	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	600	mg/m <sup>3</sup>

### **Predicted No Effect Concentration (PNEC)**

#### **1-methoxy-2-propanol**

Type of value	PNEC	
Type	Freshwater	
Concentration	10	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	1	mg/l

Type of value	PNEC	
Conditions	sporadic release	
Concentration	100	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	52,3	mg/kg

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Type of value	PNEC	
Type	saltwater sediment	
Concentration	5,2	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	4,59	mg/kg

**acetone**

Type of value	PNEC	
Type	Freshwater	
Concentration	10,6	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	1,06	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	30,4	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	3,04	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	29,5	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

Type of value	PNEC	
Conditions	sporadic release	
Concentration	21	mg/l

**n-butyl acetate**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,18	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,018	mg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	35,6	mg/l

Type of value	PNEC	
Type	Water	
Conditions	sporadic release	



Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Concentration	0,36	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,981	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,0981	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	0,0903	mg/kg

**xylene**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,327	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,327	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	12,46	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	12,46	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,31	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	6,58	mg/l

**toluene**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,68	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	16,39	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,89	mg/kg
Type of value	PNEC	

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Type	Sewage treatment plant (STP)	
Concentration	13,61	mg/l
<b>isobutyl acetate</b>		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,17	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,017	mg/l
Type of value	PNEC	
Type	Water	
Conditions	sporadic release	
Concentration	0,34	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	200	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,877	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,0877	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,0755	mg/kg

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7 mm

Breakthrough time  $\geq$  30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### **Eye protection**

Wear eye glasses with side protection according to EN 166.

### **Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

**Physical state** liquid

**Colour** coloured

**Odour** solvent-like

#### **Melting point**

Remarks not determined

#### **Freezing point**

Remarks not determined

#### **Boiling point or initial boiling point and boiling range**

Value 55,8 to 200 °C

#### **Flammability**

not determined

#### **Upper and lower explosive limits**

Remarks not determined

#### **Flash point**

Value < 21,0 °C

#### **Ignition temperature**

Remarks not determined

#### **Decomposition temperature**

Remarks not determined

#### **Viscosity**

Remarks not determined

#### **Solubility(ies)**

Remarks not determined

#### **Partition coefficient n-octanol/water (log value)**

Remarks not determined

#### **Vapour pressure**

Remarks not determined

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

#### Density and/or relative density

Value	appr.	0,963		kg/l
Temperature		20	°C	

#### Relative vapour density

Remarks	not determined
---------	----------------

#### Particle characteristics

Remarks	not determined
---------	----------------

### 9.2. Other information

#### Odour threshold

Remarks	not determined
---------	----------------

#### Evaporation rate

Remarks	not determined
---------	----------------

#### Solubility in water

Remarks	not determined
---------	----------------

#### Efflux time

Value	30	to	30	s
Temperature	20	°C		
Method	DIN 53211 4 mm			

#### Explosive properties

evaluation	not determined
------------	----------------

#### Oxidising properties

Remarks	not determined
---------	----------------

#### Non-volatile content

Value	29	%
-------	----	---

#### Other information

This information is not available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

### 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NOx), dense black smoke, No decomposition if used as prescribed.

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Acute dermal toxicity

ATE	> 10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)	
Remarks	Based on available data, the classification criteria are not met.	

#### Acute dermal toxicity (Components)

##### xylene

ATE	2000	mg/kg
Source	alle Daten über 2000 mg/kg	

#### Acute inhalational toxicity

ATE	> 20	mg/l
Administration/Form	Dust/Mist	
Method	calculated value (Regulation (EC) No. 1272/2008)	
Remarks	Based on available data, the classification criteria are not met.	

#### Acute inhalative toxicity (Components)

##### xylene

ATE	5	mg/l
Duration of exposure	4	h
Administration/Form	Dust/Mist	
Source	alle Werte über 5 mg/l	

#### Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation (Components)

##### toluene

Species	rabbit	
Duration of exposure	4	h
Observation Period	7	d
evaluation	Irritating to skin.	
Method	EEC 84/449, B.4	
Source	1 (reliable without restriction)	

##### xylene

Species	rabbit	
Observation Period	72	h
evaluation	Irritating to skin.	
Source	2 (reliable with restrictions)	

#### Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation (Components)

##### acetone



Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Species rabbit  
Observation Period 24 h  
evaluation Irritating to eyes.  
Source 1 (reliable without restriction)

#### **xylene**

Species rabbit  
evaluation Irritating to eyes.  
Source 2 (reliable with restrictions)

#### **Acid Yellow 220**

evaluation Irritating to eyes.

#### **Sensitization**

evaluation May cause sensitization by skin contact.  
Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks The classification criteria are met.

#### **Sensitization (Components)**

##### **Solvent Yellow 82**

Species mouse  
evaluation May cause sensitization by skin contact.  
Source 1 (reliable without restriction)

##### **Acid Yellow 220**

evaluation May cause sensitization by skin contact.

#### **Mutagenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

#### **Reproduction toxicity (Components)**

##### **toluene**

evaluation Reproductive toxicity, Category 2

#### **Carcinogenicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

#### **Specific Target Organ Toxicity (STOT)**

##### **Single exposure**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks The classification criteria are met.  
evaluation May cause drowsiness or dizziness.

##### **Repeated exposure**

Remarks Based on available data, the classification criteria are not met.

#### **Specific Target Organ Toxicity (STOT) (Components)**

##### **1-methoxy-2-propanol**

##### **Specific target organ toxicity - single exposure**

Organs: Nervous system  
Remarks Possible narcotic effects (drowsiness, dizziness).

##### **acetone**

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

**Specific target organ toxicity - repeated exposure**

Remarks  
Organs: Nervous system  
Possible narcotic effects (drowsiness, dizziness).

**n-butyl acetate**

**Specific target organ toxicity - repeated exposure**

Remarks  
Organs: Nervous system  
Possible narcotic effects (drowsiness, dizziness).

**toluene**

**Specific target organ toxicity - single exposure**

Remarks  
Organs: Liver  
May cause damage to organs through prolonged or repeated exposure:

**toluene**

**Specific target organ toxicity - repeated exposure**

Remarks  
Organs: Nervous system  
Possible narcotic effects (drowsiness, dizziness).

**xylene**

**Specific target organ toxicity - single exposure**

Remarks  
Route of exposure inhalative  
Organs: Respiratory tract  
May cause respiratory irritation.

**Hydrocarbons, C9, aromatics**

**Specific target organ toxicity - single exposure**

Remarks  
Route of exposure inhalative  
Possible narcotic effects (drowsiness, dizziness).

**Hydrocarbons, C9, aromatics**

**Specific target organ toxicity - single exposure**

Remarks  
Possible narcotic effects (drowsiness, dizziness).

**isobutyl acetate**

**Specific target organ toxicity - repeated exposure**

Remarks  
Organs: Nervous system  
Possible narcotic effects (drowsiness, dizziness).

**Aspiration hazard**

Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

**Endocrine disrupting properties with respect to humans**

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

**Other information**

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

### Fish toxicity (Components)

#### Hydrocarbons, C9, aromatics

Species	Oncorhynchus mykiss (rainbow trout)		
LC50	9,2		mg/l
Duration of exposure	96	h	

#### Acid Yellow 220

Species	Danio rerio (zebra fish)		
EC50	< 1		mg/l
Duration of exposure	48	h	

### Daphnia toxicity (Components)

#### Hydrocarbons, C9, aromatics

Species	Daphnia magna (Water flea)		
EC50	3,2		mg/l
Duration of exposure	48	h	

#### Hydrocarbons, C9, aromatics

Species	Daphnia magna (Water flea)		
NOEC	2,14		mg/l
Duration of exposure	21	d	

#### Solvent Yellow 82

Species	Daphnia magna (Water flea)		
EC50	1		mg/l
Duration of exposure	2	d	

#### Solvent Red 122

Species	Daphnia magna (Water flea)		
EC50	< 0,1		mg/l
Duration of exposure	48	h	

### Algae toxicity (Components)

#### Hydrocarbons, C9, aromatics

Species	Pseudokirchneriella subcapitata (green algae)		
EC50	2,6	to 2,9	mg/l
Duration of exposure	72	h	

## 12.2. Persistence and degradability

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Biodegradability (Components)

#### Hydrocarbons, C9, aromatics

evaluation Readily biodegradable.

#### Solvent Yellow 82

Value	< 10		%
Duration of test evaluation	28	d	
Not readily biodegradable.			

## 12.3. Bioaccumulative potential

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Partition coefficient n-octanol/water (log value)

Remarks not determined

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

## 12.4. Mobility in soil

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Mobility in soil

no data available

## 12.5. Results of PBT and vPvB assessment

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

## 12.6 Endocrine disrupting properties

### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## 12.7. Other adverse effects

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances

EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### modified product

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances

EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

#### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT







Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

## SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT (Acid Yellow 220)	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	II	II	II
Special provision	640D		
Limited Quantity	5 I		
Transport category	2		
14.5. Environmental hazards	 ENVIRONMENTALLY HAZARDOUS	 ENVIRONMENTALLY HAZARDOUS	 ENVIRONMENTALLY HAZARDOUS

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU) appr. 73 % 698 g/l

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

EUH066

Repeated exposure may cause skin dryness or cracking.

H201

Explosive; mass explosion hazard.

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

### CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Expl. 1.1	Explosive, Division 1.1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, Category 1B
STOT RE 2	Specific target organ toxicity - repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### Abbreviations

Flam. Liq - Flammable liquids  
 RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer  
 (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
 IMDG - International Maritime Code for Dangerous Goods  
 IATA - International Air Transport Association  
 IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
 ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
 GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
 EINECS - European Inventory of Existing Commercial Chemical Substances  
 CAS - Chemical Abstracts Service (division of the American Chemical Society)  
 GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
 LOAEL - Lowest Observed Adverse Effect Level  
 LOEL - Lowest Observed Effect Level  
 NOAEL - No Observed Adverse Effect Level  
 NOEC - No Observed Effect Concentration  
 NOEL - No Observed Effect Level  
 OECD - Organisation for Economic Cooperation and Development  
 VOC - Volatile Organic Compounds  
 Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES003 - Professional uses: Non industrial spraying (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

### **Physical form**

liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 250

### **Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Volatile organic substances will volatilise into the atmospheric air inside.

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter soil, waterways or waste water canal.

Dispose of rinse water in accordance with local and national regulations.

### **Waste water**

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

### **Exhaust air**

Keep container closed. Avoid release to the environment.

### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

### **Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
----------------	--



Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

200127 - paint, inks, adhesives and resins containing  
dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### modified product

EWC waste code

080113 - sludges from paint or varnish containing organic  
solvents or other dangerous substances

080115 - aqueous sludges containing paint or varnish  
containing organic solvents or other dangerous substances

#### Dried residues

EWC waste code

080112 - waste lacquers and waste paint except those falling  
under 080111

#### Disposal recommendations for packaging

EWC waste code

150110 - packaging containing residues of or contaminated  
by dangerous substances

Completely emptied packagings can be given for recycling.

### **Contributing exposure scenario controlling worker exposure (professional)**

#### Short title of the exposure scenario

Substance number: CES006

#### Use

SU22

Professional uses: Public domain (administration, education, entertainment,  
services, craftsmen)

PROC11

Non industrial spraying

#### Physical form

liquid

#### Maximum amount used per time or activity

Duration of exposure

<= 8 h/d

Frequency of exposure

<= 220 d/a

#### Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Volatile organic substances will volatilise into the atmospheric air inside.

Read attached instructions before use.

#### Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

#### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

#### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material

Fluorinated rubber / butyl-rubber

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Material thickness  $\geq$  0,7

Breakthrough time  $\geq$  30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	Long-term inhalative
Exposure assessment	242 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	n-butyl acetate

### Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - systemic
Exposure assessment	262,79 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,71
Lead substance	1-methoxy-2-propanol

### Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	5,49 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,11
Lead substance	1-methoxy-2-propanol

### Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic
	Indoor use
Exposure assessment	37,54 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Risk characterisation ratio (RCR) 0,1  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method dermal, long-term - systemic  
Indoor use  
Exposure assessment 2,14 mg/kg/d  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,04  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method inhalation, long-term - systemic  
Outdoor use  
Exposure assessment 131,4 mg/m<sup>3</sup>  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,36  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method dermal, long-term - systemic  
Outdoor use  
Exposure assessment 21,43 mg/kg/d  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,42  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC13  
Assessment method inhalation, long-term - systemic  
Indoor use  
Exposure assessment 262,79 mg/m<sup>3</sup>  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,71  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC13  
Assessment method dermal, long-term - systemic  
Indoor use  
Exposure assessment 13,71 mg/kg/d  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,27  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC10

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Assessment method	inhalation, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,1
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - systemic
Risk characterisation ratio (RCR)	0,75
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - systemic
Exposure assessment	200 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,6
Lead substance	acetone

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,15
Lead substance	acetone

**Workers (professional)**

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

SU  
PROC  
Assessment method  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
inhalation, long-term - systemic  
200 mg/m<sup>3</sup>  
ECETOC TRA  
0,4  
acetone

**Workers (professional)**

SU  
PROC  
Assessment method  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
dermal, long-term - systemic  
62 mg/kg/d  
ECETOC TRA  
0,01  
acetone

**Workers (professional)**

SU  
PROC  
Assessment method  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC13  
inhalation, long-term - systemic  
200 mg/m<sup>3</sup>  
ECETOC TRA  
0,5  
acetone

**Workers (professional)**

SU  
PROC  
Assessment method  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC13  
dermal, long-term - systemic  
62 mg/kg/d  
ECETOC TRA  
0,07  
acetone

**Workers (professional)**

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC10  
inhalative  
Indoor use  
0,05 mg/m<sup>3</sup>  
ECETOC TRA  
0,172  
xylene

**Workers (professional)**

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
inhalative  
Indoor use  
0,1 mg/m<sup>3</sup>  
ECETOC TRA  
0,34  
xylene

**Workers (professional)**

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

SU	SU22
PROC	PROC13
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene
SU	SU22
PROC	PROC10
Assessment method	Long-term
	inhalative
Exposure assessment	185,25 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5976
Lead substance	2-methylpropan-1-ol
SU	SU22
PROC	PROC11
Assessment method	Long-term
	inhalative
Exposure assessment	256,1 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,8261
Lead substance	2-methylpropan-1-ol
SU	SU22
PROC	PROC13
Assessment method	Long-term
	inhalative
Exposure assessment	185,25 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5976
Lead substance	2-methylpropan-1-ol

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES004 - Professional uses: roller application or brushing, dipping and pouring and other processing without aerosol formation (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring
PROCh01	Other processing without aerosol formation

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

### **Physical form**

liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 250

### **Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

### **Waste water**

Do not discharge into the drains/surface waters/groundwater.

### **Exhaust air**

Keep container closed. Avoid release to the environment.

### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

### **Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

### **modified product**

EWC waste code	080113 - sludges from paint or varnish containing organic solvents or other dangerous substances
	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

### **Dried residues**

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

### **Disposal recommendations for packaging**

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
----------------	---

Completely emptied packagings can be given for recycling.

## **Contributing exposure scenario controlling worker exposure (professional)**

### **Short title of the exposure scenario**



Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Substance number: CES008

### Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring
PROCh01	Other processing without aerosol formation

### Physical form

liquid

### Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

### Other relevant operational conditions

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Read attached instructions before use.

### Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness >= 0,7

Breakthrough time >= 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

### Exposure estimation and reference to its source

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	Long-term inhalative
Exposure assessment	242 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	n-butyl acetate

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - systemic
Exposure assessment	262,79 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,71
Lead substance	1-methoxy-2-propanol

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	5,49 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,11
Lead substance	1-methoxy-2-propanol

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic Indoor use
Exposure assessment	37,54 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,1
Lead substance	1-methoxy-2-propanol

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic Indoor use
Exposure assessment	2,14 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,04
Lead substance	1-methoxy-2-propanol

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic Outdoor use
Exposure assessment	131,4 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Risk characterisation ratio (RCR) 0,36  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method dermal, long-term - systemic  
Outdoor use  
Exposure assessment 21,43 mg/kg/d  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,42  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC13  
Assessment method inhalation, long-term - systemic  
Indoor use  
Exposure assessment 262,79 mg/m<sup>3</sup>  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,71  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC13  
Assessment method dermal, long-term - systemic  
Indoor use  
Exposure assessment 13,71 mg/kg/d  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,27  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method inhalation, long-term - systemic  
Risk characterisation ratio (RCR) 0,5  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method dermal, long-term - systemic  
Risk characterisation ratio (RCR) 0,1  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method inhalation, long-term - systemic  
Risk characterisation ratio (RCR) 0,5  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC11

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - systemic
Risk characterisation ratio (RCR)	0,75
Lead substance	4-methylpentan-2-one
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - systemic
Exposure assessment	200 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,6
Lead substance	acetone
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,15
Lead substance	acetone
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic
Exposure assessment	200 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,4
Lead substance	acetone
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,01
Lead substance	acetone
<b>Workers (professional)</b>	
SU	SU22
PROC	PROC13

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Assessment method	inhalation, long-term - systemic
Exposure assessment	200 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5
Lead substance	acetone

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - systemic
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,07
Lead substance	acetone

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene

SU	SU22
PROC	PROC10
Assessment method	Long-term
	inhalative
Exposure assessment	185,25 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5976
Lead substance	2-methylpropan-1-ol
SU	SU22
PROC	PROC11
Assessment method	Long-term

Trade name: Hesse PU Glaze lacquer PEX DB 4259X-FT

Version: 31 / GB

Revision: 12.12.2022

Replaces Version: 30 / GB

Print date: 16.01.23

Exposure assessment	inhalative
Exposure assessment (method)	256,1 mg/m <sup>3</sup>
Risk characterisation ratio (RCR)	ECETOC TRA
Lead substance	0,8261
SU	2-methylpropan-1-ol
PROC	SU22
Assessment method	PROC13
	Long-term
	inhalative
Exposure assessment	185,25 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5976
Lead substance	2-methylpropan-1-ol

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.