

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse UNA-COLOR, silk matt PEX DB 555-FT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	REACHSET 1000
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

	REACHSET 1001
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC13	Treatment of articles by dipping and pouring

	REACHSET 2001
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

	REACHSET 2003
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2 H225

STOT SE 3 H336

Aquatic Chronic 3 H412

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008

For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

##### Hazard pictograms



##### Signal word

Danger

##### Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

##### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

##### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains n-butyl acetate; 2-methoxy-1-methylethyl acetate; isobutyl acetate; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

EUH208 Contains 12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide, May produce an allergic reaction.

##### Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### n-butyl acetate

CAS No.	123-86-4			
EINECS no.	204-658-1			
Registration no.	01-2119485493-29			
Concentration	>= 25	<	50	%
Classification (Regulation (EC) No. 1272/2008)				
	Flam. Liq. 3		H226	
	STOT SE 3		H336	Nervous system
			EUH066	

#### 2-methoxy-1-methylethyl acetate

CAS No.	108-65-6			
EINECS no.	203-603-9			
Registration no.	01-2119475791-29			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)				
	Flam. Liq. 3		H226	
	STOT SE 3		H336	

#### isobutyl acetate

CAS No.	110-19-0			
EINECS no.	203-745-1			
Registration no.	01-2119488971-22			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)				
	Flam. Liq. 2		H225	
	STOT SE 3		H336	Nervous system
			EUH066	

#### Hydrocarbons, C9, aromatics

CAS No.	128601-23-0			
EINECS no.	918-668-5			
Registration no.	01-2119455851-35			
Concentration	>= 1	<	3	%
Classification (Regulation (EC) No. 1272/2008)				
	Flam. Liq. 3		H226	
	Asp. Tox. 1		H304	
	Aquatic Chronic 2		H411	
	STOT SE 3		H335	Respiratory tract
	STOT SE 3		H336	Nervous system
			EUH066	

#### xylene

CAS No.	1330-20-7			
EINECS no.	215-535-7			
Registration no.	01-2119488216-32			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)				

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Flam. Liq. 3	H226	Route of exposure: Inhalation exposure
Acute Tox. 4	H332	
Acute Tox. 4	H312	Route of exposure: Dermal exposure
Skin Irrit. 2	H315	
Asp. Tox. 1	H304	Respiratory tract; Route of exposure: inhalative
STOT SE 3	H335	
Eye Irrit. 2	H319	

ATE	Dermal exposure	2.000	mg/kg
ATE	Inhalation exposure, Dust/Mist	5	mg/l

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

CAS No.	64742-48-9			
EINECS no.	919-857-5			
Registration no.	01-2119463258-33			
Concentration	>= 1	< 10	%	
Classification (Regulation (EC) No. 1272/2008)				
	Flam. Liq. 3	H226		
	Asp. Tox. 1	H304		
	STOT SE 3	H336		Nervous system
		EUH066		

**12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide**

EINECS no.	434-430-9			
Registration no.	01-0000018057-71			
Concentration	>= 0,1	< 1	%	
Classification (Regulation (EC) No. 1272/2008)				
	Skin Sens. 1	H317		
	Aquatic Chronic 4	H413		

**cellulose nitrate < =12.6 % N**

CAS No.	9004-70-0			
Classification (Regulation (EC) No. 1272/2008)				
	Expl. 1.1	H201		

**Note**

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

If unconscious place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical attention. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

**After ingestion**

Do not induce vomiting. Take medical treatment.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Hints for the physician / treatment**

Treat symptomatically.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

**Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

**Other information**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Standard procedure for chemical fires.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

**6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

#### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

##### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

##### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

##### Storage classes

Storage class according to TRGS 510      3      Flammable liquid

##### Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

#### 7.3. Specific end use(s)

See exposure scenario, if available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limit values

###### n-butyl acetate

List	EH40			
Value	724	mg/m <sup>3</sup>	150	ppm(V)
Short term exposure limit	966	mg/m <sup>3</sup>	200	ppm(V)

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Status: 01/2020

**n-butyl acetate**

List	Directive 2017/164 EG			
Value	241	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	723	mg/m <sup>3</sup>	150	ppm(V)

Status: 10/2019

**2-methoxy-1-methylethyl acetate**

List	Directive 2017/164 EG			
Value	275	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	550	mg/m <sup>3</sup>	100	ppm(V)

Status: 12/2009

**2-methoxy-1-methylethyl acetate**

List	EH40			
Value	274	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	548	mg/m <sup>3</sup>	100	ppm(V)

Skin resorption / sensibilisation: Sk; Status: 01/2020

**xylene**

List	Directive 2017/164 EG			
Value	221	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	442	mg/m <sup>3</sup>	100	ppm(V)

Skin resorption / sensibilisation: H; Status: 12/2009

**xylene**

List	EH40			
Value	220	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	441	mg/m <sup>3</sup>	100	ppm(V)

Skin resorption / sensibilisation: Sk; Status: 01/2020

**Hydrocarbons, C9, aromatics**

List	EH40			
Value	500	mg/m <sup>3</sup>		

Status: 01/2020

**isobutyl acetate**

List	EH40			
Value	724	mg/m <sup>3</sup>	150	ppm(V)
Short term exposure limit	903	mg/m <sup>3</sup>	187	ppm(V)

Status: 01/2020

**isobutyl acetate**

List	Directive 2017/164 EG			
Value	241	mg/m <sup>3</sup>	50	ppm(V)
Short term exposure limit	723	mg/m <sup>3</sup>	150	ppm(V)

Status: 10/2019

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

List	EH40			
Value	1200	mg/m <sup>3</sup>		

Status: 01/2020

**Other information**

-

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

**2-methoxy-1-methylethyl acetate**

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	275	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	153,5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	1,67	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	33	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	54,8	mg/kg
<b>n-butyl acetate</b>		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	600	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Mode of action	Local effects	
Concentration	600	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	6	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Specific effects	
Concentration	2	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	Dermal exposure	
Mode of action	Specific effects	
Concentration	6	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	Dermal exposure	
Mode of action	Specific effects	
Concentration	11	mg/kg/d

#### **xylene**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	125	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	212	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	65,3	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Mode of action	Systemic effects	
Concentration	260	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	174	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	442	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	221	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	289	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	289	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	12,5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Local effects	
Concentration	174	mg/kg/d

**Hydrocarbons, C9, aromatics**

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	25	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	150	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32	mg/kg

**isobutyl acetate**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	10	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	600	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	600	mg/m <sup>3</sup>

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

#### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Concentration	125	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Concentration	208	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Concentration	125	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Concentration	871	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Concentration	185	mg/kg

#### **Predicted No Effect Concentration (PNEC)**

##### **2-methoxy-1-methylethyl acetate**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,635	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,0635	mg/l

Type of value	PNEC	
Conditions	sporadic release	
Concentration	6,35	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	3,29	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,329	mg/kg

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Type of value	PNEC	
Type	Soil	
Concentration	0,29	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

**n-butyl acetate**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,18	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,018	mg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	35,6	mg/l

Type of value	PNEC	
Type	Water	
Conditions	sporadic release	
Concentration	0,36	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,981	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,0981	mg/l

Type of value	PNEC	
Type	Soil	
Concentration	0,0903	mg/kg

**xylene**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,327	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,327	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	12,46	mg/kg

Type of value	PNEC	
---------------	------	--



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Type	saltwater sediment	
Concentration	12,46	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	2,31	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	6,58	mg/l

#### **isobutyl acetate**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,17	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,017	mg/l

Type of value	PNEC	
Type	Water	
Conditions	sporadic release	
Concentration	0,34	mg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	200	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,877	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,0877	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	0,0755	mg/kg

## **8.2. Exposure controls**

### **Exposure controls**

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### **Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

## Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7 mm

Breakthrough time  $\geq$  30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

## Eye protection

Wear eye glasses with side protection according to EN 166.

## Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** liquid

**Colour** coloured

**Odour** ester-like

#### Melting point

Remarks not determined

#### Freezing point

Remarks not determined

#### Boiling point or initial boiling point and boiling range

Value 82 to 200 °C

#### Flammability

not determined

#### Upper and lower explosive limits

Lower explosion limit 0,8 %(V)

#### Flash point

Value 21 to 22 °C

#### Ignition temperature

Remarks not determined

#### Decomposition temperature

Remarks not determined

#### Viscosity

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Remarks not determined

#### **Solubility(ies)**

Remarks not determined

#### **Partition coefficient n-octanol/water (log value)**

Remarks not determined

#### **Vapour pressure**

Value < 1000 hPa

#### **Density and/or relative density**

Value appr. 1,007 kg/l  
Temperature 20 °C

#### **Relative vapour density**

Remarks not determined

#### **Particle characteristics**

Remarks not determined

### **9.2. Other information**

#### **Odour threshold**

Remarks not determined

#### **Evaporation rate**

Remarks not determined

#### **Solubility in water**

Remarks not determined

#### **Efflux time**

Value 27 to 63 s  
Temperature 20 °C  
Method DIN 53211 4 mm

#### **Explosive properties**

evaluation not determined

#### **Oxidising properties**

Remarks not determined

#### **Non-volatile content**

Value 36 %

#### **Other information**

This information is not available.

## **SECTION 10: Stability and reactivity**

### **10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

### **10.2. Chemical stability**

Stable under normal conditions.

### **10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

### **10.4. Conditions to avoid**

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Isolate from sources of heat, sparks and open flame.

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Acute dermal toxicity

ATE	> 10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)	
Remarks	Based on available data, the classification criteria are not met.	

#### Acute dermal toxicity (Components)

##### xylene

ATE	2000	mg/kg
Source	alle Daten über 2000 mg/kg	

#### Acute inhalational toxicity

ATE	> 20	mg/l
Administration/Form	Dust/Mist	
Method	calculated value (Regulation (EC) No. 1272/2008)	
Remarks	Based on available data, the classification criteria are not met.	

#### Acute inhalative toxicity (Components)

##### xylene

ATE	5	mg/l
Duration of exposure	4	h
Administration/Form	Dust/Mist	
Source	alle Werte über 5 mg/l	

#### Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation (Components)

##### xylene

Species	rabbit
Observation Period	72 h
evaluation	Irritating to skin.
Source	2 (reliable with restrictions)

#### Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation (Components)

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

#### **xylene**

Species	rabbit
evaluation	Irritating to eyes.
Source	2 (reliable with restrictions)

#### **Sensitization**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### **Sensitization (Components)**

##### **12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide**

evaluation	May cause sensitization by skin contact.
------------	--

#### **Mutagenicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### **Reproductive toxicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### **Carcinogenicity**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### **Specific Target Organ Toxicity (STOT)**

##### **Single exposure**

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	The classification criteria are met.
evaluation	May cause drowsiness or dizziness.

##### **Repeated exposure**

Remarks	Based on available data, the classification criteria are not met.
---------	---

#### **Specific Target Organ Toxicity (STOT) (Components)**

##### **n-butyl acetate**

##### **Specific target organ toxicity - repeated exposure**

	Organs: Nervous system
Remarks	Possible narcotic effects (drowsiness, dizziness).

##### **xylene**

##### **Specific target organ toxicity - single exposure**

	Route of exposure inhalative
	Organs: Respiratory tract
Remarks	May cause respiratory irritation.

##### **Hydrocarbons, C9, aromatics**

##### **Specific target organ toxicity - single exposure**

	Route of exposure inhalative
Remarks	Possible narcotic effects (drowsiness, dizziness).

##### **Hydrocarbons, C9, aromatics**

##### **Specific target organ toxicity - single exposure**

Remarks	Possible narcotic effects (drowsiness, dizziness).
---------	--

##### **2-methoxy-1-methylethyl acetate**

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

**Specific target organ toxicity - repeated exposure**

evaluation May cause drowsiness or dizziness.  
Organs: Nervous system

**isobutyl acetate**

**Specific target organ toxicity - repeated exposure**

Organs: Nervous system  
Remarks Possible narcotic effects (drowsiness, dizziness).

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

**Specific target organ toxicity - repeated exposure**

Organs: Nervous system  
Remarks Possible narcotic effects (drowsiness, dizziness).

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**11.2 Information on other hazards**

**Endocrine disrupting properties with respect to humans**

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

**Other information**

No toxicological data are available.

**SECTION 12: Ecological information**

**12.1. Toxicity**

**General information**

For this subsection there is no ecotoxicological data available on the product as such.

**Fish toxicity (Components)**

**Hydrocarbons, C9, aromatics**

Species	Oncorhynchus mykiss (rainbow trout)		
LC50	9,2		mg/l
Duration of exposure	96	h	

**Daphnia toxicity (Components)**

**Hydrocarbons, C9, aromatics**

Species	Daphnia magna (Water flea)		
EC50	3,2		mg/l
Duration of exposure	48	h	

**Hydrocarbons, C9, aromatics**

Species	Daphnia magna (Water flea)		
NOEC	2,14		mg/l
Duration of exposure	21	d	

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Species	Daphnia magna (Water flea)		
EC50	22	46	mg/l
Duration of exposure	48	h	
Method	OECD 202, part 1, static		

**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Species	Daphnia magna (Water flea)		
---------	----------------------------	--	--

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

NOELR	0,23	mg/l
Duration of exposure	21	d
Method	QSAR modelled data	

### Algae toxicity (Components)

#### Hydrocarbons, C9, aromatics

Species	Pseudokirchneriella subcapitata (green algae)		
EC50	2,6	to	2,9
Duration of exposure	72	h	mg/l

## 12.2. Persistence and degradability

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Biodegradability (Components)

#### Hydrocarbons, C9, aromatics

evaluation	Readily biodegradable.
------------	------------------------

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Value	53,4	%
Duration of test	28	d
evaluation	Not readily biodegradable.	

## 12.3. Bioaccumulative potential

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Partition coefficient n-octanol/water (log value)

Remarks	not determined
---------	----------------

## 12.4. Mobility in soil

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Mobility in soil

no data available

## 12.5. Results of PBT and vPvB assessment

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Results of PBT and vPvB assessment

The product contains no PBT substances  
The product contains no vPvB substances.

## 12.6 Endocrine disrupting properties

### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## 12.7. Other adverse effects

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### General information / ecology





Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

For this subsection there is no ecotoxicological data available on the product as such.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
EWC waste code	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

#### **modified product**

EWC waste code	080113 - sludges from paint or varnish containing organic solvents or other dangerous substances
EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### **Dried residues**

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

#### **Disposal recommendations for packaging**

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
----------------	---

Completely emptied packagings can be given for recycling.

## **SECTION 14: Transport information**




Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	II	II	II
Special provision	640D		
Limited Quantity	5 l		
Transport category	2		
14.5. Environmental hazards		no	

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU)                      appr.    64                      %                      658                      g/l

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

EUH066	Repeated exposure may cause skin dryness or cracking.
H201	Explosive; mass explosion hazard.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

### **CLP categories listed in Chapter 3**

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Expl. 1.1	Explosive, Division 1.1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### **Abbreviations**

Flam. Liq - Flammable liquids  
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG - International Maritime Code for Dangerous Goods  
IATA - International Air Transport Association  
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS - European Inventory of Existing Commercial Chemical Substances  
CAS - Chemical Abstracts Service (division of the American Chemical Society)  
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL - Lowest Observed Adverse Effect Level  
LOEL - Lowest Observed Effect Level  
NOAEL - No Observed Adverse Effect Level  
NOEC - No Observed Effect Concentration  
NOEL - No Observed Effect Level  
OECD - Organisation for Economic Cooperation and Development  
VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

## **Annex to the extended Safety Data Sheet (eSDS)**

**Short title of the exposure scenario**

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

ES001 - Industrial applications: industrial spraying (inside)

### Use of the substance/preparation

Surface treatment of wood and other materials

#### Use

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

### Contributing exposure scenario controlling environmental exposure

#### Use

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix

#### Physical form

liquid

#### Hazardous ingredients

##### n-butyl acetate

CAS No.	123-86-4
EINECS no.	204-658-1
Registration no.	01-2119485493-29
Concentration	>= 25 < 50 %

##### 2-methoxy-1-methylethyl acetate

CAS No.	108-65-6
EINECS no.	203-603-9
Registration no.	01-2119475791-29
Concentration	>= 1 < 10 %

##### 4-methylpentan-2-one

CAS No.	108-10-1
EINECS no.	203-550-1
Registration no.	01-2119473980-30
Concentration	>= 1 < 10 %

##### xylene

CAS No.	1330-20-7
EINECS no.	215-535-7
Registration no.	01-2119488216-32
Concentration	>= 1 < 10 %

##### ethylbenzene

CAS No.	100-41-4
EINECS no.	202-849-4
Registration no.	01-2119489370-35
Concentration	>= 1 < 10 %

##### Hydrocarbons, C9, aromatics

CAS No.	128601-23-0
EINECS no.	918-668-5
Registration no.	01-2119455851-35
Concentration	>= 1 < 10 %

#### Maximum amount used per time or activity

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Emission days per site: <= 300

### Other relevant operational conditions

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

### Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

### Exhaust air

Keep container closed. Avoid release to the environment.

### Soil

Floors should be impervious, resistant to liquids and easy to clean.

### Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances  
200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

### modified product

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances  
080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

## Contributing exposure scenario controlling worker exposure

### Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
PROC7 Industrial spraying

### Physical form

liquid

### Hazardous ingredients

#### n-butyl acetate

CAS No. 123-86-4  
EINECS no. 204-658-1  
Registration no. 01-2119485493-29  
Concentration >= 25 < 50 %

#### 2-methoxy-1-methylethyl acetate

CAS No. 108-65-6

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

EINECS no. 203-603-9  
Registration no. 01-2119475791-29  
Concentration  $\geq 1$  < 10 %

**4-methylpentan-2-one**

CAS No. 108-10-1  
EINECS no. 203-550-1  
Registration no. 01-2119473980-30  
Concentration  $\geq 1$  < 10 %

**xylene**

CAS No. 1330-20-7  
EINECS no. 215-535-7  
Registration no. 01-2119488216-32  
Concentration  $\geq 1$  < 10 %

**ethylbenzene**

CAS No. 100-41-4  
EINECS no. 202-849-4  
Registration no. 01-2119489370-35  
Concentration  $\geq 1$  < 10 %

**Hydrocarbons, C9, aromatics**

CAS No. 128601-23-0  
EINECS no. 918-668-5  
Registration no. 01-2119455851-35  
Concentration  $\geq 1$  < 10 %

**Maximum amount used per time or activity**

Duration of exposure  $\leq 8$  h/d  
Frequency of exposure  $\leq 220$  d/a

**Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Read attached instructions before use.

**Product substance and product safety related measures**

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

**Hand protection**

Protective gloves complying with EN 374.  
Glove material  
Multilayer gloves made from  
Appropriate Material Fluorinated rubber / butyl-rubber  
Material thickness  $\geq 0,7$   
Breakthrough time  $\geq 30$

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	27,54 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,1
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	dermal, long-term - local and systemic
Exposure assessment	2,14 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,01
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	55,08 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,2
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	dermal, long-term - local and systemic
Exposure assessment	27,43 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,18
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC13
Assessment method	inhalation, long-term - local and systemic



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Exposure assessment	55,08	mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,2	
Lead substance	2-methoxy-1-methylethyl acetate	

**Workers (industrial)**

SU	SU3	
PROC	PROC13	
Assessment method	dermal, long-term - local and systemic	
Exposure assessment	13,71	mg/kg/d
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,09	
Lead substance	2-methoxy-1-methylethyl acetate	

**Workers (industrial)**

PROC	PROC7	
Assessment method	inhalation, long-term - local and systemic	
	Indoor use	
Exposure assessment	60,5	mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,126	
Lead substance	n-butyl acetate	

**Workers (industrial)**

PROC	PROC10	
Assessment method	inhalation, long-term - systemic	
	Indoor use	
Exposure assessment	242	mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,504	
Lead substance	n-butyl acetate	

**Workers (industrial)**

PROC	PROC10	
Assessment method	inhalation, long-term - systemic	
	Outdoor use	
Exposure assessment	242	mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,504	
Lead substance	n-butyl acetate	

**Workers (industrial)**

PROC	PROC13	
Assessment method	inhalation, long-term - systemic	
	Indoor use	
Exposure assessment	242	mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA	
Risk characterisation ratio (RCR)	0,504	
Lead substance	n-butyl acetate	

**Workers (industrial)**

PROC	PROC13	
Assessment method	inhalation, long-term - systemic	
	Outdoor use	
Exposure assessment	242	mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA	

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Risk characterisation ratio (RCR)

0,504

Lead substance

n-butyl acetate

**Workers (industrial)**

SU

SU3

PROC

PROC7

Assessment method

inhalation, long-term - systemic

Indoor use

Risk characterisation ratio (RCR)

0,75

Lead substance

4-methylpentan-2-one

**Workers (industrial)**

SU

SU3

PROC

PROC7

Assessment method

dermal, long-term - systemic

Indoor use

Risk characterisation ratio (RCR)

0,5

Lead substance

4-methylpentan-2-one

**Workers (industrial)**

SU

SU3

PROC

PROC10

Assessment method

inhalation, long-term - systemic

Indoor use

Risk characterisation ratio (RCR)

0,5

Lead substance

4-methylpentan-2-one

**Workers (industrial)**

SU

SU3

PROC

PROC10

Assessment method

dermal, long-term - systemic

Risk characterisation ratio (RCR)

0,5

Lead substance

4-methylpentan-2-one

**Workers (industrial)**

SU

SU3

PROC

PROC13

Assessment method

inhalation, long-term - systemic

Risk characterisation ratio (RCR)

0,5

Lead substance

4-methylpentan-2-one

**Workers (industrial)**

SU

SU3

PROC

PROC13

Assessment method

dermal, long-term - systemic

Risk characterisation ratio (RCR)

0,5

Lead substance

4-methylpentan-2-one

**Workers (industrial)**

SU

SU3

PROC

PROC7

Assessment method

inhalative

Indoor use

Exposure assessment

0,1 mg/m<sup>3</sup>

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,34

Lead substance

xylene

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

#### Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene

#### Workers (industrial)

SU	SU3
PROC	PROC13
Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene

## Information on estimated exposure and downstream-user guidance

### Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

## Annex to the extended Safety Data Sheet (eSDS)

### Short title of the exposure scenario

ES002 - Industrial applications: rolling, dipping, pouring and other processing without aerosol formation (inside)

### Use of the substance/preparation

Surface treatment of wood and other materials

### Use

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROCh02	roller coating industrial
PROC13	Treatment of articles by dipping and pouring

## Contributing exposure scenario controlling environmental exposure

### Use

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix

**Physical form** liquid

### Hazardous ingredients

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

**n-butyl acetate**

CAS No.	123-86-4			
EINECS no.	204-658-1			
Registration no.	01-2119485493-29			
Concentration	>= 25	<	50	%

**2-methoxy-1-methylethyl acetate**

CAS No.	108-65-6			
EINECS no.	203-603-9			
Registration no.	01-2119475791-29			
Concentration	>= 1	<	10	%

**4-methylpentan-2-one**

CAS No.	108-10-1			
EINECS no.	203-550-1			
Registration no.	01-2119473980-30			
Concentration	>= 1	<	10	%

**xylene**

CAS No.	1330-20-7			
EINECS no.	215-535-7			
Registration no.	01-2119488216-32			
Concentration	>= 1	<	10	%

**ethylbenzene**

CAS No.	100-41-4			
EINECS no.	202-849-4			
Registration no.	01-2119489370-35			
Concentration	>= 1	<	10	%

**Hydrocarbons, C9, aromatics**

CAS No.	128601-23-0			
EINECS no.	918-668-5			
Registration no.	01-2119455851-35			
Concentration	>= 1	<	10	%

**Maximum amount used per time or activity**

Emission days per site:	<= 300
-------------------------	--------

**Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

**Waste water**

Do not discharge into the drains/surface waters/groundwater.

**Exhaust air**

Keep container closed. Avoid release to the environment.

**Soil**

Floors should be impervious, resistant to liquids and easy to clean.

**Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances 200127 - paint, inks, adhesives and resins containing
----------------	--

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

#### modified product

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances  
080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

#### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances  
Completely emptied packagings can be given for recycling.

### Contributing exposure scenario controlling worker exposure

#### Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
PROCh01 Other processing without aerosol formation  
PROCh02 roller coating industrial  
PROC13 Treatment of articles by dipping and pouring

#### Physical form

liquid

#### Hazardous ingredients

##### n-butyl acetate

CAS No.	123-86-4				
EINECS no.	204-658-1				
Registration no.	01-2119485493-29				
Concentration	>= 25	<	50	%	

##### 2-methoxy-1-methylethyl acetate

CAS No.	108-65-6				
EINECS no.	203-603-9				
Registration no.	01-2119475791-29				
Concentration	>= 1	<	10	%	

##### 4-methylpentan-2-one

CAS No.	108-10-1				
EINECS no.	203-550-1				
Registration no.	01-2119473980-30				
Concentration	>= 1	<	10	%	

##### xylene

CAS No.	1330-20-7				
EINECS no.	215-535-7				
Registration no.	01-2119488216-32				
Concentration	>= 1	<	10	%	

##### ethylbenzene

CAS No.	100-41-4				
EINECS no.	202-849-4				
Registration no.	01-2119489370-35				
Concentration	>= 1	<	10	%	

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

#### **Hydrocarbons, C9, aromatics**

CAS No. 128601-23-0

EINECS no. 918-668-5

Registration no. 01-2119455851-35

Concentration  $\geq 1$  < 10 %

#### **Maximum amount used per time or activity**

Duration of exposure  $\leq 8$  h/d

Frequency of exposure  $\leq 220$  d/a

#### **Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Read attached instructions before use.

#### **Product substance and product safety related measures**

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

#### **Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

#### **Hand protection**

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq 0,7$

Breakthrough time  $\geq 30$

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

#### **Eye protection**

Wear eye glasses with side protection according to EN 166.

#### **Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

#### **Exposure estimation and reference to its source**

##### **Workers (industrial)**

SU

SU3

PROC

PROC7

Assessment method

inhalation, long-term - local and systemic

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Exposure assessment 27,54 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,1  
Lead substance 2-methoxy-1-methylethyl acetate

**Workers (industrial)**

SU SU3  
PROC PROC7  
Assessment method dermal, long-term - local and systemic  
Exposure assessment 2,14 mg/kg/d  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,01  
Lead substance 2-methoxy-1-methylethyl acetate

**Workers (industrial)**

SU SU3  
PROC PROC10  
Assessment method inhalation, long-term - local and systemic  
Exposure assessment 55,08 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,2  
Lead substance 2-methoxy-1-methylethyl acetate

**Workers (industrial)**

SU SU3  
PROC PROC10  
Assessment method dermal, long-term - local and systemic  
Exposure assessment 27,43 mg/kg/d  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,18  
Lead substance 2-methoxy-1-methylethyl acetate

**Workers (industrial)**

SU SU3  
PROC PROC13  
Assessment method inhalation, long-term - local and systemic  
Exposure assessment 55,08 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,2  
Lead substance 2-methoxy-1-methylethyl acetate

**Workers (industrial)**

SU SU3  
PROC PROC13  
Assessment method dermal, long-term - local and systemic  
Exposure assessment 13,71 mg/kg/d  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,09  
Lead substance 2-methoxy-1-methylethyl acetate

**Workers (industrial)**

PROC PROC7  
Assessment method inhalation, long-term - local and systemic  
Indoor use  
Exposure assessment 60,5 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Risk characterisation ratio (RCR) 0,126  
Lead substance n-butyl acetate

**Workers (industrial)**

PROC PROC10  
Assessment method inhalation, long-term - systemic  
Indoor use  
Exposure assessment 242 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,504  
Lead substance n-butyl acetate

**Workers (industrial)**

PROC PROC10  
Assessment method inhalation, long-term - systemic  
Outdoor use  
Exposure assessment 242 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,504  
Lead substance n-butyl acetate

**Workers (industrial)**

PROC PROC13  
Assessment method inhalation, long-term - systemic  
Indoor use  
Exposure assessment 242 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,504  
Lead substance n-butyl acetate

**Workers (industrial)**

PROC PROC13  
Assessment method inhalation, long-term - systemic  
Outdoor use  
Exposure assessment 242 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,504  
Lead substance n-butyl acetate

**Workers (industrial)**

SU SU3  
PROC PROC7  
Assessment method inhalation, long-term - systemic  
Indoor use  
Risk characterisation ratio (RCR) 0,75  
Lead substance 4-methylpentan-2-one

**Workers (industrial)**

SU SU3  
PROC PROC7  
Assessment method dermal, long-term - systemic  
Indoor use  
Risk characterisation ratio (RCR) 0,5  
Lead substance 4-methylpentan-2-one

**Workers (industrial)**

SU SU3

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

PROC

Assessment method

Risk characterisation ratio (RCR)

Lead substance

**Workers (industrial)**

SU

PROC

Assessment method

Risk characterisation ratio (RCR)

Lead substance

**Workers (industrial)**

SU

PROC

Assessment method

Risk characterisation ratio (RCR)

Lead substance

**Workers (industrial)**

SU

PROC

Assessment method

Risk characterisation ratio (RCR)

Lead substance

**Workers (industrial)**

SU

PROC

Assessment method

Exposure assessment

Exposure assessment (method)

Risk characterisation ratio (RCR)

Lead substance

**Workers (industrial)**

SU

PROC

Assessment method

Exposure assessment

Exposure assessment (method)

Risk characterisation ratio (RCR)

Lead substance

**Workers (industrial)**

SU

PROC

Assessment method

Exposure assessment

Exposure assessment (method)

Risk characterisation ratio (RCR)

Lead substance

PROC10

inhalation, long-term - systemic

Indoor use

0,5

4-methylpentan-2-one

SU3

PROC10

dermal, long-term - systemic

0,5

4-methylpentan-2-one

SU3

PROC13

inhalation, long-term - systemic

0,5

4-methylpentan-2-one

SU3

PROC13

dermal, long-term - systemic

0,5

4-methylpentan-2-one

SU3

PROC7

inhalative

Indoor use

0,1 mg/m<sup>3</sup>

ECETOC TRA

0,34

xylene

SU3

PROC10

inhalative

Indoor use

0,05 mg/m<sup>3</sup>

ECETOC TRA

0,172

xylene

SU3

PROC13

inhalative

Indoor use

0,1 mg/m<sup>3</sup>

ECETOC TRA

0,34

xylene

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

## Information on estimated exposure and downstream-user guidance

### Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

## Annex to the extended Safety Data Sheet (eSDS)

### Short title of the exposure scenario

ES003 - Professional uses: Non industrial spraying (inside)

### Use of the substance/preparation

Surface treatment of wood and other materials

### Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

## Contributing exposure scenario controlling environmental exposure

### Use

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

### Physical form

liquid

### Hazardous ingredients

#### n-butyl acetate

CAS No.	123-86-4
EINECS no.	204-658-1
Registration no.	01-2119485493-29
Concentration	>= 25 < 50 %

#### 2-methoxy-1-methylethyl acetate

CAS No.	108-65-6
EINECS no.	203-603-9
Registration no.	01-2119475791-29
Concentration	>= 1 < 10 %

#### 4-methylpentan-2-one

CAS No.	108-10-1
EINECS no.	203-550-1
Registration no.	01-2119473980-30
Concentration	>= 1 < 10 %

#### xylene

CAS No.	1330-20-7
EINECS no.	215-535-7
Registration no.	01-2119488216-32
Concentration	>= 1 < 10 %

#### ethylbenzene

CAS No.	100-41-4
---------	----------

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

EINECS no. 202-849-4  
Registration no. 01-2119489370-35  
Concentration  $\geq 1$  < 10 %

**Hydrocarbons, C9, aromatics**

CAS No. 128601-23-0  
EINECS no. 918-668-5  
Registration no. 01-2119455851-35  
Concentration  $\geq 1$  < 10 %

**Maximum amount used per time or activity**

Emission days per site:  $\leq 250$

**Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

**Waste water**

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

**Exhaust air**

Keep container closed. Avoid release to the environment.

**Soil**

Floors should be impervious, resistant to liquids and easy to clean.

**Disposal recommendations for the product**

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances  
200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

**modified product**

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances  
080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

**Dried residues**

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

**Disposal recommendations for packaging**

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

**Contributing exposure scenario controlling worker exposure (professional)**

**Short title of the exposure scenario**

Substance number: CES006

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

## Use

SU22 Professional uses: Public domain (administration, education, entertainment,  
services, craftsmen)  
PROC11 Non industrial spraying  
liquid

## Physical form

## Hazardous ingredients

### n-butyl acetate

CAS No.	123-86-4				
EINECS no.	204-658-1				
Registration no.	01-2119485493-29				
Concentration	>= 25	<	50	%	

### 2-methoxy-1-methylethyl acetate

CAS No.	108-65-6				
EINECS no.	203-603-9				
Registration no.	01-2119475791-29				
Concentration	>= 1	<	10	%	

### 4-methylpentan-2-one

CAS No.	108-10-1				
EINECS no.	203-550-1				
Registration no.	01-2119473980-30				
Concentration	>= 1	<	10	%	

### xylene

CAS No.	1330-20-7				
EINECS no.	215-535-7				
Registration no.	01-2119488216-32				
Concentration	>= 1	<	10	%	

### ethylbenzene

CAS No.	100-41-4				
EINECS no.	202-849-4				
Registration no.	01-2119489370-35				
Concentration	>= 1	<	10	%	

### Hydrocarbons, C9, aromatics

CAS No.	128601-23-0				
EINECS no.	918-668-5				
Registration no.	01-2119455851-35				
Concentration	>= 1	<	10	%	

## Maximum amount used per time or activity

Duration of exposure	<= 8	h/d
Frequency of exposure	<= 220	d/a

## Other relevant operational conditions

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Read attached instructions before use.

## Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7

Breakthrough time  $\geq$  30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (professional)

SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	55,08 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,2
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (professional)

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - local and systemic
Exposure assessment	13,71 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,09
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	137,71 mg/m <sup>3</sup>

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

ECETOC TRA  
0,5  
2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU  
PROC  
Assessment method  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC10  
dermal, long-term - local and systemic  
27,43 mg/kg/d  
ECETOC TRA  
0,18  
2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
inhalation, long-term - local and systemic  
Indoor use  
27,54 mg/m<sup>3</sup>  
ECETOC TRA  
0,1  
2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
dermal, long-term - local and systemic  
Indoor use  
2,14 mg/kg/d  
ECETOC TRA  
0,01  
2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
inhalation, long-term - local and systemic  
Outdoor use  
55,08 mg/m<sup>3</sup>  
ECETOC TRA  
0,2  
2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
dermal, long-term - local and systemic  
Outdoor use  
107,14 mg/kg/d  
ECETOC TRA  
0,7  
2-methoxy-1-methylethyl acetate

SU  
Assessment method

SU21  
dermal, long-term - systemic  
Indoor use

Exposure assessment

6 mg/kg/d



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Exposure assessment (method)	ConsExpo v4.1
Risk characterisation ratio (RCR)	0,11
Lead substance	2-methoxy-1-methylethyl acetate
SU	SU21
Assessment method	inhalation, long-term - systemic
	Indoor use
Exposure assessment	6,83 mg/m <sup>3</sup>
Exposure assessment (method)	ConsExpo v4.1
Risk characterisation ratio (RCR)	0,6
Lead substance	2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	Long-term
	inhalative
Exposure assessment	242 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	n-butyl acetate

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,1
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - systemic
Risk characterisation ratio (RCR)	0,75
Lead substance	4-methylpentan-2-one

**Workers (professional)**



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - systemic
Risk characterisation ratio (RCR)	0,5
Lead substance	4-methylpentan-2-one

**Workers (professional)**

SU	SU22
PROC	PROC10
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene

**Workers (professional)**

SU	SU22
PROC	PROC13
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES004 - Professional uses: roller application or brushing, dipping and pouring and other processing without aerosol formation (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring
PROCh01	Other processing without aerosol formation

## Contributing exposure scenario controlling environmental exposure

### Use

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

### Physical form

liquid

### Hazardous ingredients

#### n-butyl acetate

CAS No.	123-86-4
EINECS no.	204-658-1
Registration no.	01-2119485493-29
Concentration	>= 25 < 50 %

#### 2-methoxy-1-methylethyl acetate

CAS No.	108-65-6
EINECS no.	203-603-9
Registration no.	01-2119475791-29
Concentration	>= 1 < 10 %

#### 4-methylpentan-2-one

CAS No.	108-10-1
EINECS no.	203-550-1
Registration no.	01-2119473980-30
Concentration	>= 1 < 10 %

#### xylene

CAS No.	1330-20-7
EINECS no.	215-535-7
Registration no.	01-2119488216-32
Concentration	>= 1 < 10 %

#### ethylbenzene

CAS No.	100-41-4
EINECS no.	202-849-4
Registration no.	01-2119489370-35
Concentration	>= 1 < 10 %

#### Hydrocarbons, C9, aromatics

CAS No.	128601-23-0
EINECS no.	918-668-5
Registration no.	01-2119455851-35
Concentration	>= 1 < 10 %

### Maximum amount used per time or activity

Emission days per site:	<= 250
-------------------------	--------

### Other relevant operational conditions

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Dispose of rinse water in accordance with local and national regulations.

#### **Waste water**

Do not discharge into the drains/surface waters/groundwater.

#### **Exhaust air**

Keep container closed. Avoid release to the environment.

#### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

#### **Disposal recommendations for the product**

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### **modified product**

EWC waste code	080113 - sludges from paint or varnish containing organic solvents or other dangerous substances
	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### **Dried residues**

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

#### **Disposal recommendations for packaging**

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
----------------	---

Completely emptied packagings can be given for recycling.

### **Contributing exposure scenario controlling worker exposure (professional)**

#### **Short title of the exposure scenario**

Substance number:CES008

#### **Use**

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring
PROCh01	Other processing without aerosol formation

#### **Physical form**

liquid

#### **Hazardous ingredients**

##### **n-butyl acetate**

CAS No.	123-86-4
EINECS no.	204-658-1
Registration no.	01-2119485493-29
Concentration	>= 25 < 50 %

##### **2-methoxy-1-methylethyl acetate**

CAS No.	108-65-6
EINECS no.	203-603-9

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Registration no. 01-2119475791-29  
Concentration  $\geq 1$  < 10 %

**4-methylpentan-2-one**

CAS No. 108-10-1  
EINECS no. 203-550-1  
Registration no. 01-2119473980-30  
Concentration  $\geq 1$  < 10 %

**xylene**

CAS No. 1330-20-7  
EINECS no. 215-535-7  
Registration no. 01-2119488216-32  
Concentration  $\geq 1$  < 10 %

**ethylbenzene**

CAS No. 100-41-4  
EINECS no. 202-849-4  
Registration no. 01-2119489370-35  
Concentration  $\geq 1$  < 10 %

**Hydrocarbons, C9, aromatics**

CAS No. 128601-23-0  
EINECS no. 918-668-5  
Registration no. 01-2119455851-35  
Concentration  $\geq 1$  < 10 %

**Maximum amount used per time or activity**

Duration of exposure  $\leq 8$  h/d  
Frequency of exposure  $\leq 220$  d/a

**Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Read attached instructions before use.

**Product substance and product safety related measures**

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

**Hand protection**

Protective gloves complying with EN 374.  
Glove material  
Multilayer gloves made from  
Appropriate Material Fluorinated rubber / butyl-rubber  
Material thickness  $\geq 0,7$   
Breakthrough time  $\geq 30$

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (professional)

SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	55,08 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,2
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (professional)

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - local and systemic
Exposure assessment	13,71 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,09
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	137,71 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - local and systemic
Exposure assessment	27,43 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,18
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local and systemic

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Exposure assessment	Indoor use
Exposure assessment (method)	27,54 mg/m <sup>3</sup>
Risk characterisation ratio (RCR)	ECETOC TRA
Lead substance	0,1
	2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - local and systemic
	Indoor use
Exposure assessment	2,14 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,01
Lead substance	2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local and systemic
	Outdoor use
Exposure assessment	55,08 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,2
Lead substance	2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - local and systemic
	Outdoor use
Exposure assessment	107,14 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,7
Lead substance	2-methoxy-1-methylethyl acetate

SU	SU21
Assessment method	dermal, long-term - systemic
	Indoor use
Exposure assessment	6 mg/kg/d
Exposure assessment (method)	ConsExpo v4.1
Risk characterisation ratio (RCR)	0,11
Lead substance	2-methoxy-1-methylethyl acetate
SU	SU21
Assessment method	inhalation, long-term - systemic
	Indoor use

Exposure assessment	6,83 mg/m <sup>3</sup>
Exposure assessment (method)	ConsExpo v4.1
Risk characterisation ratio (RCR)	0,6
Lead substance	2-methoxy-1-methylethyl acetate

**Workers (professional)**

SU	SU22
PROC	PROC11
Assessment method	Long-term
	inhalative

Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

Exposure assessment 242 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,504  
Lead substance n-butyl acetate

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method inhalation, long-term - systemic  
Risk characterisation ratio (RCR) 0,5  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method dermal, long-term - systemic  
Risk characterisation ratio (RCR) 0,1  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method inhalation, long-term - systemic  
Risk characterisation ratio (RCR) 0,5  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method dermal, long-term - systemic  
Risk characterisation ratio (RCR) 0,5  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC13  
Assessment method inhalation, long-term - systemic  
Risk characterisation ratio (RCR) 0,75  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC13  
Assessment method dermal, long-term - systemic  
Risk characterisation ratio (RCR) 0,5  
Lead substance 4-methylpentan-2-one

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method inhalative  
Indoor use  
Exposure assessment 0,05 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,172  
Lead substance xylene

**Workers (professional)**



Trade name: Hesse UNA-COLOR, silk matt PEX DB 555-FT

Version: 22 / GB

Revision: 30.11.2022

Replaces Version: 21 / GB

Print date: 16.01.23

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC11  
inhalative  
Indoor use  
0,1 mg/m<sup>3</sup>  
ECETOC TRA  
0,34  
xylene

**Workers (professional)**

SU  
PROC  
Assessment method  
  
Exposure assessment  
Exposure assessment (method)  
Risk characterisation ratio (RCR)  
Lead substance

SU22  
PROC13  
inhalative  
Indoor use  
0,05 mg/m<sup>3</sup>  
ECETOC TRA  
0,172  
xylene

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.