

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

Identified Uses

	REACHSET 1003
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG
Warendorfer Strasse 21
59075 Hamm (Germany)
Telephone no. +49 (0) 2381 963-00
Fax no. +49 (0) 2381 963-849
E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1), May produce an allergic reaction.

Supplemental information

EUH210 Safety data sheet available on request.

2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

Hazardous ingredients

propan-2-ol

CAS No.	67-63-0		
EINECS no.	200-661-7		
Registration no.	01-2119457558-25		
Concentration	>= 1	< 5	%
Classification (Regulation (EC) No. 1272/2008)			
	Flam. Liq. 2	H225	
	Eye Irrit. 2	H319	
	STOT SE 3	H336	Nervous system

2-butoxyethanol

CAS No.	111-76-2		
EINECS no.	203-905-0		
Registration no.	01-2119475108-36		
Concentration	>= 1	< 4	%
Classification (Regulation (EC) No. 1272/2008)			
	Acute Tox. 4	H302	Route of exposure: Oral exposure
	Acute Tox. 4	H312	Route of exposure: Dermal exposure
	Acute Tox. 4	H332	Route of exposure: Inhalation exposure
	Eye Irrit. 2	H319	
	Skin Irrit. 2	H315	

ATE	Oral exposure	1.200	mg/kg
ATE	Dermal exposure	435	mg/kg
ATE	Inhalation exposure, Dust/Mist	2,56	mg/l

diacetone alcohol

CAS No.	123-42-2		
EINECS no.	204-626-7		
Registration no.	01-2119473975-21		
Concentration	>= 0,1	< 1	%
Classification (Regulation (EC) No. 1272/2008)			
	STOT SE 3	H335	Respiratory tract
	Eye Irrit. 2	H319	
	Repr. 2	H361d	

Concentration limits (Regulation (EC) No. 1272/2008)			
	Eye Irrit. 2	H319	10 %

1,2-benzisothiazol-3(2H)-one

CAS No.	2634-33-5		
EINECS no.	220-120-9		
Concentration		< 0,05	%
Classification (Regulation (EC) No. 1272/2008)			
	Acute Tox. 4	H302	
	Skin Irrit. 2	H315	

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 2	H411

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1	H317	>= 0,05 %
--------------	------	-----------

2-methyl-2H-isothiazol-3-one

CAS No. 2682-20-4

EINECS no. 220-239-6

Concentration < 0,0015 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3	H301
Acute Tox. 2	H330

Route of exposure: Inhalation
exposure

Skin Corr. 1B	H314
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Skin Sens. 1A	H317
Acute Tox. 3	H311
Eye Dam. 1	H318

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400	M = 10
Skin Sens. 1A	H317	>= 0,0015 %

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

CAS No. 55965-84-9

Concentration < 0,001 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 2	H330
Acute Tox. 2	H310
Acute Tox. 3	H301
Skin Corr. 1B	H314
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Eye Dam. 1	H318

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C	H314	>= 0,6 %
Skin Irrit. 2	H315	>= 0,06 %
Eye Irrit. 2	H319	>= 0,06 %
Skin Sens. 1	H317	>= 0,0015 %
Eye Dam. 1	H318	>= 0,6 %
Aquatic Chronic 1	H410	M = 100
Aquatic Acute 1	H400	M = 100

Further ingredients

ethanol

CAS No. 64-17-5

EINECS no. 200-578-6

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Registration no. 01-2119457610-43
Concentration ≥ 1 < 10 %
Advice: [3]
Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 2 H225

Note

[3] Substance with occupational exposure limits

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

After inhalation

When spray fog inhaled, seek medical aid.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage classes

Storage class according to TRGS 510 10 Flammable liquids

Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values

2-butoxyethanol

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

List	Directive 2017/164 EG			
Value	98	mg/m ³	20	ppm(V)
Short term exposure limit	246	mg/m ³	50	ppm(V)
Skin resorption / sensibilisation: H; Status: 12/2009				

2-butoxyethanol

List	EH40			
Value	123	mg/m ³	25	ppm(V)
Short term exposure limit	246	mg/m ³	50	ppm(V)
Skin resorption / sensibilisation: Sk; Status: 01/2020				

propan-2-ol

List	EH40			
Value	999	mg/m ³	400	ppm(V)
Short term exposure limit	1250	mg/m ³	500	ppm(V)
Status: 01/2020				

ethanol

List	EH40			
Value	1920	mg/m ³	1000	ppm(V)
Status: 01/2020				

Other information

-

Derived No/Minimal Effect Levels (DNEL/DMEL)

2-butoxyethanol

Type of value	Derived No Effect Level (DNEL)		
Reference group	Workers (professional)		
Duration of exposure	Long-term		
Route of exposure	Dermal exposure		
Mode of action	Acute effects		
Concentration	89		mg/kg

Type of value	Derived No Effect Level (DNEL)		
Reference group	Workers (professional)		
Duration of exposure	Long-term		
Route of exposure	inhalative		
Mode of action	Local effects		
Concentration	246		mg/m ³

Type of value	Derived No Effect Level (DNEL)		
Reference group	Workers (professional)		
Duration of exposure	Long-term		
Route of exposure	Dermal exposure		
Mode of action	Systemic effects		
Concentration	75		mg/kg/d

Type of value	Derived No Effect Level (DNEL)		
Reference group	Workers (professional)		
Duration of exposure	Long-term		
Route of exposure	inhalative		
Mode of action	Systemic effects		
Concentration	20		ppm

Type of value	Derived No Effect Level (DNEL)		
---------------	--------------------------------	--	--

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	89	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	246	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1091	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	3,2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	13,4	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	123	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Acute effects	
Concentration	44,5	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Acute effects	

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Concentration	426	mg/m ³
---------------	-----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Oral exposure
-------------------	---------------

Mode of action	Systemic effects
----------------	------------------

Concentration	6,3	mg/kg
---------------	-----	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	106,4	mg/m ³
---------------	-------	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	Dermal exposure
-------------------	-----------------

Mode of action	Systemic effects
----------------	------------------

Concentration	38	mg/kg
---------------	----	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Systemic effects
----------------	------------------

Concentration	59	mg/m ³
---------------	----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long-term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Systemic effects
----------------	------------------

Concentration	49	mg/m ³
---------------	----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Short-term
----------------------	------------

Route of exposure	Oral exposure
-------------------	---------------

Mode of action	Systemic effects
----------------	------------------

Concentration	26,7	mg/kg/d
---------------	------	---------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Short-term
----------------------	------------

Route of exposure	inhalative
-------------------	------------

Mode of action	Systemic effects
----------------	------------------

Concentration	135	mg/m ³
---------------	-----	-------------------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	147	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	89	mg/kg/d

propan-2-ol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Chronic effects	
Concentration	888	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Chronic effects	
Concentration	500	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Chronic effects	
Concentration	89	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Chronic effects	
Concentration	26	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	319	mg/kg/d

ethanol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Mode of action	Local effects	
Concentration	1900	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	343	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	960	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Acute effects	
Concentration	960	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	206	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	114	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	87	mg/kg/d
diacetone alcohol		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32,6	mg/m ³

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	467	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	5,8	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	1,67	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	167	mg/kg/d

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	0,09	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
---------------	--------------------------------	--

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,04	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	0,11	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,04	mg/m ³

Predicted No Effect Concentration (PNEC)

2-butoxyethanol

Type of value	PNEC	
Type	Freshwater	
Concentration	8,8	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,88	mg/l

Type of value	PNEC	
Type	saltwater sediment	
Concentration	3,46	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	463	mg/l

Type of value	PNEC	
Type	Soil	
Concentration	2,33	mg/kg

propan-2-ol

Type of value	PNEC	
Type	Freshwater	
Concentration	140,9	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	140,9	mg/l

Type of value	PNEC	
---------------	------	--

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Conditions	sporadic release	
Concentration	140,9	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	552	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	552	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	28	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	2251	mg/l
ethanol		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,96	mg/l
Type of value	PNEC	
Type	marine water	
Concentration	0,79	mg/l
Type of value	PNEC	
Conditions	sporadic release	
Concentration	2,75	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	580	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	3,6	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	2,9	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,63	mg/kg
diacetone alcohol		
Type of value	PNEC	
Type	Freshwater	
Concentration	2	mg/l

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Type of value	PNEC	
Type	Saltwater	
Concentration	0,2	mg/l
Type of value	PNEC	
Conditions	sporadic release	
Concentration	1	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	7,4	mg/kg/d
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,74	mg/kg/d
Type of value	PNEC	
Type	Soil	
Concentration	0,31	mg/kg/d

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H
-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one
[EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)**

Type of value	PNEC	
Type	Marine	
Concentration	3,39	µg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	0,23	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,01	mg/kg
Type of value	PNEC	
Type	Freshwater	
Concentration	3,39	µg/l

8.2. Exposure controls

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness \geq 0,5 mm

Breakthrough time \geq 120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid

Colour coloured

Odour characteristic

Melting point

Remarks not determined

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value 78 to 189 °C

Flammability

not determined

Upper and lower explosive limits

Remarks not determined

Flash point

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Value > 60 °C

Ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

pH value

Value 8,7
Concentration/H₂O 100

Viscosity

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

Value appr. 1,028 kg/l
Temperature 20 °C

Relative vapour density

Remarks not determined

Particle characteristics

Remarks not determined

9.2. Other information

Odour threshold

Remarks not determined

Solubility in water

Remarks not determined

Efflux time

Value 25 to 35 s
Temperature 20 °C
Method DIN EN ISO 2431 - 4 mm

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

Non-volatile content

Value appr. 39 %
Method calculated value

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO_x), dense black smoke, No decomposition if used as prescribed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		
Remarks	Based on available data, the classification criteria are not met.		

Acute oral toxicity (Components)

2-butoxyethanol

ATE	1200	mg/kg
-----	------	-------

2-methyl-2H-isothiazol-3-one

Species	rat	
LD50	120	mg/kg
Method	EPA	
Source	1 (reliable without restriction)	

1,2-benzisothiazol-3(2H)-one

Species	rat	
LD50	1193	mg/kg

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

ATE	53	mg/kg
-----	----	-------

Acute dermal toxicity

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		
Remarks	Based on available data, the classification criteria are not met.		

Acute dermal toxicity (Components)

2-butoxyethanol

Species	guinea pig	
LD50	435	mg/kg
Source	1 (reliable without restriction)	

2-methyl-2H-isothiazol-3-one

Species	rat
---------	-----

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

LD50 242 mg/kg
Source 1 (reliable without restriction)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

ATE 50 mg/kg
Method conversion

Acute inhalational toxicity

ATE > 20 mg/l
Administration/Form Dust/Mist
Method calculated value (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)

2-butoxyethanol

Species rat
LC50 2,56 mg/l
Duration of exposure 4 h
Administration/Form Dust/Mist
Source 1 (reliable without restriction)

2-methyl-2H-isothiazol-3-one

Species rat
LC50 0,1 mg/l
Duration of exposure 4 h
Administration/Form Dust/Mist
Source 1 (reliable without restriction)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

ATE 0,05 mg/l
Duration of exposure 4 h
Administration/Form Dust/Mist
Method conversion value
Remarks Mist

Skin corrosion/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)

2-butoxyethanol

Species rabbit
Duration of exposure 4 h
Observation Period 28 d
evaluation Irritating to skin and mucous membranes
Method EEC 84/449, B.4

2-methyl-2H-isothiazol-3-one

evaluation Causes burns.

1,2-benzisothiazol-3(2H)-one

evaluation Irritating to skin.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

Species rabbit
evaluation Severe skin irritation

Serious eye damage/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation (Components)

2-butoxyethanol

Species rabbit
Duration of exposure 24 h
Observation Period 21 d
evaluation Eye irritation
Source 1 (reliable without restriction)

propan-2-ol

Species rabbit
Observation Period 14 d
evaluation Irritating to eyes.
Source 1 (reliable without restriction)

diacetone alcohol

Species rabbit
evaluation Irritating to eyes.
Source 2 (reliable with restrictions)

2-methyl-2H-isothiazol-3-one

evaluation Causes severe caustic burns to skin and eyes.

1,2-benzisothiazol-3(2H)-one

evaluation Irritating to eyes.

Sensitization

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Sensitization (Components)

2-methyl-2H-isothiazol-3-one

evaluation May cause sensitization by skin contact.

1,2-benzisothiazol-3(2H)-one

Reference substance 1,2-benzisothiazol-3(2H)-one
evaluation May cause sensitization by skin contact.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

Species guinea pig
evaluation Causes sensitisation on guinea-pigs.

Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Reproduction toxicity (Components)

diacetone alcohol

Species	rat
evaluation	Reproductive toxicity, Category 2
Method	OECD 422
Remarks	Suspected of damaging the unborn child.
Source	2 (reliable with restrictions)

Carcinogenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

Specific Target Organ Toxicity (STOT) (Components)

propan-2-ol

Specific target organ toxicity - single exposure

Remarks	Organs: Nervous system Possible narcotic effects (drowsiness, dizziness).
---------	--

diacetone alcohol

Specific target organ toxicity - single exposure

Remarks	Organs: Respiratory tract May cause respiratory irritation.
---------	--

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

No toxicological data are available.

SECTION 12: Ecological information

12.1. Toxicity

General information

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species	Oncorhynchus mykiss (rainbow trout)	
LC50	2,18	mg/l
Duration of exposure	96	h

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

Species	Oncorhynchus mykiss (rainbow trout)	
LC50	0,19	mg/l
Duration of exposure	96	h

Daphnia toxicity (Components)

2-methyl-2H-isothiazol-3-one

Species	Daphnia magna (Water flea)	
NOEC	0,044	mg/l
Duration of exposure	21	d

1,2-benzisothiazol-3(2H)-one

Species	Daphnia magna (Water flea)	
EC50	2,94	mg/l
Duration of exposure	48	h

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

Species	Daphnia magna (Water flea)	
EC50	0,16	mg/l
Duration of exposure	48	h

Algae toxicity (Components)

2-methyl-2H-isothiazol-3-one

EC50	0,157	mg/l
Duration of exposure	96	h

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

Species	Scenedesmus capricornutum (fresh water algae)	
EC50	0,018	mg/l
Duration of exposure	72	h

Bacteria toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)

Species	activated sludge	
EC50	4,5	mg/l

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

2-methyl-2H-isothiazol-3-one

evaluation	Readily biodegradable.
------------	------------------------

1,2-benzisothiazol-3(2H)-one

evaluation	Readily biodegradable.
------------	------------------------

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

-isothiazol-3- one [EC no. 220-239-6] (3:1); reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one
[EC no. 247-500-7] and 2-methyl-4-isothiazolin-3- one [EC no. 220-239-6] (3:1)
evaluation Not readily biodegradable.

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient n-octanol/water (log value)

Remarks not determined

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

For this subsection there is no ecotoxicological data available on the product as such.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
EWC waste code	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

modified product

EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances
----------------	--

Dried residues

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated
by dangerous substances
Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

VOC (EU) appr. 3 % 36 g/l

SECTION 16: Other information

Hazard statements listed in Chapter 3

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IMDG - International Maritime Code for Dangerous Goods
IATA - International Air Transport Association
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)
GHS - Globally Harmonized System of Classification and Labelling of Chemicals
EINECS - European Inventory of Existing Commercial Chemical Substances
CAS - Chemical Abstracts Service (division of the American Chemical Society)
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)
LOAEL - Lowest Observed Adverse Effect Level
LOEL - Lowest Observed Effect Level
NOAEL - No Observed Adverse Effect Level
NOEC - No Observed Effect Concentration
NOEL - No Observed Effect Level
OECD - Organisation for Economic Cooperation and Development
VOC - Volatile Organic Compounds
Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.
This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.
The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES018 - Industrial applications: rolling, dipping, pouring and other processing without aerosol formation (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROCh02	roller coating industrial
PROC13	Treatment of articles by dipping and pouring

Contributing exposure scenario controlling environmental exposure

Use

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix

Physical form

liquid

Maximum amount used per time or activity

Emission days per site: <= 300

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

EWC waste code	080111 - waste paint and varnish containing organic solvents or other dangerous substances
	200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

modified product

EWC waste code	080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances
----------------	--

Dried residues

EWC waste code	080112 - waste lacquers and waste paint except those falling under 080111
----------------	---

Disposal recommendations for packaging

EWC waste code	150110 - packaging containing residues of or contaminated by dangerous substances
Completely emptied packagings can be given for recycling.	

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Contributing exposure scenario controlling worker exposure

Use

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
PROCh01	Other processing without aerosol formation
PROCh02	roller coating industrial
PROC13	Treatment of articles by dipping and pouring

Physical form

liquid

Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.
Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Protective gloves complying with EN 374.

Glove material

Appropriate Material butyl-rubber

Material thickness >= 0,5

Breakthrough time >= 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Eye protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Exposure estimation and reference to its source

Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23

Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	inhalation, long-term - systemic
Exposure assessment	42 mg/m ³
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,428571
Lead substance	2-butoxyethanol

Workers (industrial)

PROC	PROC7
Assessment method	dermal, long-term - systemic
Exposure assessment	8,5714 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,068571
Lead substance	2-butoxyethanol

Workers (industrial)

PROC	PROC10
Assessment method	inhalation, long-term - systemic
Exposure assessment	55 mg/m ³
Exposure assessment (method)	EASY TRA v3.5
Risk characterisation ratio (RCR)	0,561224
Lead substance	2-butoxyethanol

Workers (industrial)

PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	5,4857 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,043886
Lead substance	2-butoxyethanol

Workers (industrial)

PROC	PROC13
Assessment method	inhalation, long-term - systemic
Exposure assessment	49,2393 mg/m ³
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,502441
Lead substance	2-butoxyethanol

Workers (industrial)

PROC	PROC13
Assessment method	dermal, long-term - systemic
Exposure assessment	2,7429 mg/kg/d
Exposure assessment (method)	EASY TRA v3.5
Risk characterisation ratio (RCR)	0,021943
Lead substance	2-butoxyethanol

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.



Trade name: Hesse HYDRO Chamfer lacquer, silk matt PEX HB 65965-FT

Version: 11 / GB

Revision: 30.11.2022

Replaces Version: 10 / GB

Print date: 16.01.23