

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

|        |  |
|--------|--|
|        | REACHSET 2001  |
| SU22   | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a  | Wide dispersive indoor use of processing aids in open systems                                    |
| ERC8c  | Wide dispersive indoor use resulting in inclusion into or onto a matrix                          |
| PROC11 | Non industrial spraying  |

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

|  |      |
|--|------|
| Classification (Regulation (EC) No. 1272/2008) |      |
| Flam. Liq. 2                                   | H225 |
| Eye Irrit. 2                                   | H319 |
| STOT SE 3                                      | H336 |
| Aquatic Chronic 3                              | H412 |

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

#### Hazard pictograms

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23



## Signal word

Danger

## Hazard statements

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.                |
| H319 | Causes serious eye irritation.                     |
| H336 | May cause drowsiness or dizziness.                 |
| H412 | Harmful to aquatic life with long lasting effects. |

## Precautionary statements

|                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P261           | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P273           | Avoid release to the environment.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.   |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

## Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

|                 |   |
|-----------------|---|
| contains        | 1-methoxy-2-propanol; ethyl acetate; n-butyl acetate; Hydrocarbons, C9, aromatics                 |
| EUH208 Contains | 12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide, May produce an allergic reaction. |

## Supplemental information

|        |   |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

## 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### ethyl acetate

|  |                  |        |    |                |
|--|------------------|--------|----|----------------|
| CAS No.  | 141-78-6         |        |    |                |
| EINECS no.                                     | 205-500-4        |        |    |                |
| Registration no.                               | 01-2119475103-46 |        |    |                |
| Concentration                                  | >= 25            | <      | 50 | %              |
| Classification (Regulation (EC) No. 1272/2008) |                  |        |    |                |
|  | Flam. Liq. 2     | H225   |    |                |
|  | Eye Irrit. 2     | H319   |    |                |
|  | STOT SE 3        | H336   |    | Nervous system |
|  |                  | EUH066 |    |                |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

**n-butyl acetate**

|  |                  |      |                |
|--|------------------|------|----------------|
| CAS No.  | 123-86-4         |      |                |
| EINECS no.                                     | 204-658-1        |      |                |
| Registration no.                               | 01-2119485493-29 |      |                |
| Concentration                                  | >= 20            | < 25 | %              |
| Classification (Regulation (EC) No. 1272/2008) |                  |      |                |
| Flam. Liq. 3                                   | H226             |      |                |
| STOT SE 3                                      | H336             |      | Nervous system |
|  | EUH066           |      |                |

**Hydrocarbons, C9, aromatics**

|  |                  |      |                   |
|--|------------------|------|-------------------|
| CAS No.  | 128601-23-0      |      |                   |
| EINECS no.                                     | 918-668-5        |      |                   |
| Registration no.                               | 01-2119455851-35 |      |                   |
| Concentration                                  | >= 3             | < 10 | %                 |
| Classification (Regulation (EC) No. 1272/2008) |                  |      |                   |
| Flam. Liq. 3                                   | H226             |      |                   |
| Asp. Tox. 1                                    | H304             |      |                   |
| Aquatic Chronic 2                              | H411             |      |                   |
| STOT SE 3                                      | H335             |      | Respiratory tract |
| STOT SE 3                                      | H336             |      | Nervous system    |
|  | EUH066           |      |                   |

**1-methoxy-2-propanol**

|  |                  |      |                |
|--|------------------|------|----------------|
| CAS No.  | 107-98-2         |      |                |
| EINECS no.                                     | 203-539-1        |      |                |
| Registration no.                               | 01-2119457435-35 |      |                |
| Concentration                                  | >= 1             | < 10 | %              |
| Classification (Regulation (EC) No. 1272/2008) |                  |      |                |
| Flam. Liq. 3                                   | H226             |      |                |
| STOT SE 3                                      | H336             |      | Nervous system |

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

|  |                  |     |                |
|--|------------------|-----|----------------|
| EINECS no.                                     | 920-750-0        |     |                |
| Registration no.                               | 01-2119473851-33 |     |                |
| Concentration                                  | >= 1             | < 3 | %              |
| Classification (Regulation (EC) No. 1272/2008) |                  |     |                |
| Flam. Liq. 2                                   | H225             |     |                |
| Asp. Tox. 1                                    | H304             |     |                |
| Aquatic Chronic 2                              | H411             |     |                |
| STOT SE 3                                      | H336             |     | Nervous system |

**xylene**

|  |                  |      |  |
|--|------------------|------|--|
| CAS No.  | 1330-20-7        |      |  |
| EINECS no.                                     | 215-535-7        |      |  |
| Registration no.                               | 01-2119488216-32 |      |  |
| Concentration                                  | >= 1             | < 10 | %                                      |
| Classification (Regulation (EC) No. 1272/2008) |                  |      |  |
| Flam. Liq. 3                                   | H226             |      |  |
| Acute Tox. 4                                   | H332             |      | Route of exposure: Inhalation exposure |
| Acute Tox. 4                                   | H312             |      | Route of exposure: Dermal exposure     |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

Skin Irrit. 2 H315

Asp. Tox. 1 H304

STOT SE 3 H335

Respiratory tract; Route of exposure:  
inhalative

Eye Irrit. 2 H319

ATE Dermal exposure 2.000 mg/kg

ATE Inhalation exposure, Dust/Mist 5 mg/l

**12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide**

EINECS no. 434-430-9

Registration no. 01-0000018057-71

Concentration  $\geq 0,1$  < 1 %

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317

Aquatic Chronic 4 H413

**cellulose nitrate  $\leq 12.6$  % N**

CAS No. 9004-70-0

Classification (Regulation (EC) No. 1272/2008)

Expl. 1.1 H201

**Note**

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

If unconscious place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical attention. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

### 4.3. Indication of any immediate medical attention and special treatment needed

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

### Hints for the physician / treatment

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### Other information

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Standard procedure for chemical fires.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### 6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

### Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Storage classes

Storage class according to TRGS 510      3      Flammable liquid

### Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## 7.3. Specific end use(s)

See exposure scenario, if available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### n-butyl acetate

|                           |      |                   |     |        |
|---------------------------|------|-------------------|-----|--------|
| List                      | EH40 |                   |     |        |
| Value                     | 724  | mg/m <sup>3</sup> | 150 | ppm(V) |
| Short term exposure limit | 966  | mg/m <sup>3</sup> | 200 | ppm(V) |
| Status: 01/2020           |      |                   |     |        |

##### n-butyl acetate

|                           |                       |                   |     |        |
|---------------------------|-----------------------|-------------------|-----|--------|
| List                      | Directive 2017/164 EG |                   |     |        |
| Value                     | 241                   | mg/m <sup>3</sup> | 50  | ppm(V) |
| Short term exposure limit | 723                   | mg/m <sup>3</sup> | 150 | ppm(V) |
| Status: 10/2019           |                       |                   |     |        |

##### Hydrocarbons, C9, aromatics

|                 |      |                   |  |  |
|-----------------|------|-------------------|--|--|
| List            | EH40 |                   |  |  |
| Value           | 500  | mg/m <sup>3</sup> |  |  |
| Status: 01/2020 |      |                   |  |  |

##### ethyl acetate

|                           |                       |                   |     |        |
|---------------------------|-----------------------|-------------------|-----|--------|
| List                      | Directive 2017/164 EG |                   |     |        |
| Value                     | 734                   | mg/m <sup>3</sup> | 200 | ppm(V) |
| Short term exposure limit | 1468                  | mg/m <sup>3</sup> | 400 | ppm(V) |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

Status: 02/2017

**ethyl acetate**

|                           |      |                   |     |        |
|---------------------------|------|-------------------|-----|--------|
| List                      | EH40 |                   |     |        |
| Value                     | 734  | mg/m <sup>3</sup> | 200 | ppm(V) |
| Short term exposure limit | 1468 | mg/m <sup>3</sup> | 400 | ppm(V) |

Status: 01/2020

**1-methoxy-2-propanol**

|                           |                       |                   |     |        |
|---------------------------|-----------------------|-------------------|-----|--------|
| List                      | Directive 2017/164 EG |                   |     |        |
| Value                     | 375                   | mg/m <sup>3</sup> | 100 | ppm(V) |
| Short term exposure limit | 568                   | mg/m <sup>3</sup> | 150 | ppm(V) |

Skin resorption / sensibilisation: H; Status: 12/2009

**1-methoxy-2-propanol**

|                           |      |                   |     |        |
|---------------------------|------|-------------------|-----|--------|
| List                      | EH40 |                   |     |        |
| Value                     | 375  | mg/m <sup>3</sup> | 100 | ppm(V) |
| Short term exposure limit | 560  | mg/m <sup>3</sup> | 150 | ppm(V) |

Skin resorption / sensibilisation: Sk; Status: 01/2020

**xylene**

|                           |                       |                   |     |        |
|---------------------------|-----------------------|-------------------|-----|--------|
| List                      | Directive 2017/164 EG |                   |     |        |
| Value                     | 221                   | mg/m <sup>3</sup> | 50  | ppm(V) |
| Short term exposure limit | 442                   | mg/m <sup>3</sup> | 100 | ppm(V) |

Skin resorption / sensibilisation: H; Status: 12/2009

**xylene**

|                           |      |                   |     |        |
|---------------------------|------|-------------------|-----|--------|
| List                      | EH40 |                   |     |        |
| Value                     | 220  | mg/m <sup>3</sup> | 50  | ppm(V) |
| Short term exposure limit | 441  | mg/m <sup>3</sup> | 100 | ppm(V) |

Skin resorption / sensibilisation: Sk; Status: 01/2020

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

|       |      |                   |  |  |
|-------|------|-------------------|--|--|
| List  | EH40 |                   |  |  |
| Value | 1200 | mg/m <sup>3</sup> |  |  |

Status: 01/2020

**Other information**

-

**Derived No/Minimal Effect Levels (DNEL/DMEL)**

**1-methoxy-2-propanol**

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (industrial)           |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 369                            | mg/m <sup>3</sup> |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (industrial)           |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 183                            | mg/kg/d |

|                 |                                |
|-----------------|--------------------------------|
| Type of value   | Derived No Effect Level (DNEL) |
| Reference group | Consumer                       |



Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Duration of exposure | Long-term                      |         |
| Route of exposure    | inhalative                     |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 43,9                           | mg/m³   |
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 78                             | mg/kg/d |
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Oral exposure                  |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 33                             | mg/kg/d |
| <b>ethyl acetate</b> |                                |         |
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 63                             | mg/kg/d |
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | inhalative                     |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 734                            | mg/m³   |
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | inhalative                     |         |
| Mode of action       | Local effects                  |         |
| Concentration        | 734                            | mg/m³   |
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Short-term                     |         |
| Route of exposure    | inhalative                     |         |
| Mode of action       | Local effects                  |         |
| Concentration        | 1468                           | mg/m³   |
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Short-term                     |         |
| Route of exposure    | inhalative                     |         |
| Mode of action       | Systemic effects               |         |



Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|               |      |                   |
|---------------|------|-------------------|
| Concentration | 1468 | mg/m <sup>3</sup> |
|---------------|------|-------------------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |            |
|----------------------|------------|
| Duration of exposure | Short-term |
|----------------------|------------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |     |                   |
|---------------|-----|-------------------|
| Concentration | 734 | mg/m <sup>3</sup> |
|---------------|-----|-------------------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |            |
|----------------------|------------|
| Duration of exposure | Short-term |
|----------------------|------------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |               |
|----------------|---------------|
| Mode of action | Local effects |
|----------------|---------------|

|               |     |                   |
|---------------|-----|-------------------|
| Concentration | 734 | mg/m <sup>3</sup> |
|---------------|-----|-------------------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |    |         |
|---------------|----|---------|
| Concentration | 37 | mg/kg/d |
|---------------|----|---------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |     |                   |
|---------------|-----|-------------------|
| Concentration | 367 | mg/m <sup>3</sup> |
|---------------|-----|-------------------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |               |
|-------------------|---------------|
| Route of exposure | Oral exposure |
|-------------------|---------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |     |         |
|---------------|-----|---------|
| Concentration | 4,5 | mg/kg/d |
|---------------|-----|---------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |               |
|----------------|---------------|
| Mode of action | Local effects |
|----------------|---------------|

|               |     |                   |
|---------------|-----|-------------------|
| Concentration | 367 | mg/m <sup>3</sup> |
|---------------|-----|-------------------|

**n-butyl acetate**

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |                        |
|-----------------|------------------------|
| Reference group | Workers (professional) |
|-----------------|------------------------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |    |         |
|---------------|----|---------|
| Concentration | 11 | mg/kg/d |
|---------------|----|---------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 600                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 600                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 300                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 300                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | Dermal exposure                |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 6                              | mg/kg/d           |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | Oral exposure                  |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 2                              | mg/kg/d           |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 300                            | mg/m <sup>3</sup> |
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|               |     |                   |
|---------------|-----|-------------------|
| Concentration | 300 | mg/m <sup>3</sup> |
|---------------|-----|-------------------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |      |                   |
|---------------|------|-------------------|
| Concentration | 35,7 | mg/m <sup>3</sup> |
|---------------|------|-------------------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |               |
|----------------|---------------|
| Mode of action | Local effects |
|----------------|---------------|

|               |      |                   |
|---------------|------|-------------------|
| Concentration | 35,7 | mg/m <sup>3</sup> |
|---------------|------|-------------------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |            |
|----------------------|------------|
| Duration of exposure | Short term |
|----------------------|------------|

|                   |      |
|-------------------|------|
| Route of exposure | oral |
|-------------------|------|

|                |                  |
|----------------|------------------|
| Mode of action | Specific effects |
|----------------|------------------|

|               |   |         |
|---------------|---|---------|
| Concentration | 2 | mg/kg/d |
|---------------|---|---------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |            |
|----------------------|------------|
| Duration of exposure | Short term |
|----------------------|------------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Specific effects |
|----------------|------------------|

|               |   |         |
|---------------|---|---------|
| Concentration | 6 | mg/kg/d |
|---------------|---|---------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |        |
|-----------------|--------|
| Reference group | Worker |
|-----------------|--------|

|                      |            |
|----------------------|------------|
| Duration of exposure | Short term |
|----------------------|------------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Specific effects |
|----------------|------------------|

|               |    |         |
|---------------|----|---------|
| Concentration | 11 | mg/kg/d |
|---------------|----|---------|

**xylene**

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |     |       |
|---------------|-----|-------|
| Concentration | 125 | mg/kg |
|---------------|-----|-------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |                        |
|-----------------|------------------------|
| Reference group | Workers (professional) |
|-----------------|------------------------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |     |       |
|---------------|-----|-------|
| Concentration | 212 | mg/kg |
|---------------|-----|-------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|                      |                  |                   |
|----------------------|------------------|-------------------|
| Reference group      | Consumer         |                   |
| Duration of exposure | Long-term        |                   |
| Route of exposure    | inhalative       |                   |
| Mode of action       | Systemic effects |                   |
| Concentration        | 65,3             | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 260                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 174                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 442                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 221                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 289                            | mg/m <sup>3</sup> |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Short-term                     |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Local effects                  |                   |
| Concentration        | 289                            | mg/m <sup>3</sup> |

|                      |                                |  |
|----------------------|--------------------------------|--|
| Type of value        | Derived No Effect Level (DNEL) |  |
| Reference group      | Consumer                       |  |
| Duration of exposure | Long-term                      |  |
| Route of exposure    | Oral exposure                  |  |
| Mode of action       | Systemic effects               |  |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|               |      |         |
|---------------|------|---------|
| Concentration | 12,5 | mg/kg/d |
|---------------|------|---------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |                        |
|-----------------|------------------------|
| Reference group | Workers (professional) |
|-----------------|------------------------|

|                      |            |
|----------------------|------------|
| Duration of exposure | Short-term |
|----------------------|------------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |               |
|----------------|---------------|
| Mode of action | Local effects |
|----------------|---------------|

|               |     |         |
|---------------|-----|---------|
| Concentration | 174 | mg/kg/d |
|---------------|-----|---------|

#### Hydrocarbons, C9, aromatics

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |               |
|-------------------|---------------|
| Route of exposure | Oral exposure |
|-------------------|---------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |    |       |
|---------------|----|-------|
| Concentration | 11 | mg/kg |
|---------------|----|-------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |                        |
|-----------------|------------------------|
| Reference group | Workers (professional) |
|-----------------|------------------------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |    |       |
|---------------|----|-------|
| Concentration | 25 | mg/kg |
|---------------|----|-------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |                 |
|-------------------|-----------------|
| Route of exposure | Dermal exposure |
|-------------------|-----------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |    |       |
|---------------|----|-------|
| Concentration | 11 | mg/kg |
|---------------|----|-------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |                        |
|-----------------|------------------------|
| Reference group | Workers (professional) |
|-----------------|------------------------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |     |       |
|---------------|-----|-------|
| Concentration | 150 | mg/kg |
|---------------|-----|-------|

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |            |
|-------------------|------------|
| Route of exposure | inhalative |
|-------------------|------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |    |       |
|---------------|----|-------|
| Concentration | 32 | mg/kg |
|---------------|----|-------|

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|

|                 |          |
|-----------------|----------|
| Reference group | Consumer |
|-----------------|----------|

|                      |           |
|----------------------|-----------|
| Duration of exposure | Long-term |
|----------------------|-----------|

|                   |               |
|-------------------|---------------|
| Route of exposure | Oral exposure |
|-------------------|---------------|

|                |                  |
|----------------|------------------|
| Mode of action | Systemic effects |
|----------------|------------------|

|               |     |         |
|---------------|-----|---------|
| Concentration | 699 | mg/kg/d |
|---------------|-----|---------|

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Workers (professional)         |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 773                            | mg/kg/d |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | Dermal exposure                |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 699                            | mg/kg/d |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Workers (professional)         |                   |
| Duration of exposure | Long-term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 2035                           | mg/m <sup>3</sup> |

|                      |                                |         |
|----------------------|--------------------------------|---------|
| Type of value        | Derived No Effect Level (DNEL) |         |
| Reference group      | Consumer                       |         |
| Duration of exposure | Long-term                      |         |
| Route of exposure    | inhalative                     |         |
| Mode of action       | Systemic effects               |         |
| Concentration        | 608                            | mg/kg/d |

### **Predicted No Effect Concentration (PNEC)**

#### **1-methoxy-2-propanol**

|               |            |      |
|---------------|------------|------|
| Type of value | PNEC       |      |
| Type          | Freshwater |      |
| Concentration | 10         | mg/l |

|               |           |      |
|---------------|-----------|------|
| Type of value | PNEC      |      |
| Type          | Saltwater |      |
| Concentration | 1         | mg/l |

|               |                  |      |
|---------------|------------------|------|
| Type of value | PNEC             |      |
| Conditions    | sporadic release |      |
| Concentration | 100              | mg/l |

|               |                      |       |
|---------------|----------------------|-------|
| Type of value | PNEC                 |       |
| Type          | Fresh water sediment |       |
| Concentration | 52,3                 | mg/kg |

|               |                    |       |
|---------------|--------------------|-------|
| Type of value | PNEC               |       |
| Type          | saltwater sediment |       |
| Concentration | 5,2                | mg/kg |

|               |      |  |
|---------------|------|--|
| Type of value | PNEC |  |
| Type          | Soil |  |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|               |      |       |
|---------------|------|-------|
| Concentration | 4,59 | mg/kg |
|---------------|------|-------|

**ethyl acetate**

|               |           |      |
|---------------|-----------|------|
| Type of value | PNEC      |      |
| Type          | Saltwater |      |
| Concentration | 0,026     | mg/l |

|               |            |      |
|---------------|------------|------|
| Type of value | PNEC       |      |
| Type          | Freshwater |      |
| Concentration | 0,26       | mg/l |

|               |      |       |
|---------------|------|-------|
| Type of value | PNEC |       |
| Type          | Soil |       |
| Concentration | 0,24 | mg/kg |

|               |                              |      |
|---------------|------------------------------|------|
| Type of value | PNEC                         |      |
| Type          | Sewage treatment plant (STP) |      |
| Concentration | 650                          | mg/l |

|               |                    |       |
|---------------|--------------------|-------|
| Type of value | PNEC               |       |
| Type          | saltwater sediment |       |
| Concentration | 0,125              | mg/kg |

|               |                      |       |
|---------------|----------------------|-------|
| Type of value | PNEC                 |       |
| Type          | Fresh water sediment |       |
| Concentration | 1,25                 | mg/kg |

|               |                  |      |
|---------------|------------------|------|
| Type of value | PNEC             |      |
| Conditions    | sporadic release |      |
| Concentration | 1,65             | mg/l |

**n-butyl acetate**

|               |            |      |
|---------------|------------|------|
| Type of value | PNEC       |      |
| Type          | Freshwater |      |
| Concentration | 0,18       | mg/l |

|               |           |      |
|---------------|-----------|------|
| Type of value | PNEC      |      |
| Type          | Saltwater |      |
| Concentration | 0,018     | mg/l |

|               |                              |      |
|---------------|------------------------------|------|
| Type of value | PNEC                         |      |
| Type          | Sewage treatment plant (STP) |      |
| Concentration | 35,6                         | mg/l |

|               |                  |      |
|---------------|------------------|------|
| Type of value | PNEC             |      |
| Type          | Water            |      |
| Conditions    | sporadic release |      |
| Concentration | 0,36             | mg/l |

|               |                      |       |
|---------------|----------------------|-------|
| Type of value | PNEC                 |       |
| Type          | Fresh water sediment |       |
| Concentration | 0,981                | mg/kg |



Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|               |                              |       |
|---------------|------------------------------|-------|
| Type of value | PNEC                         |       |
| Type          | saltwater sediment           |       |
| Concentration | 0,0981                       | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Soil                         |       |
| Concentration | 0,0903                       | mg/kg |
| <b>xylene</b> |                              |       |
| Type of value | PNEC                         |       |
| Type          | Freshwater                   |       |
| Concentration | 0,327                        | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Saltwater                    |       |
| Concentration | 0,327                        | mg/l  |
| Type of value | PNEC                         |       |
| Type          | Fresh water sediment         |       |
| Concentration | 12,46                        | mg/kg |
| Type of value | PNEC                         |       |
| Type          | saltwater sediment           |       |
| Concentration | 12,46                        | mg/kg |
| Type of value | PNEC                         |       |
| Type          | Soil                         |       |
| Concentration | 2,31                         | mg/kg |
| Type of value | PNEC                         |       |
| Type          | Sewage treatment plant (STP) |       |
| Concentration | 6,58                         | mg/l  |

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7 mm

Breakthrough time  $\geq$  30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** liquid

**Colour** black

**Odour** solvent-like

#### Melting point

Remarks not determined

#### Freezing point

Remarks not determined

#### Boiling point or initial boiling point and boiling range

Value 74 to 214 °C

#### Flammability

not determined

#### Upper and lower explosive limits

Remarks not determined

#### Flash point

Value < 21 °C

#### Ignition temperature

Remarks not determined

#### Decomposition temperature

Remarks not determined

#### Viscosity

Remarks not determined

#### Solubility(ies)

Remarks not determined

#### Partition coefficient n-octanol/water (log value)

Remarks not determined

#### Vapour pressure

Value < 1000 hPa

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

**Density and/or relative density**

Value appr. 0,9 kg/l

**Relative vapour density**

Remarks not determined

**Particle characteristics**

Remarks not determined

**9.2. Other information**

**Odour threshold**

Remarks not determined

**Evaporation rate**

Remarks not determined

**Solubility in water**

Remarks not determined

**Efflux time**

Value 25 s  
Temperature 20 °C  
Method DIN EN ISO 2431 - 3 mm

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**Non-volatile content**

Value 30 %

**Other information**

This information is not available.

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

**10.4. Conditions to avoid**

Isolate from sources of heat, sparks and open flame.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

#### Acute dermal toxicity

|         |   |       |
|---------|---|-------|
| ATE     | > 10.000  | mg/kg |
| Method  | calculated value (Regulation (EC) No. 1272/2008)                  |       |
| Remarks | Based on available data, the classification criteria are not met. |       |

#### Acute dermal toxicity (Components)

##### xylene

|        |                            |       |
|--------|----------------------------|-------|
| ATE    | 2000                       | mg/kg |
| Source | alle Daten über 2000 mg/kg |       |

#### Acute inhalational toxicity

|                     |   |      |
|---------------------|---|------|
| ATE                 | > 20  | mg/l |
| Administration/Form | Dust/Mist   |      |
| Method              | calculated value (Regulation (EC) No. 1272/2008)                  |      |
| Remarks             | Based on available data, the classification criteria are not met. |      |

#### Acute inhalative toxicity (Components)

##### xylene

|                      |                        |      |
|----------------------|------------------------|------|
| ATE                  | 5                      | mg/l |
| Duration of exposure | 4                      | h    |
| Administration/Form  | Dust/Mist              |      |
| Source               | alle Werte über 5 mg/l |      |

#### Skin corrosion/irritation

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

#### Skin corrosion/irritation (Components)

##### xylene

|                    |                                |
|--------------------|--------------------------------|
| Species            | rabbit                         |
| Observation Period | 72 h                           |
| evaluation         | Irritating to skin.            |
| Source             | 2 (reliable with restrictions) |

#### Serious eye damage/irritation

|            |  |
|------------|--|
| evaluation | irritant   |
| Method     | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks    | The classification criteria are met.               |

#### Serious eye damage/irritation (Components)

##### ethyl acetate

|                    |                                |
|--------------------|--------------------------------|
| Species            | rabbit                         |
| Observation Period | 24 h                           |
| evaluation         | Irritating to eyes.            |
| Source             | 2 (reliable with restrictions) |

##### xylene

|         |        |
|---------|--------|
| Species | rabbit |
|---------|--------|

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

evaluation  
Source Irritating to eyes.  
2 (reliable with restrictions)

### Sensitization

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Sensitization (Components)

#### 12-hydroxy-N-[6-(12-hydroxyoctadecanamido)hexyl]octadecanamide

evaluation May cause sensitization by skin contact.

### Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Reproductive toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Carcinogenicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity (STOT)

#### Single exposure

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks The classification criteria are met.  
evaluation May cause drowsiness or dizziness.

#### Repeated exposure

Remarks Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity (STOT) (Components)

#### 1-methoxy-2-propanol

##### Specific target organ toxicity - single exposure

Organs: Nervous system  
Remarks Possible narcotic effects (drowsiness, dizziness).

#### ethyl acetate

##### Specific target organ toxicity - single exposure

Organs: Nervous system  
Remarks Possible narcotic effects (drowsiness, dizziness).

#### n-butyl acetate

##### Specific target organ toxicity - repeated exposure

Organs: Nervous system  
Remarks Possible narcotic effects (drowsiness, dizziness).

#### xylene

##### Specific target organ toxicity - single exposure

Route of exposure inhalative  
Organs: Respiratory tract  
Remarks May cause respiratory irritation.

#### Hydrocarbons, C9, aromatics

##### Specific target organ toxicity - single exposure

Route of exposure inhalative

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

Remarks Possible narcotic effects (drowsiness, dizziness).

#### Hydrocarbons, C9, aromatics

##### Specific target organ toxicity - single exposure

Remarks Possible narcotic effects (drowsiness, dizziness).

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

##### Specific target organ toxicity - single exposure

evaluation May cause drowsiness or dizziness.

Organs: Nervous system

Remarks Possible narcotic effects (drowsiness, dizziness).

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

#### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

#### Other information

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### Hydrocarbons, C9, aromatics

|                      |                                     |      |
|----------------------|-------------------------------------|------|
| Species              | Oncorhynchus mykiss (rainbow trout) |      |
| LC50                 | 9,2                                 | mg/l |
| Duration of exposure | 96                                  | h    |

#### Daphnia toxicity (Components)

##### Hydrocarbons, C9, aromatics

|                      |                            |      |
|----------------------|----------------------------|------|
| Species              | Daphnia magna (Water flea) |      |
| EC50                 | 3,2                        | mg/l |
| Duration of exposure | 48                         | h    |

##### Hydrocarbons, C9, aromatics

|                      |                            |      |
|----------------------|----------------------------|------|
| Species              | Daphnia magna (Water flea) |      |
| NOEC                 | 2,14                       | mg/l |
| Duration of exposure | 21                         | d    |

##### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

|                      |                            |      |
|----------------------|----------------------------|------|
| Species              | Daphnia magna (Water flea) |      |
| EC50                 | 3                          | mg/l |
| Duration of exposure | 48                         | h    |

##### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

|                      |                            |      |
|----------------------|----------------------------|------|
| Species              | Daphnia magna (Water flea) |      |
| NOEC                 | 0,17                       | mg/l |
| Duration of exposure | 21                         | d    |

#### Algae toxicity (Components)

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

#### Hydrocarbons, C9, aromatics

|                      |   |    |          |
|----------------------|---|----|----------|
| Species              | Pseudokirchneriella subcapitata (green algae) |    |          |
| EC50                 | 2,6   | to | 2,9 mg/l |
| Duration of exposure | 72  | h  |          |

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

|                      |   |      |  |
|----------------------|---|------|--|
| Species              | Pseudokirchneriella subcapitata (green algae) |      |  |
| EC50                 | 10  | mg/l |  |
| Duration of exposure | 72  | h    |  |
| Method               | OECD 201                                      |      |  |

### 12.2. Persistence and degradability

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Biodegradability (Components)

##### Hydrocarbons, C9, aromatics

evaluation Readily biodegradable.

##### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

evaluation Readily biodegradable.

### 12.3. Bioaccumulative potential

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Partition coefficient n-octanol/water (log value)

Remarks not determined

### 12.4. Mobility in soil

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Mobility in soil

no data available

### 12.5. Results of PBT and vPvB assessment

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

### 12.6 Endocrine disrupting properties

#### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

### 12.7. Other adverse effects

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.



Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

|                |  |
|----------------|--|
| EWC waste code | 080111 - waste paint and varnish containing organic solvents or other dangerous substances |
| EWC waste code | 200127 - paint, inks, adhesives and resins containing dangerous substances                 |

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### modified product

|                |  |
|----------------|--|
| EWC waste code | 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances               |
| EWC waste code | 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances |

#### Dried residues

|                |   |
|----------------|---|
| EWC waste code | 080112 - waste lacquers and waste paint except those falling under 080111 |
|----------------|---|

#### Disposal recommendations for packaging

|                |   |
|----------------|---|
| EWC waste code | 150110 - packaging containing residues of or contaminated by dangerous substances |
|----------------|---|

Completely emptied packagings can be given for recycling.

## SECTION 14: Transport information




Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|                                  | Land transport ADR/RID  | Marine transport<br>IMDG/GGVSee  | Air transport ICAO/IATA   |
|----------------------------------|---|--|---|
| Tunnel restriction code          | D/E   |  |   |
| 14.1. UN number                  | 1263  | 1263   | 1263  |
| 14.2. UN proper shipping name    | PAINT   | PAINT  | PAINT   |
| 14.3. Transport hazard class(es) | 3   | 3  | 3   |
| Label                            |  |  |  |
| 14.4. Packing group              | II  | II   | II  |
| Special provision                | 640D  |  |   |
| Limited Quantity                 | 5 l   |  |   |
| Transport category               | 2   |  |   |
| 14.5. Environmental hazards      |   | no   |   |

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU) 70 % 700 g/l

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

|        |   |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H201   | Explosive; mass explosion hazard.                     |
| H225   | Highly flammable liquid and vapour.                   |
| H226   | Flammable liquid and vapour.                          |
| H304   | May be fatal if swallowed and enters airways.         |
| H312   | Harmful in contact with skin.                         |
| H315   | Causes skin irritation.                               |
| H317   | May cause an allergic skin reaction.                  |
| H319   | Causes serious eye irritation.                        |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|      |   |
|------|---|
| H332 | Harmful if inhaled.                                     |
| H335 | May cause respiratory irritation.                       |
| H336 | May cause drowsiness or dizziness.                      |
| H411 | Toxic to aquatic life with long lasting effects.        |
| H413 | May cause long lasting harmful effects to aquatic life. |

### **CLP categories listed in Chapter 3**

|                   |  |
|-------------------|--|
| Acute Tox. 4      | Acute toxicity, Category 4                                   |
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic, Category 2    |
| Aquatic Chronic 4 | Hazardous to the aquatic environment, chronic, Category 4    |
| Asp. Tox. 1       | Aspiration hazard, Category 1                                |
| Expl. 1.1         | Explosive, Division 1.1                                      |
| Eye Irrit. 2      | Eye irritation, Category 2                                   |
| Flam. Liq. 2      | Flammable liquid, Category 2                                 |
| Flam. Liq. 3      | Flammable liquid, Category 3                                 |
| Skin Irrit. 2     | Skin irritation, Category 2                                  |
| Skin Sens. 1      | Skin sensitization, Category 1                               |
| STOT SE 3         | Specific target organ toxicity - single exposure, Category 3 |

### **Abbreviations**

Flam. Liq - Flammable liquids  
RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
IMDG - International Maritime Code for Dangerous Goods  
IATA - International Air Transport Association  
IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)  
ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)  
GHS - Globally Harmonized System of Classification and Labelling of Chemicals  
EINECS - European Inventory of Existing Commercial Chemical Substances  
CAS - Chemical Abstracts Service (division of the American Chemical Society)  
GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)  
LOAEL - Lowest Observed Adverse Effect Level  
LOEL - Lowest Observed Effect Level  
NOAEL - No Observed Adverse Effect Level  
NOEC - No Observed Effect Concentration  
NOEL - No Observed Effect Level  
OECD - Organisation for Economic Cooperation and Development  
VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

## **Annex to the extended Safety Data Sheet (eSDS)**

**Short title of the exposure scenario**

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

ES003 - Professional uses: Non industrial spraying (inside)

### Use of the substance/preparation

Surface treatment of wood and other materials

### Use

|        |  |
|--------|--|
| SU22   | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a  | Wide dispersive indoor use of processing aids in open systems                                    |
| ERC8c  | Wide dispersive indoor use resulting in inclusion into or onto a matrix                          |
| PROC11 | Non industrial spraying  |

## Contributing exposure scenario controlling environmental exposure

### Use

|       |   |
|-------|---|
| ERC8a | Wide dispersive indoor use of processing aids in open systems           |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |

### Physical form

liquid

### Hazardous ingredients

#### n-butyl acetate

|                  |                  |
|------------------|------------------|
| CAS No.          | 123-86-4         |
| EINECS no.       | 204-658-1        |
| Registration no. | 01-2119485493-29 |
| Concentration    | >= 10 < 25 %     |

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

|                  |                  |
|------------------|------------------|
| EINECS no.       | 920-750-0        |
| Registration no. | 01-2119473851-33 |
| Concentration    | >= 1 < 10 %      |

#### ethyl acetate

|                  |                  |
|------------------|------------------|
| CAS No.          | 141-78-6         |
| EINECS no.       | 205-500-4        |
| Registration no. | 01-2119475103-46 |
| Concentration    | >= 25 < 50 %     |

#### 1-methoxy-2-propanol

|                  |                  |
|------------------|------------------|
| CAS No.          | 107-98-2         |
| EINECS no.       | 203-539-1        |
| Registration no. | 01-2119457435-35 |
| Concentration    | >= 1 < 10 %      |

#### cellulose nitrate < =12.6 % N

|               |             |
|---------------|-------------|
| CAS No.       | 9004-70-0   |
| Concentration | >= 1 < 10 % |

#### Hydrocarbons, C9, aromatics

|                  |                  |
|------------------|------------------|
| CAS No.          | 128601-23-0      |
| EINECS no.       | 918-668-5        |
| Registration no. | 01-2119455851-35 |
| Concentration    | >= 1 < 10 %      |

#### xylene

|                  |                  |
|------------------|------------------|
| CAS No.          | 1330-20-7        |
| EINECS no.       | 215-535-7        |
| Registration no. | 01-2119488216-32 |
| Concentration    | >= 1 < 10 %      |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

**Naphtha (petroleum), hydrotreated heavy**

CAS No. 64742-48-9

EINECS no. 265-150-3

Registration no. 01-2119471843-32

Concentration  $\geq$  1 < 10 %

**Maximum amount used per time or activity**

Emission days per site:  $\leq$  250

**Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Volatile organic substances will volatilise into the atmospheric air inside.

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter soil, waterways or waste water canal.

Dispose of rinse water in accordance with local and national regulations.

**Waste water**

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

**Exhaust air**

Keep container closed. Avoid release to the environment.

**Soil**

Floors should be impervious, resistant to liquids and easy to clean.

**Disposal recommendations for the product**

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances  
200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

**modified product**

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances  
080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

**Dried residues**

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

**Disposal recommendations for packaging**

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Completely emptied packagings can be given for recycling.

**Contributing exposure scenario controlling worker exposure (professional)**

**Short title of the exposure scenario**

Substance number: CES006

**Use**

SU22

Professional uses: Public domain (administration, education, entertainment,

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|   |                         |
|---|-------------------------|
| PROC11  | services, craftsmen)    |
| <b>Physical form</b>  | Non industrial spraying |
|   | liquid                  |
| <b>Hazardous ingredients</b>  |                         |
| <b>n-butyl acetate</b>  |                         |
| CAS No.   | 123-86-4                |
| EINECS no.  | 204-658-1               |
| Registration no.  | 01-2119485493-29        |
| Concentration   | >= 10 < 25 %            |
| <b>Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics</b>                              |                         |
| EINECS no.  | 920-750-0               |
| Registration no.  | 01-2119473851-33        |
| Concentration   | >= 1 < 10 %             |
| <b>ethyl acetate</b>  |                         |
| CAS No.   | 141-78-6                |
| EINECS no.  | 205-500-4               |
| Registration no.  | 01-2119475103-46        |
| Concentration   | >= 25 < 50 %            |
| <b>1-methoxy-2-propanol</b>   |                         |
| CAS No.   | 107-98-2                |
| EINECS no.  | 203-539-1               |
| Registration no.  | 01-2119457435-35        |
| Concentration   | >= 1 < 10 %             |
| <b>cellulose nitrate &lt; =12.6 % N</b>   |                         |
| CAS No.   | 9004-70-0               |
| Concentration   | >= 1 < 10 %             |
| <b>Hydrocarbons, C9, aromatics</b>  |                         |
| CAS No.   | 128601-23-0             |
| EINECS no.  | 918-668-5               |
| Registration no.  | 01-2119455851-35        |
| Concentration   | >= 1 < 10 %             |
| <b>xylene</b>   |                         |
| CAS No.   | 1330-20-7               |
| EINECS no.  | 215-535-7               |
| Registration no.  | 01-2119488216-32        |
| Concentration   | >= 1 < 10 %             |
| <b>Naphtha (petroleum), hydrotreated heavy</b>  |                         |
| CAS No.   | 64742-48-9              |
| EINECS no.  | 265-150-3               |
| Registration no.  | 01-2119471843-32        |
| Concentration   | >= 1 < 10 %             |
| <b>Maximum amount used per time or activity</b>   |                         |
| Duration of exposure  | <= 8 h/d                |
| Frequency of exposure   | <= 220 d/a              |
| <b>Other relevant operational conditions</b>  |                         |
| Use: Room temperature   |                         |
| Drying and through-curing takes place at ambient temperature or at higher temperatures. |                         |
| Volatile organic substances will volatilise into the atmospheric air inside.            |                         |
| Read attached instructions before use.  |                         |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

## Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

## Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

## Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7

Breakthrough time  $\geq$  30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

## Eye protection

Wear eye glasses with side protection according to EN 166.

## Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (professional)

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU22                             |
| PROC                              | PROC10                           |
| Assessment method                 | inhalation, long-term - systemic |
| Exposure assessment               | 262,79 mg/m <sup>3</sup>         |
| Exposure assessment (method)      | ESIG GES tool                    |
| Risk characterisation ratio (RCR) | 0,71                             |
| Lead substance                    | 1-methoxy-2-propanol             |

### Workers (professional)

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU22                         |
| PROC                              | PROC10                       |
| Assessment method                 | dermal, long-term - systemic |
| Exposure assessment               | 5,49 mg/kg/d                 |
| Exposure assessment (method)      | ESIG GES tool                |
| Risk characterisation ratio (RCR) | 0,11                         |
| Lead substance                    | 1-methoxy-2-propanol         |



Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

**Workers (professional)**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU22                             |
| PROC                              | PROC11                           |
| Assessment method                 | inhalation, long-term - systemic |
|                                   | Indoor use                       |
| Exposure assessment               | 37,54 mg/m <sup>3</sup>          |
| Exposure assessment (method)      | ESIG GES tool                    |
| Risk characterisation ratio (RCR) | 0,1                              |
| Lead substance                    | 1-methoxy-2-propanol             |

**Workers (professional)**

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU22                         |
| PROC                              | PROC11                       |
| Assessment method                 | dermal, long-term - systemic |
|                                   | Indoor use                   |
| Exposure assessment               | 2,14 mg/kg/d                 |
| Exposure assessment (method)      | ESIG GES tool                |
| Risk characterisation ratio (RCR) | 0,04                         |
| Lead substance                    | 1-methoxy-2-propanol         |

**Workers (professional)**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU22                             |
| PROC                              | PROC11                           |
| Assessment method                 | inhalation, long-term - systemic |
|                                   | Outdoor use                      |
| Exposure assessment               | 131,4 mg/m <sup>3</sup>          |
| Exposure assessment (method)      | ESIG GES tool                    |
| Risk characterisation ratio (RCR) | 0,36                             |
| Lead substance                    | 1-methoxy-2-propanol             |

**Workers (professional)**

|                                   |                              |
|-----------------------------------|------------------------------|
| SU                                | SU22                         |
| PROC                              | PROC11                       |
| Assessment method                 | dermal, long-term - systemic |
|                                   | Outdoor use                  |
| Exposure assessment               | 21,43 mg/kg/d                |
| Exposure assessment (method)      | ESIG GES tool                |
| Risk characterisation ratio (RCR) | 0,42                         |
| Lead substance                    | 1-methoxy-2-propanol         |

**Workers (professional)**

|                                   |                                  |
|-----------------------------------|----------------------------------|
| SU                                | SU22                             |
| PROC                              | PROC13                           |
| Assessment method                 | inhalation, long-term - systemic |
|                                   | Indoor use                       |
| Exposure assessment               | 262,79 mg/m <sup>3</sup>         |
| Exposure assessment (method)      | ESIG GES tool                    |
| Risk characterisation ratio (RCR) | 0,71                             |
| Lead substance                    | 1-methoxy-2-propanol             |

**Workers (professional)**

|                   |                              |
|-------------------|------------------------------|
| SU                | SU22                         |
| PROC              | PROC13                       |
| Assessment method | dermal, long-term - systemic |
|                   | Indoor use                   |

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

Exposure assessment 13,71 mg/kg/d  
Exposure assessment (method) ESIG GES tool  
Risk characterisation ratio (RCR) 0,27  
Lead substance 1-methoxy-2-propanol

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method dermal, long-term - systemic  
Exposure assessment 63 mg/kg/d  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,022  
Lead substance ethyl acetate

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method inhalation, long-term - local  
Exposure assessment 734 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,018  
Lead substance ethyl acetate

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method dermal, long-term - systemic  
Exposure assessment 63 mg/kg/d  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,034  
Lead substance ethyl acetate

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method inhalation, long-term - local  
Exposure assessment 734 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,018  
Lead substance ethyl acetate

**Workers (professional)**

SU SU22  
PROC PROC11  
Assessment method Long-term  
inhalative  
Exposure assessment 242 mg/m<sup>3</sup>  
Exposure assessment (method) ECETOC TRA  
Risk characterisation ratio (RCR) 0,504  
Lead substance n-butyl acetate

**Workers (professional)**

SU SU22  
PROC PROC10  
Assessment method inhalative  
Indoor use

Trade name: Hesse FANTASTIC-COLOR Pigment glaze PEX TL 158-FT

Version: 9 / GB

Revision: 30.11.2022

Replaces Version: 8 / GB

Print date: 16.01.23

|                                   |            |                   |
|-----------------------------------|------------|-------------------|
| Exposure assessment               | 0,05       | mg/m <sup>3</sup> |
| Exposure assessment (method)      | ECETOC TRA |                   |
| Risk characterisation ratio (RCR) | 0,172      |                   |
| Lead substance                    | xylene     |                   |

**Workers (professional)**

|                   |            |
|-------------------|------------|
| SU                | SU22       |
| PROC              | PROC11     |
| Assessment method | inhalative |
|                   | Indoor use |

|                                   |            |                   |
|-----------------------------------|------------|-------------------|
| Exposure assessment               | 0,1        | mg/m <sup>3</sup> |
| Exposure assessment (method)      | ECETOC TRA |                   |
| Risk characterisation ratio (RCR) | 0,34       |                   |
| Lead substance                    | xylene     |                   |

**Workers (professional)**

|                   |            |
|-------------------|------------|
| SU                | SU22       |
| PROC              | PROC13     |
| Assessment method | inhalative |
|                   | Indoor use |

|                                   |            |                   |
|-----------------------------------|------------|-------------------|
| Exposure assessment               | 0,05       | mg/m <sup>3</sup> |
| Exposure assessment (method)      | ECETOC TRA |                   |
| Risk characterisation ratio (RCR) | 0,172      |                   |
| Lead substance                    | xylene     |                   |

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.