

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse Precious wood stain PEX BE XX-FT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG
Warendorfer Strasse 21
59075 Hamm (Germany)
Telephone no. +49 (0) 2381 963-00
Fax no. +49 (0) 2381 963-849
E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

SECTION 2: Hazards identification ***

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)
Skin Sens. 1 H317
Eye Irrit. 2 H319

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008
For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Warning

Hazard statements ***

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements ***

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains *** Acid Brown 355; 1,2-benzisothiazol-3(2H)-one; Acid Violet 90

2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients ***

Hazardous ingredients ***

2-(2-butoxyethoxy)ethanol

CAS No.	112-34-5			
EINECS no.	203-961-6			
Registration no.	01-2119475104-44			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)	Eye Irrit. 2		H319	

Acid Brown 355

CAS No.	84989-26-4			
EINECS no.	284-915-2			
Registration no.	01-2120077343-57			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)	Skin Sens. 1		H317	
	Aquatic Chronic 3		H412	

Acid Violet 90

CAS No.	61916-41-4			
EINECS no.	263-319-6			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)	Eye Irrit. 2		H319	
	Skin Sens. 1B		H317	
	Aquatic Chronic 3		H412	

1,2-benzisothiazol-3(2H)-one

CAS No.	2634-33-5			
EINECS no.	220-120-9			
Registration no.	01-2120761540-60			
Concentration	>= 0,036	<	0,1	%
Classification (Regulation (EC) No. 1272/2008)	Acute Tox. 4		H302	
	Skin Irrit. 2		H315	
	Eye Dam. 1		H318	

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Acute Tox. 2	H330

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1	H317	>= 0,036 %
--------------	------	------------

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical attention. First aider: Pay attention to self-protection! Get medical advice/attention if you feel unwell. Remove affected person from danger area, lay him down.

After inhalation

No special measures required.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Contact of the product with skin or eyes may cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

No materials to be especially mentioned.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

No special measures required.

Other information

Do not allow run-off from fire fighting to enter drains or water courses. Standard procedure for chemical

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

fires. Cool closed containers exposed to fire with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not inhale aerosols.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Do not inhale aerosols. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

No special measures necessary if used correctly.

7.2. Conditions for safe storage, including any incompatibilities

Storage stability

Protect from frost.

Requirements for storage rooms and vessels

Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep only in the original container in a cool, well ventilated place.

Hints on storage assembly

No special measures required.

Storage classes

Storage class according to TRGS 510 10 Flammable liquids

Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Store in accordance with the particular national regulations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

-

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

Derived No/Minimal Effect Levels (DNEL/DMEL)

2-(2-butoxyethoxy)ethanol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	14	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	20	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	10	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	10	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	7,5	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	10	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	1,3	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	5	mg/m ³

Acid Brown 355

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	0,51	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	0,12	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	0,04	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,36	mg/kg/d

1,2-benzisothiazol-3(2H)-one

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	6,81	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,966	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,2	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,345	mg/kg

Predicted No Effect Concentration (PNEC)

2-(2-butoxyethoxy)ethanol

Type of value	PNEC	
Type	Freshwater	
Concentration	1	mg/l

Type of value	PNEC	
Type	marine water	
Concentration	0,1	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	4	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,4	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	200	mg/l

Type of value	PNEC	
Type	Soil	
Concentration	0,4	mg/l

Acid Brown 355

Type of value	PNEC	
Type	Freshwater	
Concentration	0,01	mg/l

Type of value	PNEC	
Type	marine water	
Concentration	0,001	mg/l

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,038	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,004	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,002	mg/kg
1,2-benzisothiazol-3(2H)-one		
Type of value	PNEC	
Type	Freshwater	
Concentration	4,03	µg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,403	µg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	1,03	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,0499	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,00499	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	3	mg/kg

8.2. Exposure controls

Exposure controls

No special measures required.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.
Recommended Filter type: Half mask with a particle filter P2 (EN 143).

Hand protection

PVC gloves

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

Glove material

Appropriate Material

Nitrile rubber

Material thickness

\geq 0,4 mm

Breakthrough time

\geq 30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

liquid

Colour

coloured

Odour

characteristic

Melting point

Remarks

not determined

Freezing point

Remarks

not determined

Boiling point or initial boiling point and boiling range

Value

100

to

100

°C

Flammability

not determined

Upper and lower explosive limits

Remarks

not determined

Flash point

Value

> 60

°C

Auto-ignition temperature

Remarks

not determined

Decomposition temperature

Remarks

not determined

pH value

Value

8

Concentration/H₂O

100

Viscosity

Remarks

not determined

Solubility(ies)

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

Value appr. 1,012 kg/l
Temperature 20 °C

Relative vapour density

Remarks not determined

Particle characteristics

Remarks not determined

9.2. Other information

Odour threshold

Remarks not determined

Evaporation rate

Remarks not determined

Solubility in water

Remarks not determined

Efflux time

Value 20 to 48 s
Temperature 20 °C
Method DIN 53211 4 mm

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

Non-volatile content

Value 4 %

Other information

This information is not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

No special restrictions on storage with other products.

10.6. Hazardous decomposition products

No decomposition if used as prescribed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Acute oral toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species	rat	
LD50	450	mg/kg
Source	Annex VI Hazardous Substance	

Acute dermal toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Acute inhalational toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)

1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to skin.
------------	---------------------

Acid Violet 90

evaluation	Skin irritation
------------	-----------------

Serious eye damage/irritation

evaluation	irritant
Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	The classification criteria are met.

Serious eye damage/irritation (Components)

2-(2-butoxyethoxy)ethanol

Species	rabbit
evaluation	Irritating to eyes.
Source	2 (reliable with restrictions)

Acid Brown 355

Species	rabbit
evaluation	Irritating to eyes.

1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to eyes.
------------	---------------------

Acid Violet 90

evaluation	Irritating to eyes.
------------	---------------------

Sensitization

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

evaluation	May cause sensitization by skin contact.
Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	The classification criteria are met.

Sensitization (Components)

1,2-benzisothiazol-3(2H)-one

Reference substance	1,2-benzisothiazol-3(2H)-one
evaluation	May cause sensitization by skin contact.

Acid Brown 355

Species	mouse
evaluation	May cause sensitization by skin contact.
Source	2 (reliable with restrictions)

Mutagenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Reproductive toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Carcinogenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

No toxicological data are available.

SECTION 12: Ecological information

12.1. Toxicity

General information

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)

Acid Brown 355

Species	Danio rerio (zebra fish)	
LC50	40	mg/l
Duration of exposure	96	h

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

1,2-benzisothiazol-3(2H)-one

Species	Oncorhynchus mykiss (rainbow trout)	
LC50	2,18	mg/l
Duration of exposure	96	h

Acid Violet 90

Species	Poecilia reticulata (guppy)	
LC50	> 100	mg/l
Duration of exposure	96	h

Daphnia toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species	Daphnia magna (Water flea)	
EC50	2,94	mg/l
Duration of exposure	48	h

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

Acid Brown 355

Value	< 10	%
-------	------	---

1,2-benzisothiazol-3(2H)-one

evaluation	Not readily biodegradable.
------------	----------------------------

Chemical oxygen demand (COD) (Components)

Acid Brown 355

Value	990	g O2/g
-------	-----	--------

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient n-octanol/water (log value)

Remarks	not determined
---------	----------------

Octanol/water partition coefficient (log Pow) (Components)

Acid Violet 90

log Pow	-1,796
Temperature	20 °C

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

Results of PBT and vPvB assessment

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

The product contains no PBT substances
The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

For this subsection there is no ecotoxicological data available on the product as such.

General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

Information for all modes of transport

14.6. Special precautions for user

See Sections 6 to 8

Other information

14.7. Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restriction according to annex XVII to regulation (EU) No 1907/2006

The product is subject to restrictions according to Annex XVII Regulation (EU) No. 1907/2006: Entry No. 3.

Trade name: Hesse Precious wood stain PEX BE XX-FT

Version: 23 / WORLD

Revision: 22.09.2025

Replaces Version: 22 / WORLD

Print date: 07.11.25

15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, Category 1B

Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.