

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

Identified Uses

	REACHSET 1000
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying
	REACHSET 2001
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying
	REACHSET 2003
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG
Warendorfer Strasse 21
59075 Hamm (Germany)
Telephone no. +49 (0) 2381 963-00
Fax no. +49 (0) 2381 963-849
E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 2 H225

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Eye Irrit. 2	H319
Repr. 2	H361d
STOT SE 3	H336
Aquatic Chronic 3	H412

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008
For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains	toluene; 2-methylpropan-1-ol; acetone; ethyl acetate
----------	--

Supplemental information

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

Hazardous ingredients

n-butyl acetate	
CAS No.	123-86-4

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

EINECS no. 204-658-1
Registration no. 01-2119485493-29
Concentration ≥ 25 < 50 %
Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 3 H226
STOT SE 3 H336
EUH066
Nervous system

isobutyl acetate

CAS No. 110-19-0
EINECS no. 203-745-1
Registration no. 01-2119488971-22
Concentration ≥ 10 < 20 %
Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 2 H225
STOT SE 3 H336
EUH066
Nervous system

ethyl acetate

CAS No. 141-78-6
EINECS no. 205-500-4
Registration no. 01-2119475103-46
Concentration ≥ 10 < 20 %
Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 2 H225
Eye Irrit. 2 H319
STOT SE 3 H336
EUH066
Nervous system

acetone

CAS No. 67-64-1
EINECS no. 200-662-2
Registration no. 01-2119471330-49
Concentration ≥ 1 < 10 %
Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 2 H225
Eye Irrit. 2 H319
STOT SE 3 H336
EUH066
Nervous system

Hydrocarbons, C9, aromatics

CAS No. 128601-23-0
EINECS no. 918-668-5
Registration no. 01-2119455851-35
Concentration ≥ 3 < 10 %
Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 3 H226
Asp. Tox. 1 H304
Aquatic Chronic 2 H411
STOT SE 3 H335
STOT SE 3 H336
EUH066
Respiratory tract
Nervous system

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

toluene

CAS No.	108-88-3		
EINECS no.	203-625-9		
Registration no.	01-2119471310-51		
Concentration	>= 3	< 4	%
Classification (Regulation (EC) No. 1272/2008)			
Flam. Liq. 2	H225		
Repr. 2	H361d		
Asp. Tox. 1	H304		
STOT RE 2	H373		
Skin Irrit. 2	H315		
STOT SE 3	H336		Nervous system

2-methylpropan-1-ol

CAS No.	78-83-1		
EINECS no.	201-148-0		
Registration no.	01-2119484609-23		
Concentration	>= 1	< 3	%
Classification (Regulation (EC) No. 1272/2008)			
Flam. Liq. 3	H226		
STOT SE 3	H335		Respiratory tract
Skin Irrit. 2	H315		
Eye Dam. 1	H318		
STOT SE 3	H336		Nervous system

xylene

CAS No.	1330-20-7		
EINECS no.	215-535-7		
Registration no.	01-2119488216-32		
Concentration	>= 1	< 2	%
Classification (Regulation (EC) No. 1272/2008)			
Flam. Liq. 3	H226		
Acute Tox. 4	H332		Route of exposure: Inhalation exposure
Acute Tox. 4	H312		Route of exposure: Dermal exposure
Skin Irrit. 2	H315		
Asp. Tox. 1	H304		
STOT SE 3	H335		Respiratory tract; Route of exposure: inhalative
Eye Irrit. 2	H319		

ATE	Dermal exposure	2.000	mg/kg
ATE	Inhalation exposure, Dust/Mist	5	mg/l

Naphtha (petroleum), hydrotreated heavy

CAS No.	64742-48-9		
EINECS no.	919-857-5		
Registration no.	01-2119463258-33		
Concentration	>= 1	< 10	%
Classification (Regulation (EC) No. 1272/2008)			
Asp. Tox. 1	H304		

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Further ingredients

aluminium powder (stabilised)

CAS No.	7429-90-5				
EINECS no.	231-072-3				
Registration no.	01-2119529243-45				
Concentration	>= 1	<	10	%	
Advice: [3]					
Classification (Regulation (EC) No. 1272/2008)					
	Water-react. 2				H261
	Flam. Sol. 1				H228

Note

[3] Substance with occupational exposure limits

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical attention. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage classes

Storage class according to TRGS 510 3 Flammable liquid

Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

-

Derived No/Minimal Effect Levels (DNEL/DMEL)

2-methylpropan-1-ol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	310	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	55	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Local effects	
Concentration	25	mg/kg/d

acetone

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1210	mg/m ³

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	186	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	2420	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1210	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	62	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	62	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	200	mg/m ³

ethyl acetate

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	63	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	734	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	734	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	1468	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1468	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	734	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	734	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	37	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	367	mg/m ³

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	4,5	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	367	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Local effects	
Concentration	63	mg/kg

isobutyl acetate

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	10	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	5	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	600	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	600	mg/m ³

n-butyl acetate

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	600	mg/m ³

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	600	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	6	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	35,7	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Specific effects	
Concentration	2	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	Dermal exposure	
Mode of action	Specific effects	
Concentration	6	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	Dermal exposure	
Mode of action	Specific effects	
Concentration	11	mg/kg/d

toluene

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	343	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	384	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	192	mg/m ³

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	192	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	384	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	226	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	226	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	56,5	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	226	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	8,13	mg/kg/d

xylene

Type of value	Derived No Effect Level (DNEL)
Reference group	Consumer

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	125	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	212	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	65,3	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	260	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	174	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	442	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	221	mg/m ³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	289	mg/m ³

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	289	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	12,5	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Local effects	
Concentration	174	mg/kg/d

Hydrocarbons, C9, aromatics

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	25	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	11	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	150	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	11	mg/kg

aluminium powder (stabilised)

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	3,72	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	3,72	mg/m ³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	7,9	mg/kg/d

Predicted No Effect Concentration (PNEC)

2-methylpropan-1-ol

Type of value	PNEC	
Type	Freshwater	
Concentration	0,4	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,04	mg/l

Type of value	PNEC	
Conditions	sporadic release	
Concentration	11	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	1,52	mg/kg



Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,152	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	0,0699	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l

acetone

Type of value	PNEC	
Type	Freshwater	
Concentration	10,6	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	1,06	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	30,4	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	3,04	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	29,5	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

Type of value	PNEC	
Conditions	sporadic release	
Concentration	21	mg/l

ethyl acetate

Type of value	PNEC	
Type	Saltwater	
Concentration	0,026	mg/l

Type of value	PNEC	
Type	Freshwater	
Concentration	0,26	mg/l

Type of value	PNEC	
Type	Soil	
Concentration	0,24	mg/kg



Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	650	mg/l
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,125	mg/kg
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	1,25	mg/kg
Type of value	PNEC	
Conditions	sporadic release	
Concentration	1,65	mg/l
isobutyl acetate		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,17	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,017	mg/l
Type of value	PNEC	
Type	Water	
Conditions	sporadic release	
Concentration	0,34	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	200	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,877	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,0877	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,0755	mg/kg

n-butyl acetate

Type of value	PNEC	
Type	Freshwater	
Concentration	0,18	mg/l

Type of value	PNEC	
---------------	------	--

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type	Saltwater	
Concentration	0,018	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	35,6	mg/l
Type of value	PNEC	
Type	Water	
Conditions	sporadic release	
Concentration	0,36	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,981	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,0981	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	0,0903	mg/kg
toluene		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,68	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	16,39	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,89	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	13,61	mg/l
xylene		
Type of value	PNEC	
Type	Freshwater	
Concentration	0,327	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,327	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	12,46	mg/kg

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Type of value	PNEC	
Type	saltwater sediment	
Concentration	12,46	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	2,31	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	6,58	mg/l

aluminium powder (stabilised)

Type of value	PNEC	
Type	Freshwater	
Concentration	0,0749	mg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	20	mg/l

8.2. Exposure controls

Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material
Multilayer gloves made from
Appropriate Material Fluorinated rubber / butyl-rubber
Material thickness \geq 0,7 mm
Breakthrough time \geq 30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid
Colour coloured
Odour solvent-like

Melting point
Remarks not determined

Freezing point
Remarks not determined

Boiling point or initial boiling point and boiling range
Value 55,8 to 214 °C

Flammability
not determined

Upper and lower explosive limits
Remarks not determined

Flash point
Value < 21 °C

Auto-ignition temperature
Remarks not determined

Decomposition temperature
Remarks not determined

pH value
Remarks Not applicable

Viscosity
Remarks not determined

Solubility(ies)
Remarks not determined

Partition coefficient n-octanol/water (log value)
Remarks not determined

Vapour pressure
Remarks not determined

Density and/or relative density
Value appr. 0,95 kg/l
Temperature 20 °C

Relative vapour density
Remarks not determined

Particle characteristics
Remarks not determined

9.2. Other information

Odour threshold
Remarks not determined

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Evaporation rate

Remarks not determined

Solubility in water

Remarks not determined

Efflux time

Value 36 to 54 s
Temperature 20 °C
Method DIN 53211 4 mm

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

Non-volatile content

Value 29,5 %

Other information

This information is not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO_x), dense black smoke, No decomposition if used as prescribed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Acute dermal toxicity

ATE > 10.000 mg/kg
Method calculated value (Regulation (EC) No. 1272/2008)

Acute dermal toxicity (Components)

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

xylene

ATE 2000 mg/kg
Source alle Daten über 2000 mg/kg

Acute inhalational toxicity

ATE > 20 mg/l
Administration/Form Dust/Mist
Method calculated value (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Acute inhalative toxicity (Components)

xylene

ATE 5 mg/l
Duration of exposure 4 h
Administration/Form Dust/Mist
Source alle Werte über 5 mg/l

Skin corrosion/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)

2-methylpropan-1-ol

Species rabbit
Duration of exposure 8 d
Observation Period 24 h
evaluation Skin irritation
Method Value taken from the literature
Source 2 (reliable with restrictions)

toluene

Species rabbit
Duration of exposure 4 h
Observation Period 7 d
evaluation Irritating to skin.
Method EEC 84/449, B.4
Source 1 (reliable without restriction)

xylene

Species rabbit
Observation Period 72 h
evaluation Irritating to skin.
Source 2 (reliable with restrictions)

Serious eye damage/irritation

evaluation irritant
Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks The classification criteria are met.

Serious eye damage/irritation (Components)

2-methylpropan-1-ol

Species rabbit
Observation Period 14 d
evaluation irritant - risk of serious damage to eyes
Source 1 (reliable without restriction)

acetone

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Species rabbit
Observation Period 24 h
evaluation Irritating to eyes.
Source 1 (reliable without restriction)

ethyl acetate

Species rabbit
Observation Period 24 h
evaluation Irritating to eyes.
Source 2 (reliable with restrictions)

xylene

Species rabbit
evaluation Irritating to eyes.
Source 2 (reliable with restrictions)

Sensitization

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

evaluation Suspected of damaging the unborn child.
Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks The classification criteria are met.

Reproduction toxicity (Components)

toluene

evaluation Reproductive toxicity, Category 2

Carcinogenicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT)

Single exposure

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks The classification criteria are met.
evaluation May cause drowsiness or dizziness.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) (Components)

2-methylpropan-1-ol

Specific target organ toxicity - single exposure

Remarks Organs: Respiratory tract
May cause respiratory irritation.

2-methylpropan-1-ol

Specific target organ toxicity - single exposure

Remarks Organs: Nervous system
Possible narcotic effects (drowsiness, dizziness).

acetone

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Specific target organ toxicity - repeated exposure

Remarks
Organs: Nervous system
Possible narcotic effects (drowsiness, dizziness).

ethyl acetate

Specific target organ toxicity - single exposure

Remarks
Organs: Nervous system
Possible narcotic effects (drowsiness, dizziness).

isobutyl acetate

Specific target organ toxicity - repeated exposure

Remarks
Organs: Nervous system
Possible narcotic effects (drowsiness, dizziness).

n-butyl acetate

Specific target organ toxicity - repeated exposure

Remarks
Organs: Nervous system
Possible narcotic effects (drowsiness, dizziness).

toluene

Specific target organ toxicity - single exposure

Remarks
Organs: Liver
May cause damage to organs through prolonged or repeated exposure:

toluene

Specific target organ toxicity - repeated exposure

Remarks
Organs: Nervous system
Possible narcotic effects (drowsiness, dizziness).

xylene

Specific target organ toxicity - single exposure

Remarks
Route of exposure inhalative
Organs: Respiratory tract
May cause respiratory irritation.

Hydrocarbons, C9, aromatics

Specific target organ toxicity - single exposure

Remarks
Route of exposure inhalative
Possible narcotic effects (drowsiness, dizziness).

Hydrocarbons, C9, aromatics

Specific target organ toxicity - single exposure

Remarks
Possible narcotic effects (drowsiness, dizziness).

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

No toxicological data are available.

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

SECTION 12: Ecological information

12.1. Toxicity

General information

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)

Hydrocarbons, C9, aromatics

Species	Oncorhynchus mykiss (rainbow trout)		
LC50	9,2		mg/l
Duration of exposure	96	h	

Daphnia toxicity (Components)

Hydrocarbons, C9, aromatics

Species	Daphnia magna (Water flea)		
EC50	3,2		mg/l
Duration of exposure	48	h	

Hydrocarbons, C9, aromatics

Species	Daphnia magna (Water flea)		
NOEC	2,14		mg/l
Duration of exposure	21	d	

Algae toxicity (Components)

Hydrocarbons, C9, aromatics

Species	Pseudokirchneriella subcapitata (green algae)		
EC50	2,6	to	2,9 mg/l
Duration of exposure	72	h	

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

Hydrocarbons, C9, aromatics

evaluation	Readily biodegradable.
------------	------------------------

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient n-octanol/water (log value)

Remarks	not determined
---------	----------------

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

For this subsection there is no ecotoxicological data available on the product as such.

Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

For this subsection there is no ecotoxicological data available on the product as such.

General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

SECTION 14: Transport information




Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	II	II	II
Special provision	640C		
Remarks	The product is viscous; packing group III in containers with not more than 450 ltrs.	The product is viscous; packing group III in containers with not more than 450 ltrs.	Transport in accordance with 3.3.3.1 of the IATA regulations
Limited Quantity	5 l		
Transport category	2		
14.5. Environmental hazards	-		

Information for all modes of transport

14.6. Special precautions for user

See Sections 6 to 8

Other information

14.7. Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 2012/18/EU

Category P5c FLAMMABLE LIQUID 5.000.000 kg 50.000.000 kg

Restriction according to annex XVII to regulation (EU) No 1907/2006

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

The product is subject to restrictions according to Annex XVII Regulation (EU) No. 1907/2006: Entry No. 3.

15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin irritation, Category 2
STOT RE 2	Specific target organ toxicity - repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3
Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.	

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES001 - Industrial applications: industrial spraying (inside)

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Use of the substance/preparation

Surface treatment of wood and other materials

Use

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

Contributing exposure scenario controlling environmental exposure

Use

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix

Physical form liquid

Maximum amount used per time or activity

Emission days per site: <= 300

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure

Use

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
PROC7	Industrial spraying

Physical form liquid

Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

Other relevant operational conditions

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Read attached instructions before use.

Product substance and product safety related measures

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Multilayer gloves made from

Appropriate Material

Fluorinated rubber / butyl-rubber

Material thickness

$\geq 0,7$

Breakthrough time

≥ 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Exposure estimation and reference to its source

Workers (industrial)

PROC

Assessment method

PROC7

inhalation, long-term - local and systemic

Indoor use

Exposure assessment

60,5 mg/m³

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,126

Lead substance

isobutyl acetate

Workers (industrial)

PROC

Assessment method

PROC10

inhalation, long-term - local and systemic

Indoor use

Exposure assessment

242 mg/m³

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,504

Lead substance

isobutyl acetate

Workers (industrial)

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (industrial)

PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (industrial)

PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (industrial)

PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (industrial)

PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (industrial)

PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (industrial)

SU
PROC

PROC13
inhalation, long-term - local and systemic
Indoor use
242 mg/m³
ECETOC TRA
0,504
isobutyl acetate

PROC7
inhalation, long-term - local and systemic
Indoor use
60,5 mg/m³
ECETOC TRA
0,126
n-butyl acetate

PROC10
inhalation, long-term - systemic
Indoor use
242 mg/m³
ECETOC TRA
0,504
n-butyl acetate

PROC10
inhalation, long-term - systemic
Outdoor use
242 mg/m³
ECETOC TRA
0,504
n-butyl acetate

PROC13
inhalation, long-term - systemic
Indoor use
242 mg/m³
ECETOC TRA
0,504
n-butyl acetate

PROC13
inhalation, long-term - systemic
Outdoor use
242 mg/m³
ECETOC TRA
0,504
n-butyl acetate

SU3
PROC7

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Assessment method	inhalation, long-term - systemic
	Indoor use
Exposure assessment	200 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,05
Lead substance	acetone

Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	dermal, long-term - systemic
	Indoor use
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,01
Lead substance	acetone

Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	inhalation, long-term - systemic
	Indoor use
Exposure assessment	200 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5
Lead substance	acetone

Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	dermal, long-term - systemic
	Indoor use
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,15
Lead substance	acetone

Workers (industrial)

SU	SU3
PROC	PROC13
Assessment method	inhalation, long-term - systemic
	Indoor use
Exposure assessment	200 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5
Lead substance	acetone

Workers (industrial)

SU	SU3
PROC	PROC13
Assessment method	dermal, long-term - systemic
	Indoor use
Exposure assessment	61 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,074
Lead substance	acetone

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	dermal, long-term - systemic
Exposure assessment	63 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,034
Lead substance	ethyl acetate

Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	inhalation, long-term - local
Exposure assessment	734 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,075
Lead substance	ethyl acetate

Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	63 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,011
Lead substance	ethyl acetate

Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	inhalation, long-term - local
Exposure assessment	734 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,075
Lead substance	ethyl acetate

Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene

Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Workers (industrial)

SU	SU3
PROC	PROC13
Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene
SU	SU3
PROC	PROC7
Assessment method	Long-term
	inhalative
Exposure assessment	0 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0
Lead substance	2-methylpropan-1-ol
SU	SU3
PROC	PROC10
Assessment method	Long-term
	inhalative
Exposure assessment	15,44 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,0498
Lead substance	2-methylpropan-1-ol
SU	SU3
PROC	PROC13
Assessment method	Long-term
	inhalative
Exposure assessment	15,44 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,0498
Lead substance	2-methylpropan-1-ol

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES003 - Professional uses: Non industrial spraying (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

ERC8c
PROC11

Wide dispersive indoor use resulting in inclusion into or onto a matrix
Non industrial spraying

Contributing exposure scenario controlling environmental exposure

Use

ERC8a Wide dispersive indoor use of processing aids in open systems
ERC8c Wide dispersive indoor use resulting in inclusion into or onto a matrix

Physical form liquid

Maximum amount used per time or activity

Emission days per site: <= 250

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Volatile organic substances will volatilise into the atmospheric air inside.
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure (professional)

Short title of the exposure scenario

Substance number:CES006

Use

SU22 Professional uses: Public domain (administration, education, entertainment,
services, craftsmen)
PROC11 Non industrial spraying

Physical form liquid

Maximum amount used per time or activity

Duration of exposure <= 8 h/d
Frequency of exposure <= 220 d/a

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Volatile organic substances will volatilise into the atmospheric air inside.

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness \geq 0,7

Breakthrough time \geq 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Exposure estimation and reference to its source

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local and systemic
	Indoor use
Exposure assessment	242 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	isobutyl acetate

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local and systemic
	Outdoor use
Exposure assessment	242 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	isobutyl acetate

Workers (professional)

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

SU
PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC11
Long-term
inhalative
242 mg/m³
ECETOC TRA
0,504
n-butyl acetate

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC10
inhalation, long-term - systemic
200 mg/m³
ECETOC TRA
0,6
acetone

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC10
dermal, long-term - systemic
62 mg/kg/d
ECETOC TRA
0,15
acetone

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC11
inhalation, long-term - systemic
200 mg/m³
ECETOC TRA
0,4
acetone

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC11
dermal, long-term - systemic
62 mg/kg/d
ECETOC TRA
0,01
acetone

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC13
inhalation, long-term - systemic
200 mg/m³
ECETOC TRA
0,5
acetone

Workers (professional)

SU

SU22

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

PROC13
dermal, long-term - systemic
62 mg/kg/d
ECETOC TRA
0,07
acetone

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC10
dermal, long-term - systemic
63 mg/kg/d
ECETOC TRA
0,022
ethyl acetate

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC10
inhalation, long-term - local
734 mg/m³
ECETOC TRA
0,018
ethyl acetate

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC11
dermal, long-term - systemic
63 mg/kg/d
ECETOC TRA
0,034
ethyl acetate

Workers (professional)

SU
PROC
Assessment method
Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC11
inhalation, long-term - local
734 mg/m³
ECETOC TRA
0,018
ethyl acetate

Workers (professional)

SU
PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU22
PROC10
inhalative
Indoor use
0,05 mg/m³
ECETOC TRA
0,172
xylene

Workers (professional)

SU
PROC

SU22
PROC11

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene

Workers (professional)

SU	SU22
PROC	PROC13
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene
SU	SU22
PROC	PROC10
Assessment method	Long-term
	inhalative
Exposure assessment	185,25 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5976
Lead substance	2-methylpropan-1-ol
SU	SU22
PROC	PROC11
Assessment method	Long-term
	inhalative
Exposure assessment	256,1 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,8261
Lead substance	2-methylpropan-1-ol
SU	SU22
PROC	PROC13
Assessment method	Long-term
	inhalative
Exposure assessment	185,25 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5976
Lead substance	2-methylpropan-1-ol

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES004 - Professional uses: roller application or brushing, dipping and pouring and other processing without aerosol formation (inside)

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Use of the substance/preparation

Surface treatment of wood and other materials

Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring
PROCh01	Other processing without aerosol formation

Contributing exposure scenario controlling environmental exposure

Use

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

Physical form

liquid

Maximum amount used per time or activity

Emission days per site: <= 250

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Volatile organic substances will volatilise into the atmospheric air inside.
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure (professional)

Short title of the exposure scenario

Substance number:CES008

Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

PROCh01 Other processing without aerosol formation

Physical form liquid

Maximum amount used per time or activity

Duration of exposure	<=	8	h/d
Frequency of exposure	<=	220	d/a

Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Volatile organic substances will volatilise into the atmospheric air inside.

Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness >= 0,7

Breakthrough time >= 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Exposure estimation and reference to its source

Workers (professional)

SU

SU22

PROC

PROC11

Assessment method

inhalation, long-term - local and systemic

Indoor use

Exposure assessment

242 mg/m³

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,504

Lead substance

isobutyl acetate

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local and systemic
	Outdoor use
Exposure assessment	242 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	isobutyl acetate

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	Long-term
	inhalative
Exposure assessment	242 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	n-butyl acetate

Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - systemic
Exposure assessment	200 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,6
Lead substance	acetone

Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,15
Lead substance	acetone

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - systemic
Exposure assessment	200 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,4
Lead substance	acetone

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,01
Lead substance	acetone

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Workers (professional)

SU	SU22
PROC	PROC13
Assessment method	inhalation, long-term - systemic
Exposure assessment	200 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,5
Lead substance	acetone

Workers (professional)

SU	SU22
PROC	PROC13
Assessment method	dermal, long-term - systemic
Exposure assessment	62 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,07
Lead substance	acetone

Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	dermal, long-term - systemic
Exposure assessment	63 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,022
Lead substance	ethyl acetate

Workers (professional)

SU	SU22
PROC	PROC10
Assessment method	inhalation, long-term - local
Exposure assessment	734 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,018
Lead substance	ethyl acetate

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	dermal, long-term - systemic
Exposure assessment	63 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,034
Lead substance	ethyl acetate

Workers (professional)

SU	SU22
PROC	PROC11
Assessment method	inhalation, long-term - local
Exposure assessment	734 mg/m ³
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,018
Lead substance	ethyl acetate

Workers (professional)

SU	SU22
----	------

Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (professional)

SU
PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

Workers (professional)

SU
PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU
PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU
PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

SU
PROC
Assessment method

Exposure assessment
Exposure assessment (method)
Risk characterisation ratio (RCR)
Lead substance

PROC10
inhalative
Indoor use
0,05 mg/m³
ECETOC TRA
0,172
xylene

SU22
PROC11
inhalative
Indoor use
0,1 mg/m³
ECETOC TRA
0,34
xylene

SU22
PROC13
inhalative
Indoor use
0,05 mg/m³
ECETOC TRA
0,172
xylene

SU22
PROC10
Long-term
inhalative
185,25 mg/m³
ECETOC TRA
0,5976
2-methylpropan-1-ol

SU22
PROC11
Long-term
inhalative
256,1 mg/m³
ECETOC TRA
0,8261
2-methylpropan-1-ol

SU22
PROC13
Long-term
inhalative
185,25 mg/m³
ECETOC TRA
0,5976
2-methylpropan-1-ol

Information on estimated exposure and downstream-user guidance



Trade name: Hesse PU Metallic Effect lacquer coarse, silk mat PEX DB 46004-FT

Version: 24 / WORLD

Revision: 25.02.2025

Replaces Version: 23 / WORLD

Print date: 07.11.25

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.