

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, reaction mass of:  
5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-  
-isothiazol-3-one [EC no. 220-239-6] (3:1), May produce an allergic reaction.

#### Supplemental information

EUH210 Safety data sheet available on request.

### 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### 1,2-benzisothiazol-3(2H)-one

CAS No. 2634-33-5  
EINECS no. 220-120-9  
Registration no. 01-2120761540-60

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Concentration < 0,036 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Acute Tox. 2	H330

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1	H317	>= 0,036 %
--------------	------	------------

### 2-methyl-2H-isothiazol-3-one

CAS No. 2682-20-4

EINECS no. 220-239-6

Registration no. 01-2120764690-50

Concentration < 0,0015 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3	H301
Acute Tox. 2	H330
Skin Corr. 1B	H314
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Skin Sens. 1A	H317
Acute Tox. 3	H311
Eye Dam. 1	H318

Route of exposure: Inhalation exposure

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400	M = 10
Skin Sens. 1A	H317	>= 0,0015 %

### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

CAS No. 55965-84-9

Concentration < 0,001 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 2	H330
Acute Tox. 2	H310
Acute Tox. 3	H301
Skin Corr. 1B	H314
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Eye Dam. 1	H318

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C	H314	>= 0,6 %
Skin Irrit. 2	H315	>= 0,06 %
Eye Irrit. 2	H319	>= 0,06 %
Skin Sens. 1	H317	>= 0,0015 %
Eye Dam. 1	H318	>= 0,6 %
Aquatic Chronic 1	H410	M = 100
Aquatic Acute 1	H400	M = 100

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

#### **General information**

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

#### **After inhalation**

When spray fog inhaled, seek medical aid.

#### **After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### **After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### **After ingestion**

Do not induce vomiting. Take medical treatment.

### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

### **4.3. Indication of any immediate medical attention and special treatment needed**

#### **Hints for the physician / treatment**

Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

#### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### **Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

### **5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

## 6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

## 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

## 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

### Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

### Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

## 7.2. Conditions for safe storage, including any incompatibilities

### Storage stability

Protect from frost.

### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Storage classes

Storage class according to TRGS 510      10      Flammable liquids

### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

# SECTION 8: Exposure controls/personal protection \*\*\*

## 8.1. Control parameters

### Other information

-

### Derived No/Minimal Effect Levels (DNEL/DMEL) \*\*\*

#### 1,2-benzisothiazol-3(2H)-one

Type of value	Derived No Effect Level (DNEL)
Reference group	Worker
Duration of exposure	Long term

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	6,81	mg/m³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,966	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,2	mg/m³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,345	mg/kg

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	0,09	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m³

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Concentration	0,04	mg/m³
---------------	------	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Short-term
----------------------	------------

Route of exposure	Oral exposure
-------------------	---------------

Mode of action	Systemic effects
----------------	------------------

Concentration	0,11	mg/kg/d
---------------	------	---------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Workers (industrial)
-----------------	----------------------

Duration of exposure	Short-term
----------------------	------------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	0,04	mg/m³
---------------	------	-------

**2-methyl-2H-isothiazol-3-one**

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Worker
-----------------	--------

Duration of exposure	Long term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	0,021	mg/m³
---------------	-------	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Worker
-----------------	--------

Duration of exposure	Short term
----------------------	------------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	0,043	mg/m³
---------------	-------	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long term
----------------------	-----------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	0,021	mg/m³
---------------	-------	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Short term
----------------------	------------

Route of exposure	inhalative
-------------------	------------

Mode of action	Local effects
----------------	---------------

Concentration	0,043	mg/m³
---------------	-------	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Reference group	Consumer
-----------------	----------

Duration of exposure	Long term
----------------------	-----------

Route of exposure	oral
-------------------	------

Mode of action	Systemic effects
----------------	------------------

Concentration	0,027	mg/m³
---------------	-------	-------

Type of value	Derived No Effect Level (DNEL)
---------------	--------------------------------

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	0,053	mg/m³

**Predicted No Effect Concentration (PNEC) \*\*\***

**1,2-benzisothiazol-3(2H)-one**

Type of value	PNEC	
Type	Freshwater	
Concentration	4,03	µg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,403	µg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	1,03	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,0499	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,00499	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	3	mg/kg

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Type of value	PNEC	
Type	Marine	
Concentration	3,39	µg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	0,23	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Soil	

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Concentration	0,01	mg/kg
---------------	------	-------

Type of value	PNEC	
---------------	------	--

Type	Freshwater	
------	------------	--

Concentration	3,39	µg/l
---------------	------	------

#### **2-methyl-2H-isothiazol-3-one**

Type of value	PNEC	
---------------	------	--

Type	Freshwater	
------	------------	--

Concentration	3,39	µg/l
---------------	------	------

Type of value	PNEC	
---------------	------	--

Type	Saltwater	
------	-----------	--

Concentration	3,39	µg/l
---------------	------	------

Type of value	PNEC	
---------------	------	--

Type	Sewage treatment plant (STP)	
------	------------------------------	--

Concentration	023	mg/l
---------------	-----	------

Type of value	PNEC	
---------------	------	--

Type	Soil	
------	------	--

Concentration	0,047	mg/kg
---------------	-------	-------

## **8.2. Exposure controls**

### **Exposure controls**

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### **Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### **Hand protection**

Glove material

Appropriate Material	butyl-rubber
----------------------	--------------

Material thickness	>= 0,5	mm
--------------------	--------	----

Breakthrough time	>= 120	min
-------------------	--------	-----

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### **Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.



Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	liquid
<b>Colour</b>	coloured
<b>Odour</b>	characteristic
<b>Melting point</b>	
Remarks	not determined
<b>Freezing point</b>	
Remarks	not determined
<b>Boiling point or initial boiling point and boiling range</b>	
Value	100 to 170 °C
<b>Flammability</b>	
not determined	
<b>Upper and lower explosive limits</b>	
Remarks	not determined
<b>Flash point</b>	
Value	> 60 °C
<b>Auto-ignition temperature</b>	
Remarks	not determined
<b>Decomposition temperature</b>	
Remarks	not determined
<b>pH value</b>	
Value	8
Concentration/H <sub>2</sub> O	100
Remarks	Not applicable
<b>Viscosity</b>	
Remarks	not determined
<b>Solubility(ies)</b>	
Remarks	not determined
<b>Partition coefficient n-octanol/water (log value)</b>	
Remarks	not determined
<b>Vapour pressure</b>	
Remarks	not determined
<b>Density and/or relative density</b>	
Value	appr. 1,046 kg/l
Temperature	20 °C
<b>Relative vapour density</b>	
Remarks	not determined
<b>Particle characteristics</b>	
Remarks	not determined

### 9.2. Other information

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

#### Odour threshold

Remarks not determined

#### Solubility in water

Remarks not determined

#### Efflux time

Value 26 to 40 s  
Temperature 20 °C  
Method DIN 53211 - 6 mm

#### Explosive properties

evaluation not determined

#### Oxidising properties

Remarks not determined

#### Non-volatile content

Value 39,7 %  
Method calculated value

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

#### 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

#### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute oral toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

##### Acute oral toxicity (Components)

###### 2-methyl-2H-isothiazol-3-one

Species rat  
LD50 120 mg/kg  
Method EPA  
Source 1 (reliable without restriction)

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

#### 1,2-benzisothiazol-3(2H)-one

Species	rat	
LD50	450	mg/kg
Source	Annex VI Hazardous Substance	

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

ATE	53	mg/kg
-----	----	-------

#### Acute dermal toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Acute dermal toxicity (Components)

##### 2-methyl-2H-isothiazol-3-one

Species	rat	
LD50	242	mg/kg
Source	1 (reliable without restriction)	

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

ATE	50	mg/kg
-----	----	-------

Method	conversion
--------	------------

#### Acute inhalational toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Acute inhalative toxicity (Components)

##### 2-methyl-2H-isothiazol-3-one

Species	rat	
LC50	0,1	mg/l
Duration of exposure	4	h
Administration/Form	Dust/Mist	
Source	1 (reliable without restriction)	

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

ATE	0,05	mg/l
-----	------	------

Duration of exposure	4	h
----------------------	---	---

Administration/Form	Dust/Mist
---------------------	-----------

Method	conversion value
--------	------------------

Remarks	Mist
---------	------

#### Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation (Components)

##### 2-methyl-2H-isothiazol-3-one

evaluation	Causes burns.
------------	---------------

##### 1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to skin.
------------	---------------------

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Species	rabbit
---------	--------

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

evaluation

Severe skin irritation

### Serious eye damage/irritation

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

### Serious eye damage/irritation (Components)

#### 2-methyl-2H-isothiazol-3-one

evaluation

Causes severe caustic burns to skin and eyes.

#### 1,2-benzisothiazol-3(2H)-one

evaluation

Irritating to eyes.

### Sensitization

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

### Sensitization (Components)

#### 2-methyl-2H-isothiazol-3-one

evaluation

May cause sensitization by skin contact.

#### 1,2-benzisothiazol-3(2H)-one

Reference substance

1,2-benzisothiazol-3(2H)-one

evaluation

May cause sensitization by skin contact.

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species

guinea pig

evaluation

Causes sensitisation on guinea-pigs.

### Mutagenicity

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

### Reproductive toxicity

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

### Carcinogenicity

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity (STOT)

#### Single exposure

Method

Calculation method (Regulation (EC) No. 1272/2008)

Remarks

Based on available data, the classification criteria are not met.

#### Repeated exposure

Remarks

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Other information

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

Species	Oncorhynchus mykiss (rainbow trout)		
LC50	2,18		mg/l
Duration of exposure	96	h	

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Oncorhynchus mykiss (rainbow trout)		
LC50	0,19		mg/l
Duration of exposure	96	h	

#### Daphnia toxicity (Components)

##### 2-methyl-2H-isothiazol-3-one

Species	Daphnia magna (Water flea)		
NOEC	0,044		mg/l
Duration of exposure	21	d	

##### 1,2-benzisothiazol-3(2H)-one

Species	Daphnia magna (Water flea)		
EC50	2,94		mg/l
Duration of exposure	48	h	

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Daphnia magna (Water flea)		
EC50	0,16		mg/l
Duration of exposure	48	h	

#### Algae toxicity (Components)

##### 2-methyl-2H-isothiazol-3-one

EC50	0,157		mg/l
Duration of exposure	96	h	

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Scenedesmus capricornutum (fresh water algae)		
EC50	0,018		mg/l
Duration of exposure	72	h	

#### Bacteria toxicity (Components)

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	activated sludge		
EC50	4,5		mg/l

### 12.2. Persistence and degradability

#### General information

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

For this subsection there is no ecotoxicological data available on the product as such.

#### **Biodegradability (Components)**

##### **1,2-benzisothiazol-3(2H)-one**

evaluation Not readily biodegradable.

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

evaluation Not readily biodegradable.

### **12.3. Bioaccumulative potential**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Partition coefficient n-octanol/water (log value)**

Remarks not determined

#### **Octanol/water partition coefficient (log Pow) (Components)**

##### **2-methyl-2H-isothiazol-3-one**

log Pow	-0,486	
Temperature	20	°C

### **12.4. Mobility in soil**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Mobility in soil**

no data available

### **12.5. Results of PBT and vPvB assessment**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Results of PBT and vPvB assessment**

The product contains no PBT substances

The product contains no vPvB substances.

### **12.6 Endocrine disrupting properties**

#### **Endocrine disrupting properties with respect to the environment**

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

### **12.7. Other adverse effects**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Disposal recommendations for the product**

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### **Disposal recommendations for packaging**

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Completely emptied packagings can be given for recycling.

## SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
<b>14.1. UN number</b>	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

### Information for all modes of transport

#### 14.6. Special precautions for user

See Sections 6 to 8

### Other information

#### 14.7. Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information \*\*\*

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU) 0,8 % 9 g/l

### Ingredients with restrictions according to Annex XVII Regulation (EU) No. 1907/2006 \*\*\*

#### 2-methyl-2H-isothiazol-3-one

Entry No. 75 (\*)

(\*) Conditions of restriction see Annex XVII Regulation (EU) No. 1907/2006 (REACH)

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4

Trade name: Hesse COOLPRO-COLOR Pearl structure medium, matt PEX HDB 54892-F

Version: 3 / WORLD

Revision: 22.10.2025

Replaces Version: 2 / WORLD

Print date: 07.11.25

Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A

Changes since the last version are highlighted in the margin (\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.