

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse Wiping stain PEX TD 4220-FT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

Identified Uses

| | |
|--------|--|
| | REACHSET 1000 |
| SU3 | Industrial uses: Uses of substances as such or in preparations at industrial sites |
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC5 | Industrial use resulting in inclusion into or onto a matrix |
| PROC7 | Industrial spraying |
| | REACHSET 2001 |
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |
| PROC11 | Non industrial spraying |
| | REACHSET 2003 |
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |
| PROC10 | Roller application or brushing |

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG
Warendorfer Strasse 21
59075 Hamm (Germany)
Telephone no. +49 (0) 2381 963-00
Fax no. +49 (0) 2381 963-849
E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)
Flam. Liq. 2 H225

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | |
|-------------------|------|
| Skin Irrit. 2 | H315 |
| Eye Dam. 1 | H318 |
| STOT SE 3 | H335 |
| STOT SE 3 | H336 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 2 | H411 |

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008
For explanation of abbreviations see section 16.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



Signal word

Danger

Hazard statements

| | |
|------|--|
| H225 | Highly flammable liquid and vapour. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H304 | May be fatal if swallowed and enters airways. |
| H411 | Toxic to aquatic life with long lasting effects. |

Precautionary statements

| | |
|----------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313 | IF exposed or concerned: Get medical advice/ attention. |
| P331 | Do NOT induce vomiting. |

Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

| | |
|----------|---|
| contains | 2-methylpropan-1-ol; Hydrocarbons, C9, aromatics; propan-2-ol; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics |
|----------|---|

2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Hazardous ingredients

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

| | | | | |
|--|-------------------|------|---|----------------|
| CAS No. | 64742-49-0 | | | |
| EINECS no. | 920-750-0 | | | |
| Registration no. | 01-2119473851-33 | | | |
| Concentration | >= 30 | < 50 | % | |
| Classification (Regulation (EC) No. 1272/2008) | | | | |
| | Flam. Liq. 2 | H225 | | |
| | Asp. Tox. 1 | H304 | | |
| | Aquatic Chronic 2 | H411 | | |
| | STOT SE 3 | H336 | | Nervous system |

Hydrocarbons, C9, aromatics

| | | | | |
|--|-------------------|--------|---|-------------------|
| CAS No. | 128601-23-0 | | | |
| EINECS no. | 918-668-5 | | | |
| Registration no. | 01-2119455851-35 | | | |
| Concentration | >= 20 | < 25 | % | |
| Classification (Regulation (EC) No. 1272/2008) | | | | |
| | Flam. Liq. 3 | H226 | | |
| | Asp. Tox. 1 | H304 | | |
| | Aquatic Chronic 2 | H411 | | |
| | STOT SE 3 | H335 | | Respiratory tract |
| | STOT SE 3 | H336 | | Nervous system |
| | | EUH066 | | |

2-methylpropan-1-ol

| | | | | |
|--|------------------|------|---|-------------------|
| CAS No. | 78-83-1 | | | |
| EINECS no. | 201-148-0 | | | |
| Registration no. | 01-2119484609-23 | | | |
| Concentration | >= 10 | < 20 | % | |
| Classification (Regulation (EC) No. 1272/2008) | | | | |
| | Flam. Liq. 3 | H226 | | |
| | STOT SE 3 | H335 | | Respiratory tract |
| | Skin Irrit. 2 | H315 | | |
| | Eye Dam. 1 | H318 | | |
| | STOT SE 3 | H336 | | Nervous system |

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | | | | |
|--|------------------|--------|---|----------------|
| CAS No. | 64742-48-9 | | | |
| EINECS no. | 919-857-5 | | | |
| Registration no. | 01-2119463258-33 | | | |
| Concentration | >= 10 | < 20 | % | |
| Classification (Regulation (EC) No. 1272/2008) | | | | |
| | Flam. Liq. 3 | H226 | | |
| | Asp. Tox. 1 | H304 | | |
| | STOT SE 3 | H336 | | Nervous system |
| | | EUH066 | | |

propan-2-ol

| | |
|------------|-----------|
| CAS No. | 67-63-0 |
| EINECS no. | 200-661-7 |

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | | | |
|--|------------------|--------|---|
| Registration no. | 01-2119457558-25 | | |
| Concentration | \geq 1 | $<$ 10 | % |
| Classification (Regulation (EC) No. 1272/2008) | | | |
| Flam. Liq. 2 | H225 | | |
| Eye Irrit. 2 | H319 | | |
| STOT SE 3 | H336 | | |
| | Nervous system | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical attention. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

5.3. Advice for firefighters

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage classes

Storage class according to TRGS 510 3 Flammable liquid

Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Other information

-

Derived No/Minimal Effect Levels (DNEL/DMEL)

propan-2-ol

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | Dermal exposure | |
| Mode of action | Chronic effects | |
| Concentration | 888 | mg/kg/d |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Chronic effects | |
| Concentration | 500 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Chronic effects | |
| Concentration | 89 | mg/m ³ |

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Oral exposure | |
| Mode of action | Chronic effects | |
| Concentration | 26 | mg/kg/d |

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Dermal exposure | |
| Mode of action | Systemic effects | |
| Concentration | 319 | mg/kg/d |

2-methylpropan-1-ol

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 310 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 55 | mg/m ³ |

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Oral exposure | |
| Mode of action | Local effects | |
| Concentration | 25 | mg/kg/d |

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Oral exposure | |
| Concentration | 125 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | Dermal exposure | |
| Concentration | 208 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Dermal exposure | |
| Concentration | 125 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Concentration | 871 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Concentration | 185 | mg/kg |

Hydrocarbons, C9, aromatics

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Oral exposure | |
| Mode of action | Systemic effects | |
| Concentration | 11 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | Dermal exposure | |
| Mode of action | Systemic effects | |
| Concentration | 25 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Dermal exposure | |
| Mode of action | Systemic effects | |
| Concentration | 11 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 150 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 32 | mg/kg |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 11 | mg/kg |

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Oral exposure | |
| Mode of action | Systemic effects | |
| Concentration | 699 | mg/kg/d |

| | | |
|----------------------|--------------------------------|--|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | | |
|-------------------|------------------|---------|
| Route of exposure | Dermal exposure | |
| Mode of action | Systemic effects | |
| Concentration | 773 | mg/kg/d |

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | Dermal exposure | |
| Mode of action | Systemic effects | |
| Concentration | 699 | mg/kg/d |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (professional) | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 2035 | mg/m³ |

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 608 | mg/kg/d |

Predicted No Effect Concentration (PNEC)

propan-2-ol

| | | |
|---------------|------------|------|
| Type of value | PNEC | |
| Type | Freshwater | |
| Concentration | 140,9 | mg/l |

| | | |
|---------------|-----------|------|
| Type of value | PNEC | |
| Type | Saltwater | |
| Concentration | 140,9 | mg/l |

| | | |
|---------------|------------------|------|
| Type of value | PNEC | |
| Conditions | sporadic release | |
| Concentration | 140,9 | mg/l |

| | | |
|---------------|----------------------|-------|
| Type of value | PNEC | |
| Type | Fresh water sediment | |
| Concentration | 552 | mg/kg |

| | | |
|---------------|--------------------|-------|
| Type of value | PNEC | |
| Type | saltwater sediment | |
| Concentration | 552 | mg/kg |

| | | |
|---------------|------|-------|
| Type of value | PNEC | |
| Type | Soil | |
| Concentration | 28 | mg/kg |

| | | |
|---------------|------|--|
| Type of value | PNEC | |
|---------------|------|--|

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | | |
|----------------------------|------------------------------|-------|
| Type | Sewage treatment plant (STP) | |
| Concentration | 2251 | mg/l |
| 2-methylpropan-1-ol | | |
| Type of value | PNEC | |
| Type | Freshwater | |
| Concentration | 0,4 | mg/l |
| Type of value | PNEC | |
| Type | Saltwater | |
| Concentration | 0,04 | mg/l |
| Type of value | PNEC | |
| Conditions | sporadic release | |
| Concentration | 11 | mg/l |
| Type of value | PNEC | |
| Type | Fresh water sediment | |
| Concentration | 1,52 | mg/kg |
| Type of value | PNEC | |
| Type | saltwater sediment | |
| Concentration | 0,152 | mg/kg |
| Type of value | PNEC | |
| Type | Soil | |
| Concentration | 0,0699 | mg/kg |
| Type of value | PNEC | |
| Type | Sewage treatment plant (STP) | |
| Concentration | 10 | mg/l |

8.2. Exposure controls

Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness \geq 0,7 mm

Breakthrough time \geq 30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid

Colour coloured

Odour solvent-like

Melting point

Remarks not determined

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value 82 to 200 °C

Flammability

not determined

Upper and lower explosive limits

Remarks not determined

Flash point

Value < 21 °C

Auto-ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

pH value

Remarks Not applicable

Viscosity

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

Value appr. 0,818 kg/l

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Temperature 20 °C

Relative vapour density

Remarks not determined

Particle characteristics

Remarks not determined

9.2. Other information

Odour threshold

Remarks not determined

Evaporation rate

Remarks not determined

Solubility in water

Remarks not determined

Efflux time

Value 20 to 48 s
Temperature 20 °C
Method DIN EN ISO 2431 - 3 mm

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

Non-volatile content

Value 10,5 %

Other information

This information is not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO_x), dense black smoke, No decomposition if used as prescribed.

SECTION 11: Toxicological information

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Acute dermal toxicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Acute inhalational toxicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Skin corrosion/irritation

| | |
|------------|--|
| evaluation | irritant |
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | The classification criteria are met. |

Skin corrosion/irritation (Components)

2-methylpropan-1-ol

| | |
|----------------------|---------------------------------|
| Species | rabbit |
| Duration of exposure | 8 d |
| Observation Period | 24 h |
| evaluation | Skin irritation |
| Method | Value taken from the literature |
| Source | 2 (reliable with restrictions) |

Serious eye damage/irritation

| | |
|------------|--|
| evaluation | corrosive |
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | The classification criteria are met. |

Serious eye damage/irritation (Components)

propan-2-ol

| | |
|--------------------|----------------------------------|
| Species | rabbit |
| Observation Period | 14 d |
| evaluation | Irritating to eyes. |
| Source | 1 (reliable without restriction) |

2-methylpropan-1-ol

| | |
|--------------------|---|
| Species | rabbit |
| Observation Period | 14 d |
| evaluation | irritant - risk of serious damage to eyes |
| Source | 1 (reliable without restriction) |

Sensitization

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Mutagenicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Reproductive toxicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Carcinogenicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Specific Target Organ Toxicity (STOT)

Single exposure

| | |
|------------|--|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | The classification criteria are met. |
| evaluation | May cause respiratory irritation. |
| evaluation | May cause drowsiness or dizziness. |

Repeated exposure

| | |
|---------|---|
| Remarks | Based on available data, the classification criteria are not met. |
|---------|---|

Specific Target Organ Toxicity (STOT) (Components)

propan-2-ol

Specific target organ toxicity - single exposure

| | |
|---------|--|
| | Organs: Nervous system |
| Remarks | Possible narcotic effects (drowsiness, dizziness). |

2-methylpropan-1-ol

Specific target organ toxicity - single exposure

| | |
|---------|-----------------------------------|
| | Organs: Respiratory tract |
| Remarks | May cause respiratory irritation. |

2-methylpropan-1-ol

Specific target organ toxicity - single exposure

| | |
|---------|--|
| | Organs: Nervous system |
| Remarks | Possible narcotic effects (drowsiness, dizziness). |

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Specific target organ toxicity - repeated exposure

| | |
|---------|--|
| | Organs: Nervous system |
| Remarks | Possible narcotic effects (drowsiness, dizziness). |

Hydrocarbons, C9, aromatics

Specific target organ toxicity - single exposure

| | |
|---------|--|
| | Route of exposure inhalative |
| Remarks | Possible narcotic effects (drowsiness, dizziness). |

Hydrocarbons, C9, aromatics

Specific target organ toxicity - single exposure

| | |
|---------|--|
| Remarks | Possible narcotic effects (drowsiness, dizziness). |
|---------|--|

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Specific target organ toxicity - single exposure

| | |
|------------|--|
| evaluation | May cause drowsiness or dizziness. |
| | Organs: Nervous system |
| Remarks | Possible narcotic effects (drowsiness, dizziness). |

Aspiration hazard

The classification criteria are met.
Harmful: may cause lung damage if swallowed.

11.2. Information on other hazards

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

No toxicological data are available.

SECTION 12: Ecological information

12.1. Toxicity

General information

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)

Hydrocarbons, C9, aromatics

| | | | |
|----------------------|-------------------------------------|---|------|
| Species | Oncorhynchus mykiss (rainbow trout) | | |
| LC50 | 9,2 | | mg/l |
| Duration of exposure | 96 | h | |

Daphnia toxicity (Components)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | | | |
|----------------------|----------------------------|----|------|
| Species | Daphnia magna (Water flea) | | |
| EC50 | 22 | 46 | mg/l |
| Duration of exposure | 48 | h | |
| Method | OECD 202, part 1, static | | |

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| NOELR | 0,23 | | mg/l |
| Duration of exposure | 21 | d | |
| Method | QSAR modelled data | | |

Hydrocarbons, C9, aromatics

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| EC50 | 3,2 | | mg/l |
| Duration of exposure | 48 | h | |

Hydrocarbons, C9, aromatics

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| NOEC | 2,14 | | mg/l |
| Duration of exposure | 21 | d | |

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| EC50 | 3 | | mg/l |
| Duration of exposure | 48 | h | |

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| NOEC | 0,17 | | mg/l |
| Duration of exposure | 21 | d | |

Algae toxicity (Components)

Hydrocarbons, C9, aromatics

| | | | |
|----------------------|---|----|----------|
| Species | Pseudokirchneriella subcapitata (green algae) | | |
| EC50 | 2,6 | to | 2,9 mg/l |
| Duration of exposure | 72 | h | |

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

| | | | |
|----------------------|---|---|------|
| Species | Pseudokirchneriella subcapitata (green algae) | | |
| EC50 | 10 | | mg/l |
| Duration of exposure | 72 | h | |
| Method | OECD 201 | | |

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | | |
|------------------|----------------------------|---|
| Value | 53,4 | % |
| Duration of test | 28 | d |
| evaluation | Not readily biodegradable. | |

Hydrocarbons, C9, aromatics

evaluation Readily biodegradable.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

evaluation Readily biodegradable.

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient n-octanol/water (log value)

Remarks not determined

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

Results of PBT and vPvB assessment

The product contains no PBT substances
The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

For this subsection there is no ecotoxicological data available on the product as such.

General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Replaces Version: 13 / WORLD

Revision: 03.08.2024

Print date: 07.11.25

SECTION 13: Disposal considerations

13.1. Waste treatment methods







Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

SECTION 14: Transport information ***

| | Land transport ADR/RID | Marine transport IMDG/GGVSee *** | Air transport ICAO/IATA |
|-------------------------------------|---|--|---|
| Tunnel restriction code | D/E | | |
| 14.1. UN number | 1263 | 1263 | 1263 |
| 14.2. UN proper shipping name | PAINT | PAINT | PAINT |
| 14.3. Transport hazard class(es) | 3 | 3 | 3 |
| Label |  |  |  |
| 14.4. Packing group | II | II | II |
| Special provision | 640D | | |
| Limited Quantity | 5 I | | |
| Transport category | 2 | | |
| 14.5. Environmental hazards |  ENVIRONMENTALLY HAZARDOUS | Marine Pollutant  ENVIRONMENTALLY HAZARDOUS |  ENVIRONMENTALLY HAZARDOUS |

Information for all modes of transport

14.6. Special precautions for user

See Sections 6 to 8

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Other information

14.7. Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Major-accident categories acc. 2012/18/EU ***

| | | | | | | |
|----------|-----|--------------------------------------|-----------|----|------------|----|
| Category | P5c | FLAMMABLE LIQUID | 5.000.000 | kg | 50.000.000 | kg |
| Category | E2 | Hazardous to the Aquatic Environment | 200.000 | kg | 500.000 | kg |

Restriction according to annex XVII to regulation (EU) No 1907/2006

The product is subject to restrictions according to Annex XVII Regulation (EU) No. 1907/2006: Entry No. 3.

Other information

All components are contained in the TSCA inventory or exempted.

All components are contained in the IECSC inventory.

15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

SECTION 16: Other information

Hazard statements listed in Chapter 3

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H411 | Toxic to aquatic life with long lasting effects. |

CLP categories listed in Chapter 3

| | |
|---|--|
| Aquatic Chronic 2 | Hazardous to the aquatic environment, chronic, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Eye Dam. 1 | Serious eye damage, Category 1 |
| Eye Irrit. 2 | Eye irritation, Category 2 |
| Flam. Liq. 2 | Flammable liquid, Category 2 |
| Flam. Liq. 3 | Flammable liquid, Category 3 |
| Skin Irrit. 2 | Skin irritation, Category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, Category 3 |
| Changes since the last version are highlighted in the margin (***). This version replaces all previous versions. | |
| This safety datasheet only contains information relating to safety and does not replace any product information or product specification. | |

Print date: 07.11.25

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

| | |
|--------|--|
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |
| PROC11 | Non industrial spraying |

Disposal recommendations for packaging

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure (professional)

Short title of the exposure scenario

Substance number:CES006

Use

SU22 Professional uses: Public domain (administration, education, entertainment,
services, craftsmen)

PROC11 Non industrial spraying

Physical form liquid

Maximum amount used per time or activity

Duration of exposure <= 8 h/d

Frequency of exposure <= 220 d/a

Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Volatile organic substances will volatilise into the atmospheric air inside.

Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness >= 0,7

Breakthrough time >= 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Exposure estimation and reference to its source

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | |
|-----------------------------------|--------------------------|
| SU | SU22 |
| PROC | PROC10 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 185,25 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,5976 |
| Lead substance | 2-methylpropan-1-ol |
| SU | SU22 |
| PROC | PROC11 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 256,1 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,8261 |
| Lead substance | 2-methylpropan-1-ol |
| SU | SU22 |
| PROC | PROC13 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 185,25 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,5976 |
| Lead substance | 2-methylpropan-1-ol |

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES001 - Industrial applications: industrial spraying (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

| | |
|-------|--|
| SU3 | Industrial uses: Uses of substances as such or in preparations at industrial sites |
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC5 | Industrial use resulting in inclusion into or onto a matrix |
| PROC7 | Industrial spraying |

Contributing exposure scenario controlling environmental exposure

Use

| | |
|------|--|
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC5 | Industrial use resulting in inclusion into or onto a matrix |

Physical form

liquid

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Maximum amount used per time or activity

Emission days per site: <= 300

Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter soil, waterways or waste water canal.

Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure

Use

SU3

Industrial uses: Uses of substances as such or in preparations at industrial sites

PROC7

Industrial spraying

Physical form

liquid

Maximum amount used per time or activity

Duration of exposure <= 8 h/d

Frequency of exposure <= 220 d/a

Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Read attached instructions before use.

Product substance and product safety related measures

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

Material thickness \geq 0,7

Breakthrough time \geq 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Exposure estimation and reference to its source

| | |
|-----------------------------------|-------------------------|
| SU | SU3 |
| PROC | PROC7 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 0 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0 |
| Lead substance | 2-methylpropan-1-ol |
| SU | SU3 |
| PROC | PROC10 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 15,44 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,0498 |
| Lead substance | 2-methylpropan-1-ol |
| SU | SU3 |
| PROC | PROC13 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 15,44 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,0498 |
| Lead substance | 2-methylpropan-1-ol |

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES004 - Professional uses: roller application or brushing, dipping and pouring and other processing



Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

without aerosol formation (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

| | |
|---------|--|
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |
| PROC10 | Roller application or brushing |
| PROC13 | Treatment of articles by dipping and pouring |
| PROCh01 | Other processing without aerosol formation |

Contributing exposure scenario controlling environmental exposure

Use

| | |
|-------|---|
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |

Physical form

liquid

Maximum amount used per time or activity

Emission days per site: <= 250

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Volatile organic substances will volatilise into the atmospheric air inside.
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure (professional)

Short title of the exposure scenario

Substance number:CES008

Use

| | |
|--------|--|
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| PROC10 | Roller application or brushing |

Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

PROC13 Treatment of articles by dipping and pouring
PROCh01 Other processing without aerosol formation

Physical form liquid

Maximum amount used per time or activity

| | | | |
|-----------------------|----|-----|-----|
| Duration of exposure | <= | 8 | h/d |
| Frequency of exposure | <= | 220 | d/a |

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Volatile organic substances will volatilise into the atmospheric air inside.
Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.
Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material
Multilayer gloves made from
Appropriate Material Fluorinated rubber / butyl-rubber
Material thickness >= 0,7
Breakthrough time >= 30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Exposure estimation and reference to its source

| | |
|-----------------------------------|--------------------------|
| SU | SU22 |
| PROC | PROC10 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 185,25 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,5976 |
| Lead substance | 2-methylpropan-1-ol |
| SU | SU22 |



Trade name: Hesse Wiping stain PEX TD 4220-FT

Version: 14 / WORLD

Revision: 03.08.2024

Replaces Version: 13 / WORLD

Print date: 07.11.25

| | |
|-----------------------------------|--------------------------|
| PROC | PROC11 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 256,1 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,8261 |
| Lead substance | 2-methylpropan-1-ol |
| SU | SU22 |
| PROC | PROC13 |
| Assessment method | Long-term inhalative |
| Exposure assessment | 185,25 mg/m ³ |
| Exposure assessment (method) | ECETOC TRA |
| Risk characterisation ratio (RCR) | 0,5976 |
| Lead substance | 2-methylpropan-1-ol |

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.