

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse HYDRO Multi stain PEX WUE XX-FT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)  
Skin Sens. 1 H317

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

##### Hazard pictograms



##### Signal word

Warning

##### Hazard statements

H317 May cause an allergic skin reaction.

##### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.

### **Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)**

contains 1,2-benzisothiazol-3(2H)-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

### **2.3. Other hazards**

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## **SECTION 3: Composition/information on ingredients \*\*\***

### **Hazardous ingredients \*\*\***

#### **1,2-benzisothiazol-3(2H)-one**

CAS No.	2634-33-5			
EINECS no.	220-120-9			
Registration no.	01-2120761540-60			
Concentration	>= 0,036	<	0,1	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 4		H302	
	Skin Irrit. 2		H315	
	Eye Dam. 1		H318	
	Skin Sens. 1		H317	
	Aquatic Acute 1		H400	
	Aquatic Chronic 1		H410	
	Acute Tox. 2		H330	

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1	H317	>= 0,036 %
--------------	------	------------

#### **reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)**

CAS No.	55965-84-9			
Concentration		<	0,001	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 2		H330	
	Acute Tox. 2		H310	
	Acute Tox. 3		H301	
	Skin Corr. 1B		H314	
	Skin Sens. 1		H317	
	Aquatic Acute 1		H400	
	Aquatic Chronic 1		H410	
	Eye Dam. 1		H318	

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C	H314	>= 0,6 %
Skin Irrit. 2	H315	>= 0,06 %
Eye Irrit. 2	H319	>= 0,06 %
Skin Sens. 1	H317	>= 0,0015 %
Eye Dam. 1	H318	>= 0,6 %

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Aquatic Chronic 1 H410 M = 100  
Aquatic Acute 1 H400 M = 100

#### Further ingredients

##### propane-1,2-diol

CAS No. 57-55-6  
EINECS no. 200-338-0  
Registration no. 01-2119456809-23  
Concentration  $\geq 1$   $< 10$  %  
Advice: [3]

#### Note

[3] Substance with occupational exposure limits

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

#### After inhalation

When spray fog inhaled, seek medical aid.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced.  
Exposure to decomposition products may cause a health hazard.

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 7 and 8.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### **Advice on protection against fire and explosion**

Fight fire with normal precautions from a reasonable distance.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Storage stability**

Protect from frost.

#### **Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### **Hints on storage assembly**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### **Storage classes**

Storage class according to TRGS 510      10      Flammable liquids

#### **Further information on storage conditions**

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

accordance with the particular national regulations.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### propane-1,2-diol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	168	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	10	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	50	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	10	mg/m <sup>3</sup>

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	oral	
Mode of action	Systemic effects	

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Concentration 0,09 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure inhalative

Mode of action Local effects

Concentration 0,02 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short-term

Route of exposure inhalative

Mode of action Local effects

Concentration 0,04 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short-term

Route of exposure Oral exposure

Mode of action Systemic effects

Concentration 0,11 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Workers (industrial)

Duration of exposure Short-term

Route of exposure inhalative

Mode of action Local effects

Concentration 0,04 mg/m<sup>3</sup>

#### 1,2-benzisothiazol-3(2H)-one

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 6,81 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Long term

Route of exposure dermal

Mode of action Systemic effects

Concentration 0,966 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 1,2 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,345	mg/kg

### Predicted No Effect Concentration (PNEC)

#### propane-1,2-diol

Type of value	PNEC	
Type	Freshwater	
Concentration	260	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	26	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	20000	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	572	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	57,2	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	50	mg/kg

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Type of value	PNEC	
Type	Marine	
Concentration	3,39	µg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	0,23	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Soil	

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Concentration	0,01	mg/kg
---------------	------	-------

Type of value	PNEC	
Type	Freshwater	
Concentration	3,39	µg/l

#### **1,2-benzisothiazol-3(2H)-one**

Type of value	PNEC	
Type	Freshwater	
Concentration	4,03	µg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,403	µg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	1,03	mg/l

Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,0499	mg/kg

Type of value	PNEC	
Type	Marine sediment	
Concentration	0,00499	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	3	mg/kg

## **8.2. Exposure controls**

### **Exposure controls**

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### **Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### **Hand protection**

Glove material	
Appropriate Material	butyl-rubber
Material thickness	>= 0,5 mm
Breakthrough time	>= 120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and



Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### **Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

**Physical state** liquid

**Colour** coloured

**Odour** characteristic

#### **Melting point**

Remarks not determined

#### **Freezing point**

Remarks not determined

#### **Boiling point or initial boiling point and boiling range**

Value 100 to 244 °C

#### **Flammability**

not determined

#### **Upper and lower explosive limits**

Remarks not determined

#### **Flash point**

Value > 60 °C

#### **Auto-ignition temperature**

Remarks not determined

#### **Decomposition temperature**

Remarks not determined

#### **pH value**

Value 8

Concentration/H<sub>2</sub>O 100

Remarks Not applicable

#### **Viscosity**

Remarks not determined

#### **Solubility(ies)**

Remarks not determined

#### **Partition coefficient n-octanol/water (log value)**

Remarks not determined

#### **Vapour pressure**

Remarks not determined

#### **Density and/or relative density**

Value appr. 1,07 kg/l

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Temperature 20 °C

**Relative vapour density**

Remarks not determined

**Particle characteristics**

Remarks not determined

**9.2. Other information**

**Odour threshold**

Remarks not determined

**Solubility in water**

Remarks not determined

**Efflux time**

Value 20 to 48 s  
Temperature 20 °C  
Method DIN EN ISO 2431 - 3 mm

**Explosive properties**

evaluation not determined

**Oxidising properties**

Remarks not determined

**Non-volatile content**

Value 14,5 %

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Stable under recommended storage and handling conditions (see section 7).

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

To avoid thermal decomposition, do not overheat.

**10.4. Conditions to avoid**

Isolate from sources of heat, sparks and open flame.

**10.5. Incompatible materials**

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

**10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

**SECTION 11: Toxicological information**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute oral toxicity**

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

### Acute oral toxicity (Components)

#### 1,2-benzisothiazol-3(2H)-one

Species	rat	
LD50	450	mg/kg
Source	Annex VI Hazardous Substance	

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

ATE	53	mg/kg
-----	----	-------

### Acute dermal toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Acute dermal toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

ATE	50	mg/kg
Method	conversion	

### Acute inhalational toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Acute inhalative toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

ATE	0,05	mg/l
Duration of exposure	4	h
Administration/Form	Dust/Mist	
Method	conversion value	
Remarks	Mist	

### Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Skin corrosion/irritation (Components)

#### 1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to skin.
------------	---------------------

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	rabbit
evaluation	Severe skin irritation

### Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Serious eye damage/irritation (Components)

#### 1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to eyes.
------------	---------------------

### Sensitization

evaluation	May cause sensitization by skin contact.
Method	Calculation method (Regulation (EC) No. 1272/2008)

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Remarks The classification criteria are met.

### Sensitization (Components)

#### 1,2-benzisothiazol-3(2H)-one

Reference substance 1,2-benzisothiazol-3(2H)-one  
evaluation May cause sensitization by skin contact.

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species guinea pig  
evaluation Causes sensitisation on guinea-pigs.

### Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Reproductive toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Carcinogenicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity (STOT)

#### Single exposure

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

#### Repeated exposure

Remarks Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Other information

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

#### 1,2-benzisothiazol-3(2H)-one

Species Oncorhynchus mykiss (rainbow trout)  
LC50 2,18 mg/l  
Duration of exposure 96 h

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

Species	Oncorhynchus mykiss (rainbow trout)	
LC50	0,19	mg/l
Duration of exposure	96	h

#### Daphnia toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

Species	Daphnia magna (Water flea)	
EC50	2,94	mg/l
Duration of exposure	48	h

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Daphnia magna (Water flea)	
EC50	0,16	mg/l
Duration of exposure	48	h

#### Algae toxicity (Components)

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Scenedesmus capricornutum (fresh water algae)	
EC50	0,018	mg/l
Duration of exposure	72	h

#### Bacteria toxicity (Components)

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	activated sludge	
EC50	4,5	mg/l

## 12.2. Persistence and degradability

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Biodegradability (Components)

#### 1,2-benzisothiazol-3(2H)-one

evaluation Not readily biodegradable.

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

evaluation Not readily biodegradable.

## 12.3. Bioaccumulative potential

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Partition coefficient n-octanol/water (log value)

Remarks not determined

## 12.4. Mobility in soil

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Mobility in soil

no data available

## 12.5. Results of PBT and vPvB assessment

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

## 12.6 Endocrine disrupting properties

### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## 12.7. Other adverse effects

### General information

For this subsection there is no ecotoxicological data available on the product as such.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

## SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

### Information for all modes of transport

#### 14.6. Special precautions for user

See Sections 6 to 8

### Other information

#### 14.7. Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restriction according to annex XVII to regulation (EU) No 1907/2006

The product is subject to restrictions according to Annex XVII Regulation (EU) No. 1907/2006: Entry No.

Trade name: Hesse HYDRO Multi stain PEX WUE XX-FT

Version: 21 / WORLD

Revision: 22.09.2025

Replaces Version: 20 / WORLD

Print date: 07.11.25

3.

## **SECTION 16: Other information**

### **Hazard statements listed in Chapter 3**

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### **CLP categories listed in Chapter 3**

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.