

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse PERFECT-COLOR, matt PEX HDB 54343-F

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	REACHSET 1000
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying
	REACHSET 2001
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3- one [EC no. 220-239-6] (3:1), May produce an allergic reaction.

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

## Supplemental information

EUH210

Safety data sheet available on request.

## 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### 3-butoxypropan-2-ol

CAS No.	5131-66-8			
EINECS no.	225-878-4			
Registration no.	01-2119475527-28			
Concentration	>= 1	<	10	%
Classification (Regulation (EC) No. 1272/2008)				
	Eye Irrit. 2		H319	
	Skin Irrit. 2		H315	

#### 1,2-benzisothiazol-3(2H)-one

CAS No.	2634-33-5			
EINECS no.	220-120-9			
Registration no.	01-2120761540-60			
Concentration		<	0,036	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 4		H302	
	Skin Irrit. 2		H315	
	Eye Dam. 1		H318	
	Skin Sens. 1		H317	
	Aquatic Acute 1		H400	
	Aquatic Chronic 1		H410	
	Acute Tox. 2		H330	

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 >= 0,036 %

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

CAS No.	55965-84-9			
EINECS no.	611-341-5			
Concentration		<	0,001	%
Classification (Regulation (EC) No. 1272/2008)				
	Acute Tox. 2		H330	
	Acute Tox. 2		H310	
	Acute Tox. 3		H301	
	Skin Corr. 1B		H314	
	Skin Sens. 1		H317	
	Aquatic Acute 1		H400	
	Aquatic Chronic 1		H410	
	Eye Dam. 1		H318	

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C	H314	$\geq 0,6 \%$
Skin Irrit. 2	H315	$\geq 0,06 \%$
Eye Irrit. 2	H319	$\geq 0,06 \%$
Skin Sens. 1	H317	$\geq 0,0015 \%$
Eye Dam. 1	H318	$\geq 0,6 \%$
Aquatic Chronic 1	H410	M = 100
Aquatic Acute 1	H400	M = 100

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

#### After inhalation

When spray fog inhaled, seek medical aid.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

#### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

#### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 7 and 8.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

##### **Advice on protection against fire and explosion**

Fight fire with normal precautions from a reasonable distance.

#### **7.2. Conditions for safe storage, including any incompatibilities**

##### **Storage stability**

Protect from frost.

##### **Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

##### **Hints on storage assembly**

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

##### **Storage classes**

Storage class according to TRGS 510      10      Flammable liquids

##### **Further information on storage conditions**

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

## Other information

-

## Derived No/Minimal Effect Levels (DNEL/DMEL)

### 3-butoxypropan-2-ol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	8,75	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	16	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	44	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	33,8	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	270,5	mg/m <sup>3</sup>

### 1,2-benzisothiazol-3(2H)-one

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	6,81	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

Mode of action	Systemic effects	
Concentration	0,966	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,2	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,345	mg/kg

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	0,09	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,04	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	0,11	mg/kg/d

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,04	mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC)

#### 3-butoxypropan-2-ol

Type of value	PNEC	
Type	Freshwater	
Concentration	0,525	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,0525	mg/l
Type of value	PNEC	
Conditions	sporadic release	
Concentration	5,25	mg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	2,36	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,236	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,16	mg/kg

#### 1,2-benzisothiazol-3(2H)-one

Type of value	PNEC	
Type	Freshwater	
Concentration	4,03	µg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,403	µg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	1,03	mg/l
Type of value	PNEC	

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

Type	Freshwater sediment	
Concentration	0,0499	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,00499	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	3	mg/kg

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Type of value	PNEC	
Type	marine water	
Concentration	3,39	µg/l
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	0,23	mg/l
Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Marine sediment	
Concentration	0,027	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,01	mg/kg
Type of value	PNEC	
Type	Freshwater	
Concentration	3,39	µg/l

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Glove material	
Appropriate Material	butyl-rubber
Material thickness	>= 0,5 mm



Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

Breakthrough time  $\geq$  120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** liquid

**Colour** colourless

**Odour** characteristic

#### Melting point

Remarks not determined

#### Freezing point

Remarks not determined

#### Boiling point or initial boiling point and boiling range

Value 78 to 170 °C

#### Flammability

not determined

#### Upper and lower explosive limits

Remarks not determined

#### Flash point

Value  $>$  60 °C

#### Auto-ignition temperature

Remarks not determined

#### Decomposition temperature

Remarks not determined

#### pH value

Value 8

Concentration/H<sub>2</sub>O 100

Remarks Not applicable

#### Viscosity

Remarks not determined

#### Solubility(ies)

Remarks not determined

#### Partition coefficient n-octanol/water (log value)

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

Remarks not determined

#### Vapour pressure

Remarks not determined

#### Density and/or relative density

Value appr. 1,047 kg/l  
Temperature 20 °C

#### Relative vapour density

Remarks not determined

#### Particle characteristics

Remarks not determined

### 9.2. Other information

#### Odour threshold

Remarks not determined

#### Solubility in water

Remarks not determined

#### Efflux time

Value 28 to 42 s  
Temperature 20 °C  
Method DIN 53211 - 6 mm

#### Explosive properties

evaluation not determined

#### Oxidising properties

Remarks not determined

#### Non-volatile content

Value 37,6 %  
Method calculated value

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

### 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Acute oral toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

Species	rat	
LD50	450	mg/kg
Source	Annex VI Hazardous Substance	

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

ATE	53	mg/kg
-----	----	-------

#### Acute dermal toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Acute dermal toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

ATE	50	mg/kg
Method	conversion	

#### Acute inhalational toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Acute inhalative toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

ATE	0,05	mg/l
Duration of exposure	4	h
Administration/Form	Dust/Mist	
Method	conversion value	

#### Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation (Components)

##### 3-butoxypropan-2-ol

Species	rabbit
evaluation	Irritating to skin.

##### 1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to skin.
------------	---------------------

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	rabbit
evaluation	Severe skin irritation

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

### Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Serious eye damage/irritation (Components)

#### 3-butoxypropan-2-ol

Species	rabbit
evaluation	irritating

#### 1,2-benzisothiazol-3(2H)-one

evaluation	Irritating to eyes.
------------	---------------------

### Sensitization

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Sensitization (Components)

#### 1,2-benzisothiazol-3(2H)-one

Reference substance	1,2-benzisothiazol-3(2H)-one
evaluation	May cause sensitization by skin contact.

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	guinea pig
evaluation	Causes sensitisation on guinea-pigs.

### Mutagenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Reproductive toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Carcinogenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity (STOT)

#### Single exposure

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Other information

No toxicological data are available.

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

Species	Oncorhynchus mykiss (rainbow trout)
LC50	2,18 mg/l
Duration of exposure	96 h

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Oncorhynchus mykiss (rainbow trout)
LC50	0,19 mg/l
Duration of exposure	96 h

#### Daphnia toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

Species	Daphnia magna (Water flea)
EC50	2,94 mg/l
Duration of exposure	48 h

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Daphnia magna (Water flea)
EC50	0,16 mg/l
Duration of exposure	48 h

#### Algae toxicity (Components)

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Scenedesmus capricornutum (fresh water algae)
EC50	0,018 mg/l
Duration of exposure	72 h

#### Bacteria toxicity (Components)

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	activated sludge
EC50	4,5 mg/l

### 12.2. Persistence and degradability

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Biodegradability (Components)

##### 1,2-benzisothiazol-3(2H)-one

evaluation	Not readily biodegradable.
------------	----------------------------

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

evaluation	Not readily biodegradable.
------------	----------------------------

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

### 12.3. Bioaccumulative potential

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Partition coefficient n-octanol/water (log value)

Remarks not determined

### 12.4. Mobility in soil

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Mobility in soil

no data available

### 12.5. Results of PBT and vPvB assessment

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

### 12.6 Endocrine disrupting properties

#### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

### 12.7. Other adverse effects

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

## SECTION 14: Transport information

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

### Information for all modes of transport

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

#### 14.6. Special precautions for user

See Sections 6 to 8

#### Other information

##### 14.7. Maritime transport in bulk according to IMO instruments

Not relevant

### SECTION 15: Regulatory information \*\*\*

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### VOC \*\*\*

VOC (EU)	2,7	%	29	g/l
----------	-----	---	----	-----

### SECTION 16: Other information

#### Hazard statements listed in Chapter 3

H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not



Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

guarantee certain properties.

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES017 - Industrial applications: industrial spraying (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix

### **Physical form**

liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 300

### **Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Curing takes place through UV light exposure (only with UV light curing systems ).  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

### **Waste water**

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

### **Exhaust air**

Keep container closed. Avoid release to the environment.

### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

### **Disposal recommendations for the product**

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

### **Disposal recommendations for packaging**

Completely emptied packagings can be given for recycling.

## **Contributing exposure scenario controlling worker exposure**

### **Use**

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
-----	--



Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

PROC7 Industrial spraying

**Physical form** liquid

**Maximum amount used per time or activity**

Duration of exposure <= 8 h/d

Frequency of exposure <= 220 d/a

**Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems ).

Read attached instructions before use.

**Product substance and product safety related measures**

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

**Hand protection**

Glove material

Appropriate Material butyl-rubber

Material thickness >= 0,5

Breakthrough time >= 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

**Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

**Information on estimated exposure and downstream-user guidance**

**Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

**Annex to the extended Safety Data Sheet (eSDS)**

**Short title of the exposure scenario**

ES019 - Professional uses: Non industrial spraying (inside)

Trade name: Hesse PERFECT-COLOR, matt PEX HDB 54343-F

Version: 2 / ZA

Revision: 10.09.2025

Replaces Version: 1 / ZA

Print date: 01.12.25

### Use of the substance/preparation

Surface treatment of wood and other materials

#### Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC11	Non industrial spraying

## Contributing exposure scenario controlling environmental exposure

#### Use

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

#### Physical form

liquid

#### Maximum amount used per time or activity

Emission days per site: <= 250

#### Other relevant operational conditions

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Curing takes place through UV light exposure (only with UV light curing systems ).  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

#### Waste water

Do not discharge into the drains/surface waters/groundwater.

#### Exhaust air

Keep container closed. Avoid release to the environment.

#### Soil

Floors should be impervious, resistant to liquids and easy to clean.

#### Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

#### Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

## Contributing exposure scenario controlling worker exposure (professional)

#### Short title of the exposure scenario

Substance number:CES038

#### Use

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC11	Non industrial spraying

#### Physical form

liquid

#### Maximum amount used per time or activity

Duration of exposure <= 8 h/d

Print date: 01.12.25