

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Hesse HYDRO Isolating filler PEX HP 6645-FT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/preparation

Surface treatment of wood and other materials

Identified Uses

| | |
|--------|--|
| | REACHSET 1000 |
| SU3 | Industrial uses: Uses of substances as such or in preparations at industrial sites |
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC5 | Industrial use resulting in inclusion into or onto a matrix |
| PROC7 | Industrial spraying |
| | REACHSET 2001 |
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |
| PROC11 | Non industrial spraying |

1.3. Details of the supplier of the safety data sheet

Manufacturer

Hesse GmbH & Co. KG
Warendorfer Strasse 21
59075 Hamm (Germany)
Telephone no. +49 (0) 2381 963-00
Fax no. +49 (0) 2381 963-849
E-mail address ps@hesse-lignal.de

1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (Regulation (EC) No. 1272/2008)

This product is not classified hazardous in accordance with Regulation (EC) No 1272/2008.

2.2. Label elements

Labelling according to regulation (EC) No 1272/2008

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3- one [EC no. 220-239-6] (3:1), May produce an allergic reaction.

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Supplemental information

EUH210

Safety data sheet available on request.

2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

SECTION 3: Composition/information on ingredients

Hazardous ingredients

3-iodo-2-propynyl butylcarbamate

CAS No. 55406-53-6

EINECS no. 259-627-5

Concentration \geq 0,01 < 0,1 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3 H331

Route of exposure: Inhalation exposure

Acute Tox. 4 H302

Route of exposure: Oral exposure

Eye Dam. 1 H318

Skin Sens. 1 H317

STOT SE 3 H335

Respiratory tract

Aquatic Acute 1 H400

Aquatic Chronic 1 H410

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400 M = 10

1,2-benzisothiazol-3(2H)-one

CAS No. 2634-33-5

EINECS no. 220-120-9

Registration no. 01-2120761540-60

Concentration < 0,036 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H302

Skin Irrit. 2 H315

Eye Dam. 1 H318

Skin Sens. 1 H317

Aquatic Acute 1 H400

Aquatic Chronic 1 H410

Acute Tox. 2 H330

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 \geq 0,036 %

Bronopol (INN)

CAS No. 52-51-7

EINECS no. 200-143-0

Registration no. 01-2119980938-15

Concentration \geq 0,01 < 0,1 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4 H312

Acute Tox. 4 H302

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

| | | |
|-------------------|------|-------------------|
| STOT SE 3 | H335 | Respiratory tract |
| Skin Irrit. 2 | H315 | |
| Eye Dam. 1 | H318 | |
| Aquatic Acute 1 | H400 | |
| Aquatic Chronic 1 | H410 | |

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1 H400 M = 10

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

CAS No. 55965-84-9

EINECS no. 611-341-5

Concentration < 0,001 %

Classification (Regulation (EC) No. 1272/2008)

| | |
|-------------------|------|
| Acute Tox. 2 | H330 |
| Acute Tox. 2 | H310 |
| Acute Tox. 3 | H301 |
| Skin Corr. 1B | H314 |
| Skin Sens. 1 | H317 |
| Aquatic Acute 1 | H400 |
| Aquatic Chronic 1 | H410 |
| Eye Dam. 1 | H318 |

Concentration limits (Regulation (EC) No. 1272/2008)

| | | |
|-------------------|------|-------------|
| Skin Corr. 1C | H314 | >= 0,6 % |
| Skin Irrit. 2 | H315 | >= 0,06 % |
| Eye Irrit. 2 | H319 | >= 0,06 % |
| Skin Sens. 1 | H317 | >= 0,0015 % |
| Eye Dam. 1 | H318 | >= 0,6 % |
| Aquatic Chronic 1 | H410 | M = 100 |
| Aquatic Acute 1 | H400 | M = 100 |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

After inhalation

When spray fog inhaled, seek medical aid.

After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

After ingestion

Do not induce vomiting. Take medical treatment.

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

4.3. Indication of any immediate medical attention and special treatment needed

Hints for the physician / treatment

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Recommended: alcohol resistant foam, CO₂, powders, water spray/mist

Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

5.3. Advice for firefighters

Special protective equipment for fire-fighting

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

Other information

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

6.2. Environmental precautions

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes.

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

7.2. Conditions for safe storage, including any incompatibilities

Storage stability

Protect from frost.

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

Storage classes

Storage class according to TRGS 510 10 Flammable liquids

Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

SECTION 8: Exposure controls/personal protection ***

8.1. Control parameters

Other information

-

Derived No/Minimal Effect Levels (DNEL/DMEL) ***

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (industrial) | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 0,02 | mg/m ³ |

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | oral | |
| Mode of action | Systemic effects | |
| Concentration | 0,09 | mg/kg/d |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long-term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 0,02 | mg/m ³ |

| | | |
|---------------|--------------------------------|--|
| Type of value | Derived No Effect Level (DNEL) | |
|---------------|--------------------------------|--|

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

| | | |
|----------------------|---------------|-------------------|
| Reference group | Consumer | |
| Duration of exposure | Short-term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 0,04 | mg/m ³ |

| | | |
|----------------------|--------------------------------|---------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Short-term | |
| Route of exposure | Oral exposure | |
| Mode of action | Systemic effects | |
| Concentration | 0,11 | mg/kg/d |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Workers (industrial) | |
| Duration of exposure | Short-term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 0,04 | mg/m ³ |

1,2-benzisothiazol-3(2H)-one

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 6,81 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 0,966 | mg/kg |

| | | |
|----------------------|--------------------------------|-------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 1,2 | mg/m ³ |

| | | |
|----------------------|--------------------------------|-------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 0,345 | mg/kg |

Bronopol (INN)

| | | |
|----------------------|--------------------------------|--|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

| | | |
|----------------------|--------------------------------|---------|
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 3,5 | mg/m³ |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Short term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 10,5 | mg/m³ |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 2,5 | mg/m³ |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Short term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 2,5 | mg/m³ |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 2 | mg/kg/d |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Short term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 6 | mg/kg/d |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 0,6 | mg/m³ |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Short term | |
| Route of exposure | inhalative | |
| Mode of action | Systemic effects | |
| Concentration | 1,8 | mg/m³ |



Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

| | | |
|----------------------|--------------------------------|--------------------|
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 0,6 | mg/m ³ |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Short term | |
| Route of exposure | inhalative | |
| Mode of action | Local effects | |
| Concentration | 0,6 | mg/m ³ |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 0,7 | mg/kg/d |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Short term | |
| Route of exposure | dermal | |
| Mode of action | Systemic effects | |
| Concentration | 2,1 | mg/kg/d |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | oral | |
| Mode of action | Systemic effects | |
| Concentration | 0,18 | mg/kg/d |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Short term | |
| Route of exposure | oral | |
| Mode of action | Systemic effects | |
| Concentration | 0,15 | mg/kg/d |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Mode of action | Local effects | |
| Concentration | 0,008 | mg/cm ² |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Worker | |
| Duration of exposure | Short term | |
| Route of exposure | dermal | |

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

| | | |
|----------------------|--------------------------------|--------------------|
| Mode of action | Local effects | |
| Concentration | 0,008 | mg/cm ² |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Long term | |
| Route of exposure | dermal | |
| Concentration | 0,004 | mg/cm ² |
| Type of value | Derived No Effect Level (DNEL) | |
| Reference group | Consumer | |
| Duration of exposure | Short term | |
| Route of exposure | dermal | |
| Mode of action | Local effects | |
| Concentration | 0,004 | mg/cm ² |

Predicted No Effect Concentration (PNEC) ***

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | |
|---------------|------------------------------|-------|
| Type of value | PNEC | |
| Type | marine water | |
| Concentration | 3,39 | µg/l |
| Type of value | PNEC | |
| Type | Sewage treatment plant (STP) | |
| Concentration | 0,23 | mg/l |
| Type of value | PNEC | |
| Type | Freshwater sediment | |
| Concentration | 0,027 | mg/kg |
| Type of value | PNEC | |
| Type | Marine sediment | |
| Concentration | 0,027 | mg/kg |
| Type of value | PNEC | |
| Type | Soil | |
| Concentration | 0,01 | mg/kg |
| Type of value | PNEC | |
| Type | Freshwater | |
| Concentration | 3,39 | µg/l |

1,2-benzisothiazol-3(2H)-one

| | | |
|---------------|------------|------|
| Type of value | PNEC | |
| Type | Freshwater | |
| Concentration | 4,03 | µg/l |
| Type of value | PNEC | |
| Type | Saltwater | |
| Concentration | 0,403 | µg/l |

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

| | | |
|-----------------------|------------------------------|-------|
| Type of value | PNEC | |
| Type | Sewage treatment plant (STP) | |
| Concentration | 1,03 | mg/l |
| Type of value | PNEC | |
| Type | Freshwater sediment | |
| Concentration | 0,0499 | mg/kg |
| Type of value | PNEC | |
| Type | Marine sediment | |
| Concentration | 0,00499 | mg/kg |
| Type of value | PNEC | |
| Type | Soil | |
| Concentration | 3 | mg/kg |
| Bronopol (INN) | | |
| Type of value | PNEC | |
| Type | Freshwater | |
| Concentration | 0 | mg/l |
| Type of value | PNEC | |
| Type | Saltwater | |
| Concentration | 0,001 | mg/l |
| Type of value | PNEC | |
| Type | Sewage treatment plant (STP) | |
| Concentration | 0,43 | mg/l |
| Type of value | PNEC | |
| Type | Freshwater sediment | |
| Concentration | 0,008 | mg/kg |
| Type of value | PNEC | |
| Type | Marine sediment | |
| Concentration | 0,009 | mg/l |
| Type of value | PNEC | |
| Type | Sediment | |
| Concentration | 0,21 | mg/kg |

8.2. Exposure controls

Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Hand protection

Glove material

Appropriate Material butyl-rubber

Material thickness \geq 0,5 mm

Breakthrough time \geq 120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state liquid

Colour coloured

Odour characteristic

Melting point

Remarks not determined

Freezing point

Remarks not determined

Boiling point or initial boiling point and boiling range

Value 100 to 195 °C

Flammability

not determined

Upper and lower explosive limits

Remarks not determined

Flash point

Value $>$ 60 °C

Auto-ignition temperature

Remarks not determined

Decomposition temperature

Remarks not determined

pH value

Value 8

Concentration/H₂O 100

Remarks Not applicable

Viscosity

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Remarks not determined

Solubility(ies)

Remarks not determined

Partition coefficient n-octanol/water (log value)

Remarks not determined

Vapour pressure

Remarks not determined

Density and/or relative density

| | | |
|-------------|-------------|------|
| Value | appr. 1,258 | kg/l |
| Temperature | 20 °C | |

Relative vapour density

Remarks not determined

Particle characteristics

Remarks not determined

9.2. Other information

Odour threshold

Remarks not determined

Solubility in water

Remarks not determined

Efflux time

Method not applicable

Explosive properties

evaluation not determined

Oxidising properties

Remarks not determined

Non-volatile content

| | | |
|--------|------------------|---|
| Value | appr. 55 | % |
| Method | calculated value | |

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO_x), dense black smoke, No decomposition if used as prescribed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Acute oral toxicity (Components)

1,2-benzisothiazol-3(2H)-one

| | | |
|---------|------------------------------|-------|
| Species | rat | |
| LD50 | 450 | mg/kg |
| Source | Annex VI Hazardous Substance | |

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | |
|-----|----|-------|
| ATE | 53 | mg/kg |
|-----|----|-------|

Bronopol (INN)

| | | |
|---------|-----|-------|
| Species | rat | |
| LD50 | 307 | mg/kg |

3-iodo-2-propynyl butylcarbamate

| | | |
|--------|------------------|-------|
| ATE | 500 | mg/kg |
| Method | conversion value | |

Acute dermal toxicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Acute dermal toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | |
|--------|------------|-------|
| ATE | 50 | mg/kg |
| Method | conversion | |

Bronopol (INN)

| | | |
|---------|--------|-------|
| Species | rabbit | |
| LD50 | 1600 | mg/kg |

Acute inhalational toxicity

| | |
|---------|---|
| Method | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks | Based on available data, the classification criteria are not met. |

Acute inhalative toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | |
|----------------------|------------------|------|
| ATE | 0,05 | mg/l |
| Duration of exposure | 4 | h |
| Administration/Form | Dust/Mist | |
| Method | conversion value | |

3-iodo-2-propynyl butylcarbamate

| | | |
|-----|-----|------|
| ATE | 0,5 | mg/l |
|-----|-----|------|

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Duration of exposure 4 h
Administration/Form Dust/Mist
Method conversion value

Skin corrosion/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Skin corrosion/irritation (Components)

1,2-benzisothiazol-3(2H)-one

evaluation Irritating to skin.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species rabbit
evaluation Severe skin irritation

Bronopol (INN)

evaluation Irritating to skin.

Serious eye damage/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Serious eye damage/irritation (Components)

1,2-benzisothiazol-3(2H)-one

evaluation Irritating to eyes.

Bronopol (INN)

evaluation irritant - risk of serious damage to eyes

3-iodo-2-propynyl butylcarbamate

Sensitization

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Sensitization (Components)

1,2-benzisothiazol-3(2H)-one

Reference substance 1,2-benzisothiazol-3(2H)-one
evaluation May cause sensitization by skin contact.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species guinea pig
evaluation Causes sensitisation on guinea-pigs.

3-iodo-2-propynyl butylcarbamate

evaluation May cause sensitization by skin contact.

Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Reproductive toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Carcinogenicity

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Specific Target Organ Toxicity (STOT)

Single exposure

Method Calculation method (Regulation (EC) No. 1272/2008)
Remarks Based on available data, the classification criteria are not met.

Repeated exposure

Remarks Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) (Components)

Bronopol (INN)

Specific target organ toxicity - single exposure

evaluation May cause respiratory irritation.
Route of exposure inhalative
Organs: Respiratory tract

3-iodo-2-propynyl butylcarbamate

Specific target organ toxicity - single exposure

evaluation May cause respiratory irritation.
Organs: Respiratory tract

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

Other information

No toxicological data are available.

SECTION 12: Ecological information

12.1. Toxicity

General information

For this subsection there is no ecotoxicological data available on the product as such.

Fish toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species Oncorhynchus mykiss (rainbow trout)
LC50 2,18 mg/l
Duration of exposure 96 h

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species Oncorhynchus mykiss (rainbow trout)
LC50 0,19 mg/l
Duration of exposure 96 h

Daphnia toxicity (Components)

1,2-benzisothiazol-3(2H)-one

Species Daphnia magna (Water flea)
EC50 2,94 mg/l
Duration of exposure 48 h

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| EC50 | 0,16 | | mg/l |
| Duration of exposure | 48 | h | |

Bronopol (INN)

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| EC50 | < 0,1 | | mg/l |
| Duration of exposure | 48 | h | |

3-iodo-2-propynyl butylcarbamate

| | | | |
|----------------------|----------------------------|---|------|
| Species | Daphnia magna (Water flea) | | |
| EC50 | < 0,01 | | mg/l |
| Duration of exposure | 48 | h | |

Algae toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | | |
|----------------------|---|---|------|
| Species | Scenedesmus capricornutum (fresh water algae) | | |
| EC50 | 0,018 | | mg/l |
| Duration of exposure | 72 | h | |

Bacteria toxicity (Components)

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

| | | | |
|---------|------------------|--|------|
| Species | activated sludge | | |
| EC50 | 4,5 | | mg/l |

12.2. Persistence and degradability

General information

For this subsection there is no ecotoxicological data available on the product as such.

Biodegradability (Components)

1,2-benzisothiazol-3(2H)-one

evaluation Not readily biodegradable.

reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

evaluation Not readily biodegradable.

12.3. Bioaccumulative potential

General information

For this subsection there is no ecotoxicological data available on the product as such.

Partition coefficient n-octanol/water (log value)

Remarks not determined

Octanol/water partition coefficient (log Pow) (Components)

Bronopol (INN)

| | | |
|-------------|------|----|
| log Pow | 0,15 | |
| Temperature | 23 | °C |

12.4. Mobility in soil

General information

For this subsection there is no ecotoxicological data available on the product as such.

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

General information

For this subsection there is no ecotoxicological data available on the product as such.

Results of PBT and vPvB assessment

The product contains no PBT substances

The product contains no vPvB substances.

12.6 Endocrine disrupting properties

Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

12.7. Other adverse effects

General information

For this subsection there is no ecotoxicological data available on the product as such.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

SECTION 14: Transport information

| | Land transport ADR/RID | Marine transport IMDG/GGVSee | Air transport ICAO/IATA |
|------------------------|--|--|--|
| 14.1. UN number | Not classified as dangerous in the meaning of transport regulations. | Not classified as dangerous in the meaning of sea and air transport regulations. | Not a dangerous substance as defined in the above regulations. |

Information for all modes of transport

14.6. Special precautions for user

See Sections 6 to 8

Other information

14.7. Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information ***

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

VOC

VOC (EU) 7 % 80 g/l

Ingredients with restrictions according to Annex XVII Regulation (EU) No. 1907/2006 ***

Bronopol (INN)

Entry No. 75 (*)

(*) Conditions of restriction see Annex XVII Regulation (EU) No. 1907/2006 (REACH)

Other information

All components are contained in the TSCA inventory or exempted.

SECTION 16: Other information

Hazard statements listed in Chapter 3

| | |
|------|---|
| H301 | Toxic if swallowed. |
| H302 | Harmful if swallowed. |
| H310 | Fatal in contact with skin. |
| H312 | Harmful in contact with skin. |
| H314 | Causes severe skin burns and eye damage. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H330 | Fatal if inhaled. |
| H331 | Toxic if inhaled. |
| H335 | May cause respiratory irritation. |
| H400 | Very toxic to aquatic life. |
| H410 | Very toxic to aquatic life with long lasting effects. |

CLP categories listed in Chapter 3

| | |
|-------------------|--|
| Acute Tox. 2 | Acute toxicity, Category 2 |
| Acute Tox. 3 | Acute toxicity, Category 3 |
| Acute Tox. 4 | Acute toxicity, Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment, acute, Category 1 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic, Category 1 |
| Eye Dam. 1 | Serious eye damage, Category 1 |
| Skin Corr. 1B | Skin corrosion, Category 1B |
| Skin Irrit. 2 | Skin irritation, Category 2 |
| Skin Sens. 1 | Skin sensitization, Category 1 |
| STOT SE 3 | Specific target organ toxicity - single exposure, Category 3 |

Changes since the last version are highlighted in the margin (***). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES017 - Industrial applications: industrial spraying (inside)

Use of the substance/preparation

Surface treatment of wood and other materials

Use

| | |
|-------|--|
| SU3 | Industrial uses: Uses of substances as such or in preparations at industrial sites |
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
| ERC5 | Industrial use resulting in inclusion into or onto a matrix |
| PROC7 | Industrial spraying |

Contributing exposure scenario controlling environmental exposure

Use

| | |
|------|--|
| ERC4 | Industrial use of processing aids in processes and products, not becoming part of articles |
|------|--|

| | |
|------|---|
| ERC5 | Industrial use resulting in inclusion into or onto a matrix |
|------|---|

Physical form

liquid

Maximum amount used per time or activity

Emission days per site: <= 300

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure

Use

| | |
|-------|--|
| SU3 | Industrial uses: Uses of substances as such or in preparations at industrial sites |
| PROC7 | Industrial spraying |

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Physical form liquid

Maximum amount used per time or activity

| | | | |
|-----------------------|----|-----|-----|
| Duration of exposure | <= | 8 | h/d |
| Frequency of exposure | <= | 220 | d/a |

Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems).

Read attached instructions before use.

Product substance and product safety related measures

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Appropriate Material butyl-rubber

Material thickness >= 0,5

Breakthrough time >= 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Annex to the extended Safety Data Sheet (eSDS)

Short title of the exposure scenario

ES019 - Professional uses: Non industrial spraying (inside)

Use of the substance/preparation



Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Surface treatment of wood and other materials

Use

| | |
|--------|--|
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |
| PROC11 | Non industrial spraying |

Contributing exposure scenario controlling environmental exposure

Use

| | |
|-------|---|
| ERC8a | Wide dispersive indoor use of processing aids in open systems |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |

Physical form

liquid

Maximum amount used per time or activity

Emission days per site: <= 250

Other relevant operational conditions

Use: Room temperature
Drying and through-curing takes place at ambient temperature or at higher temperatures.
Curing takes place through UV light exposure (only with UV light curing systems).
Where possible recycling is preferred to disposal or incineration.
Do not allow to enter soil, waterways or waste water canal.
Dispose of rinse water in accordance with local and national regulations.

Waste water

Do not discharge into the drains/surface waters/groundwater.

Exhaust air

Keep container closed. Avoid release to the environment.

Soil

Floors should be impervious, resistant to liquids and easy to clean.

Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.
Do not allow to enter drains or waterways.

Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

Contributing exposure scenario controlling worker exposure (professional)

Short title of the exposure scenario

Substance number:CES038

Use

| | |
|--------|--|
| SU22 | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| PROC11 | Non industrial spraying |

Physical form

liquid

Maximum amount used per time or activity

| | | | |
|-----------------------|----|-----|-----|
| Duration of exposure | <= | 8 | h/d |
| Frequency of exposure | <= | 220 | d/a |

Trade name: Hesse HYDRO Isolating filler PEX HP 6645-FT

Version: 12 / ZA

Revision: 21.11.2025

Replaces Version: 11 / ZA

Print date: 01.12.25

Other relevant operational conditions

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems).

Read attached instructions before use.

Product substance and product safety related measures

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Hand protection

Glove material

Appropriate Material butyl-rubber

Material thickness \geq 0,5

Breakthrough time \geq 120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Information on estimated exposure and downstream-user guidance

Guidance for Downstream Users

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.