

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse FABULAC , silk matt PEX HUB 85555-F

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	REACHSET 1000
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)  
Skin Sens. 1A H317

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

#### Hazard pictograms



Signal word

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Warning

### Hazard statements

H317 May cause an allergic skin reaction.

### Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.

### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide; 2-propenoic acid, reaction products with dipentaerythritol; 2-methyl-2H-isothiazol-3-one; 1,2-benzisothiazol-3(2H)-one

### 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### 2-butoxyethanol

CAS No.	111-76-2			
EINECS no.	203-905-0			
Registration no.	01-2119475108-36			
Concentration	>= 1	< 5		%
Classification (Regulation (EC) No. 1272/2008)	Acute Tox. 4	H302		
	Eye Irrit. 2	H319		
	Skin Irrit. 2	H315		
	Acute Tox. 3	H331		
ATE	Oral exposure	1.200	mg/kg	
cATpE	Inhalation exposure, Dust/Mist	0,5	mg/l	
				Route of exposure: Oral exposure

#### 2-propenoic acid, reaction products with dipentaerythritol

CAS No.	1384855-91-7			
Registration no.	01-2119980666-22			
Concentration	>= 1	< 4		%
Classification (Regulation (EC) No. 1272/2008)	Eye Irrit. 2	H319		
	Skin Sens. 1A	H317		
	Aquatic Chronic 3	H412		

#### phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

CAS No.	162881-26-7			
EINECS no.	423-340-5			
Registration no.	01-2119489401-38			
Concentration	>= 0,1	< 1		%

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Classification (Regulation (EC) No. 1272/2008)

Skin Sens. 1A	H317
Aquatic Chronic 4	H413

**Triethylamine (neutralized form)**

CAS No. 121-44-8

EINECS no. 204-469-4

Registration no. 01-2119475467-26

Concentration  $\geq 0,1$  < 0,9 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 2	H225
Acute Tox. 3	H331

Route of exposure: Inhalation exposure

Acute Tox. 3	H311
Acute Tox. 3	H301
Skin Corr. 1A	H314
STOT SE 3	H335
Eye Dam. 1	H318

Route of exposure: Dermal exposure

Concentration limits (Regulation (EC) No. 1272/2008)

STOT SE 3 H335  $\geq 1$  %

ATE Oral exposure 100 mg/kg

ATE Dermal exposure 300 mg/kg

cATpE Inhalation exposure, Dust/Mist 0,5 mg/l

**1,2-benzisothiazol-3(2H)-one**

CAS No. 2634-33-5

EINECS no. 220-120-9

Registration no. 01-2120761540-60

Concentration < 0,036 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 4	H302
Skin Irrit. 2	H315
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Acute Tox. 2	H330

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317  $\geq 0,036$  %

**2-methyl-2H-isothiazol-3-one**

CAS No. 2682-20-4

EINECS no. 220-239-6

Registration no. 01-2120764690-50

Concentration < 0,0015 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 3	H301
Acute Tox. 2	H330

Route of exposure: Inhalation exposure

Skin Corr. 1B	H314
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Skin Sens. 1A	H317
Acute Tox. 3	H311
Eye Dam. 1	H318

Concentration limits (Regulation (EC) No. 1272/2008)

Aquatic Acute 1	H400	M = 10
Skin Sens. 1A	H317	>= 0,0015 %

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H  
-isothiazol-3- one [EC no. 220-239-6] (3:1)**

CAS No. 55965-84-9

EINECS no. 611-341-5

Concentration < 0,001 %

Classification (Regulation (EC) No. 1272/2008)

Acute Tox. 2	H330
Acute Tox. 2	H310
Acute Tox. 3	H301
Skin Corr. 1B	H314
Skin Sens. 1	H317
Aquatic Acute 1	H400
Aquatic Chronic 1	H410
Eye Dam. 1	H318

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Corr. 1C	H314	>= 0,6 %
Skin Irrit. 2	H315	>= 0,06 %
Eye Irrit. 2	H319	>= 0,06 %
Skin Sens. 1	H317	>= 0,0015 %
Eye Dam. 1	H318	>= 0,6 %
Aquatic Chronic 1	H410	M = 100
Aquatic Acute 1	H400	M = 100

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In case of accidental skin or eye contact, avoid exposure to ultra-violet light. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

#### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

##### **Hints for the physician / treatment**

Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

##### **Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

#### **5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

#### **5.3. Advice for firefighters**

##### **Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

##### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

#### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

#### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

#### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 7 and 8.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

##### **Advice on safe handling**

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes.

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

### Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

## 7.2. Conditions for safe storage, including any incompatibilities

### Storage stability

Protect from frost.

### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Storage classes

Storage class according to TRGS 510 10 Flammable liquids

### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### 2-butoxyethanol

List	OEL (ZA)		
Value		40	ppm(V)
Status: 03/2021			

##### 2-butoxyethanol

List	OEL	
Value	200	mg/g creatinine

Status: 03/2021

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### 2-butoxyethanol

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Acute effects	
Concentration	89	mg/kg

Type of value	Derived No Effect Level (DNEL)
Reference group	Workers (professional)
Duration of exposure	Long-term
Route of exposure	inhalative
Mode of action	Local effects



Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Concentration	246	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	75	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	20	ppm
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	89	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	246	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1091	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	3,2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	13,4	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	123	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Acute effects	
Concentration	44,5	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Acute effects	
Concentration	426	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	6,3	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	106,4	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	38	mg/kg
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	59	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	49	mg/m <sup>3</sup>



Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	26,7	mg/kg/d

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	135	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	147	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	89	mg/kg/d

**phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	21	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	21	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	21	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	21	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	3,3	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	3,3	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	3,3	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Short-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	3,3	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	5,2	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	1,5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	1,5	mg/kg/d

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

**Triethylamine (neutralized form)**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	8,4	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	8,4	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	12,6	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	12,6	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	12,1	mg/kg/d

**2-propenoic acid, reaction products with dipentaerythritol**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,76	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	0,50	mg/kg

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	0,09	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,02	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,04	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	0,11	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (industrial)	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,04	mg/m <sup>3</sup>

**1,2-benzisothiazol-3(2H)-one**

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	6,81	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
---------------	--------------------------------	--

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,966	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	1,2	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	0,345	mg/kg

#### 2-methyl-2H-isothiazol-3-one

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,021	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,043	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,021	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	0,043	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Mode of action	Systemic effects	
Concentration	0,027	mg/m <sup>3</sup>

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	0,053	mg/m <sup>3</sup>

### **Predicted No Effect Concentration (PNEC)**

#### **2-butoxyethanol**

Type of value	PNEC	
Type	Freshwater	
Concentration	8,8	mg/l
Type of value	PNEC	
Type	Saltwater	
Concentration	0,88	mg/l
Type of value	PNEC	
Type	saltwater sediment	
Concentration	3,46	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	463	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	2,33	mg/kg

#### **Triethylamine (neutralized form)**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,11	mg/l
Type of value	PNEC	
Type	marine water	
Concentration	0,011	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	1,575	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	0,25	mg/kg
Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Type of value	PNEC	
Conditions	sporadic release	
Concentration	0,08	mg/l

Type of value	PNEC	
Type	Marine sediment	
Concentration	0,158	mg/kg

**2-propenoic acid, reaction products with dipentaerythritol**

Type of value	PNEC	
Type	Freshwater	
Concentration	0,013	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,0013	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	2,8	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,28	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	10	mg/l

Type of value	PNEC	
Type	Soil	
Concentration	0,55	mg/kg

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Type of value	PNEC	
Type	marine water	
Concentration	3,39	µg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	0,23	mg/l

Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,027	mg/kg

Type of value	PNEC	
Type	Marine sediment	
Concentration	0,027	mg/kg

Type of value	PNEC	
---------------	------	--

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Type	Soil	
Concentration	0,01	mg/kg

Type of value	PNEC	
Type	Freshwater	
Concentration	3,39	µg/l

#### 1,2-benzisothiazol-3(2H)-one

Type of value	PNEC	
Type	Freshwater	
Concentration	4,03	µg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,403	µg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	1,03	mg/l

Type of value	PNEC	
Type	Freshwater sediment	
Concentration	0,0499	mg/kg

Type of value	PNEC	
Type	Marine sediment	
Concentration	0,00499	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	3	mg/kg

#### 2-methyl-2H-isothiazol-3-one

Type of value	PNEC	
Type	Freshwater	
Concentration	3,39	µg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	3,39	µg/l

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	023	mg/l

Type of value	PNEC	
Type	Soil	
Concentration	0,047	mg/kg

## 8.2. Exposure controls

### Exposure controls



Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Glove material

Appropriate Material	butyl-rubber
Material thickness	>= 0,5 mm
Breakthrough time	>= 120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** liquid

**Colour** coloured

**Odour** characteristic

#### Melting point

Remarks not determined

#### Freezing point

Remarks not determined

#### Boiling point or initial boiling point and boiling range

Value 100 to 173 °C

#### Flammability

not determined

#### Upper and lower explosive limits

Remarks not determined

#### Flash point

Value > 60 °C

#### Auto-ignition temperature

Remarks not determined

#### Decomposition temperature

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Remarks not determined

#### pH value

Value 8

Concentration/H<sub>2</sub>O 100

Remarks Not applicable

#### Viscosity

Remarks not determined

#### Solubility(ies)

Remarks not determined

#### Partition coefficient n-octanol/water (log value)

Remarks not determined

#### Vapour pressure

Remarks not determined

#### Density and/or relative density

Value appr. 1,082 kg/l

Temperature 20 °C

#### Relative vapour density

Remarks not determined

#### Particle characteristics

Remarks not determined

### 9.2. Other information

#### Odour threshold

Remarks not determined

#### Evaporation rate

Remarks not determined

#### Solubility in water

Remarks not determined

#### Efflux time

Value 25 to 35 s

Temperature 20 °C

Method DIN 53211 - 6 mm

#### Explosive properties

evaluation not determined

#### Oxidising properties

Remarks not determined

#### Non-volatile content

Value 38 %

Method calculated value

#### Other information

This information is not available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Stable under recommended storage and handling conditions (see section 7).

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

## 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

## 10.5. Incompatible materials

Keep away from free radical initiators, peroxides, strong alkalis or reactive metals.

## 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

# SECTION 11: Toxicological information

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute oral toxicity

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		

### Acute oral toxicity (Components)

#### 2-butoxyethanol

ATE	1200	mg/kg
-----	------	-------

#### Triethylamine (neutralized form)

ATE	100	mg/kg
Source	Annex VI Hazardous Substance	

#### 2-methyl-2H-isothiazol-3-one

Species	rat	
LD50	120	mg/kg
Method	EPA	
Source	1 (reliable without restriction)	

#### 1,2-benzisothiazol-3(2H)-one

Species	rat	
LD50	450	mg/kg
Source	Annex VI Hazardous Substance	

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

ATE	53	mg/kg
-----	----	-------

### Acute dermal toxicity

ATE	>	10.000	mg/kg
Method	calculated value (Regulation (EC) No. 1272/2008)		

### Acute dermal toxicity (Components)

#### Triethylamine (neutralized form)

ATE	300	mg/kg
Source	Annex VI Hazardous Substance	

#### 2-methyl-2H-isothiazol-3-one

Species	rat	
---------	-----	--

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

LD50 242 mg/kg

Source 1 (reliable without restriction)

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

ATE 50 mg/kg

Method conversion

#### Acute inhalational toxicity

ATE 15,7922 mg/l

Administration/Form Dust/Mist

Method calculated value (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

#### Acute inhalative toxicity (Components)

##### 2-butoxyethanol

ATE 3 mg/l

Duration of exposure 4 h

Administration/Form Vapors

Source Annex VI Hazardous Substance

##### Triethylamine (neutralized form)

ATE 7,2 mg/l

Duration of exposure 4 h

Administration/Form Vapors

Source Annex VI Hazardous Substance

##### 2-methyl-2H-isothiazol-3-one

Species rat

LC50 0,1 mg/l

Duration of exposure 4 h

Administration/Form Dust/Mist

Source 1 (reliable without restriction)

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

ATE 0,05 mg/l

Duration of exposure 4 h

Administration/Form Dust/Mist

Method conversion value

#### Skin corrosion/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)

Remarks Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation (Components)

##### 2-butoxyethanol

Species rabbit

Duration of exposure 4 h

Observation Period 28 d

evaluation Irritating to skin and mucous membranes

Method EEC 84/449, B.4

##### Triethylamine (neutralized form)

evaluation Causes burns.

##### 2-methyl-2H-isothiazol-3-one

evaluation Causes burns.

##### 1,2-benzisothiazol-3(2H)-one

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

evaluation Irritating to skin.

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Species rabbit  
evaluation Severe skin irritation

### Serious eye damage/irritation

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

### Serious eye damage/irritation (Components)

#### 2-butoxyethanol

Species rabbit  
Duration of exposure 24 h  
Observation Period 21 d  
evaluation Eye irritation  
Source 1 (reliable without restriction)

#### 2-methyl-2H-isothiazol-3-one

evaluation Causes severe caustic burns to skin and eyes.

#### 1,2-benzisothiazol-3(2H)-one

evaluation Irritating to eyes.

#### 2-propenoic acid, reaction products with dipentaerythritol

Species rabbit  
Observation Period 14 d  
evaluation Irritating to eyes.

### Sensitization

evaluation May cause sensitization by skin contact.  
Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks The classification criteria are met.

### Sensitization (Components)

#### phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species guinea pig  
Method OECD Test Guideline 406  
Remarks May cause sensitisation by skin contact.

#### 2-methyl-2H-isothiazol-3-one

evaluation May cause sensitization by skin contact.

#### 1,2-benzisothiazol-3(2H)-one

Reference substance 1,2-benzisothiazol-3(2H)-one  
evaluation May cause sensitization by skin contact.

**reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)**

Species guinea pig  
evaluation Causes sensitisation on guinea-pigs.

#### 2-propenoic acid, reaction products with dipentaerythritol

Species mouse  
evaluation May cause sensitization by skin contact.

### Mutagenicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

### Reproductive toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Carcinogenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

### Specific Target Organ Toxicity (STOT)

#### Single exposure

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

### Specific Target Organ Toxicity (STOT) (Components)

#### Triethylamine (neutralized form)

##### Specific target organ toxicity - single exposure

Remarks	Organs: Respiratory tract May cause respiratory irritation.
---------	--

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Other information

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

Species	Oncorhynchus mykiss (rainbow trout)
LC50	2,18 mg/l
Duration of exposure	96 h

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species	Oncorhynchus mykiss (rainbow trout)
LC50	0,19 mg/l
Duration of exposure	96 h

#### Daphnia toxicity (Components)

##### phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Species	Daphnia magna (Water flea)
EC50	10 to 100 mg/l

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Duration of exposure 48 h

#### 2-methyl-2H-isothiazol-3-one

Species Daphnia magna (Water flea)  
NOEC 0,044 mg/l  
Duration of exposure 21 d

#### 1,2-benzisothiazol-3(2H)-one

Species Daphnia magna (Water flea)  
EC50 2,94 mg/l  
Duration of exposure 48 h

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species Daphnia magna (Water flea)  
EC50 0,16 mg/l  
Duration of exposure 48 h

#### 2-propenoic acid, reaction products with dipentaerythritol

Species Daphnia magna (Water flea)  
EC50 18 mg/l  
Duration of exposure 48 h

### Algae toxicity (Components)

#### 2-methyl-2H-isothiazol-3-one

EC50 0,157 mg/l  
Duration of exposure 96 h

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species Scenedesmus capricornutum (fresh water algae)  
EC50 0,018 mg/l  
Duration of exposure 72 h

### Bacteria toxicity (Components)

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Species activated sludge  
EC50 4,5 mg/l

## 12.2. Persistence and degradability

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Biodegradability (Components)

#### phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Value 1 %  
Duration of test 28 d  
evaluation Not readily biodegradable.

#### 1,2-benzisothiazol-3(2H)-one

evaluation Not readily biodegradable.

#### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

evaluation Not readily biodegradable.

## 12.3. Bioaccumulative potential

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Partition coefficient n-octanol/water (log value)

Remarks not determined

### Octanol/water partition coefficient (log Pow) (Components)

#### Triethylamine (neutralized form)

log Pow to 1,45

#### 2-methyl-2H-isothiazol-3-one

log Pow -0,486  
Temperature 20 °C

## 12.4. Mobility in soil

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Mobility in soil

no data available

## 12.5. Results of PBT and vPvB assessment

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### Results of PBT and vPvB assessment

The product contains no PBT substances  
The product contains no vPvB substances.

## 12.6 Endocrine disrupting properties

### Endocrine disrupting properties with respect to the environment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## 12.7. Other adverse effects

### General information

For this subsection there is no ecotoxicological data available on the product as such.

### General information / ecology

For this subsection there is no ecotoxicological data available on the product as such.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

#### Disposal recommendations for packaging

Completely emptied packagings can be given for recycling.

## SECTION 14: Transport information



Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
<b>14.1. UN number</b>	Not classified as dangerous in the meaning of transport regulations.	Not classified as dangerous in the meaning of sea and air transport regulations.	Not a dangerous substance as defined in the above regulations.

## Information for all modes of transport

### 14.6. Special precautions for user

See Sections 6 to 8

## Other information

### 14.7. Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information \*\*\*

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU) 3 % 32 g/l

#### Restriction according to annex XVII to regulation (EU) No 1907/2006

The product is subject to restrictions according to Annex XVII Regulation (EU) No. 1907/2006: Entry No. 3.

#### Ingredients with restrictions according to Annex XVII Regulation (EU) No. 1907/2006 \*\*\*

##### 2-methyl-2H-isothiazol-3-one

Entry No. 75 (\*)

(\*) Conditions of restriction see Annex XVII Regulation (EU) No. 1907/2006 (REACH)

##### reaction mass of: 5-chloro-2- methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3- one [EC no. 220-239-6] (3:1)

Entry No. 75 (\*)

(\*) Conditions of restriction see Annex XVII Regulation (EU) No. 1907/2006 (REACH)

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

### CLP categories listed in Chapter 3

Acute Tox. 2	Acute toxicity, Category 2
Acute Tox. 3	Acute toxicity, Category 3
Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic, Category 4
Eye Dam. 1	Serious eye damage, Category 1
Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Skin Corr. 1A	Skin corrosion, Category 1A
Skin Corr. 1B	Skin corrosion, Category 1B
Skin Irrit. 2	Skin irritation, Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1A	Skin sensitization, Category 1A
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Changes since the last version are highlighted in the margin (\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES017 - Industrial applications: industrial spraying (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROC7	Industrial spraying

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

ERC4 Industrial use of processing aids in processes and products, not becoming part of articles

ERC5 Industrial use resulting in inclusion into or onto a matrix

**Physical form** liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 300

### **Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems ).

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter soil, waterways or waste water canal.

Dispose of rinse water in accordance with local and national regulations.

### **Waste water**

Do not discharge into the drains/surface waters/groundwater. Spray cabin waters are to be conducted after mechanical pretreatment into a wastewater treatment facility.

### **Exhaust air**

Keep container closed. Avoid release to the environment.

### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

### **Disposal recommendations for the product**

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

### **Disposal recommendations for packaging**

Completely emptied packagings can be given for recycling.

## **Contributing exposure scenario controlling worker exposure**

### **Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

PROC7 Industrial spraying

**Physical form** liquid

### **Maximum amount used per time or activity**

Duration of exposure <= 8 h/d

Frequency of exposure <= 220 d/a

### **Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Curing takes place through UV light exposure (only with UV light curing systems ).

Read attached instructions before use.

### **Product substance and product safety related measures**

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Glove material  
Appropriate Material butyl-rubber  
Material thickness  $\geq$  0,5  
Breakthrough time  $\geq$  120

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	inhalation, long-term - systemic
Exposure assessment	42 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,428571
Lead substance	2-butoxyethanol

### Workers (industrial)

PROC	PROC7
Assessment method	dermal, long-term - systemic
Exposure assessment	8,5714 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,068571
Lead substance	2-butoxyethanol

### Workers (industrial)

PROC	PROC10
Assessment method	inhalation, long-term - systemic
Exposure assessment	55 mg/m <sup>3</sup>
Exposure assessment (method)	EASY TRA v3.5
Risk characterisation ratio (RCR)	0,561224
Lead substance	2-butoxyethanol

### Workers (industrial)

PROC	PROC10
Assessment method	dermal, long-term - systemic

Trade name: Hesse FABULAC , silk matt PEX HUB 85555-F

Version: 23 / ZA

Revision: 01.12.2025

Replaces Version: 22 / ZA

Print date: 01.12.25

Exposure assessment	5,4857 mg/kg/d
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,043886
Lead substance	2-butoxyethanol

**Workers (industrial)**

PROC	PROC13
Assessment method	inhalation, long-term - systemic
Exposure assessment	49,2393 mg/m <sup>3</sup>
Exposure assessment (method)	ESIG GES tool
Risk characterisation ratio (RCR)	0,502441
Lead substance	2-butoxyethanol

**Workers (industrial)**

PROC	PROC13
Assessment method	dermal, long-term - systemic
Exposure assessment	2,7429 mg/kg/d
Exposure assessment (method)	EASY TRA v3.5
Risk characterisation ratio (RCR)	0,021943
Lead substance	2-butoxyethanol

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.