

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse PU TINT-AID PEX LPM 10-FT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	REACHSET 1003
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3	H226
STOT SE 3	H336
Aquatic Chronic 3	H412

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

#### Hazard pictograms



Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

## Signal word

Warning

## Hazard statements

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

## Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P308+P313 IF exposed or concerned: Get medical advice/ attention.

## Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains n-butyl acetate; Hydrocarbons, C9, aromatics; 2-methoxy-1-methylethyl acetate

## Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients

### Hazardous ingredients

#### n-butyl acetate

CAS No.	123-86-4			
EINECS no.	204-658-1			
Registration no.	01-2119485493-29			
Concentration	>= 25	< 50	%	
Classification (Regulation (EC) No. 1272/2008)	Flam. Liq. 3	H226		
	STOT SE 3	H336		Nervous system
		EUH066		

#### Hydrocarbons, C9, aromatics

CAS No.	128601-23-0			
EINECS no.	918-668-5			
Registration no.	01-2119455851-35			
Concentration	>= 3	< 10	%	
Classification (Regulation (EC) No. 1272/2008)	Flam. Liq. 3	H226		
	Asp. Tox. 1	H304		
	Aquatic Chronic 2	H411		
	STOT SE 3	H335		Respiratory tract
	STOT SE 3	H336		Nervous system
		EUH066		

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

**2-methoxy-1-methylethyl acetate**

CAS No. 108-65-6

EINECS no. 203-603-9

Registration no. 01-2119475791-29

Concentration  $\geq 1$  < 10 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226

STOT SE 3 H336

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

If unconscious place in recovery position and seek medical advice. In all cases of doubt, or when symptoms persist, seek medical attention. First aider: Pay attention to self-protection! Remove affected person from danger area, lay him down.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep warm, calm and covered up. In all cases of doubt, or when symptoms persist, seek medical attention.

#### After skin contact

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

#### After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

#### After ingestion

Do not induce vomiting. Take medical treatment.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

#### Non suitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced.

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Exposure to decomposition products may cause a health hazard. Vapours can form an explosive mixture with air.

### **5.3. Advice for firefighters**

#### **Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

#### **Other information**

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses. Standard procedure for chemical fires.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Do not inhale vapours. Do not inhale gases. Do not inhale mist.

### **6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

### **6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 7 and 8.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

#### **Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### **Advice on protection against fire and explosion**

Vapours can form an explosive mixture with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Fight fire with normal precautions from a reasonable distance.

### **7.2. Conditions for safe storage, including any incompatibilities**

#### **Requirements for storage rooms and vessels**

Provide solvent-resistant and impermeable floor. Keep only in the original container in a cool, well

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

### Storage classes

Storage class according to TRGS 510      3      Flammable liquid

### Further information on storage conditions

Protect from frost. Protect from heat and direct sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limit values

##### n-butyl acetate

List	OEL (ZA)		
Value		100	ppm(V)
Short term exposure limit		300	ppm(V)
Status: 03/2021			

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### 2-methoxy-1-methylethyl acetate

Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	275	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	153,5	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	1,67	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Concentration 33 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure Dermal exposure

Mode of action Systemic effects

Concentration 54,8 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Acute

Route of exposure inhalative

Mode of action Local effects

Concentration 550 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long term

Route of exposure inhalative

Mode of action Local effects

Concentration 33 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Acute

Route of exposure inhalative

Mode of action Local effects

Concentration 33 mg/m<sup>3</sup>

**n-butyl acetate**

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure Long-term

Route of exposure Dermal exposure

Mode of action Systemic effects

Concentration 11 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure Short-term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 600 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure Short-term

Route of exposure inhalative

Mode of action Local effects

Concentration 600 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	Systemic effects	
Concentration	6	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	Systemic effects	
Concentration	2	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short-term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	300	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	35,7	mg/m <sup>3</sup>
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Local effects	





Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Concentration 35,7 mg/m<sup>3</sup>

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short term

Route of exposure oral

Mode of action Specific effects

Concentration 2 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Short term

Route of exposure Dermal exposure

Mode of action Specific effects

Concentration 6 mg/kg/d

Type of value Derived No Effect Level (DNEL)

Reference group Worker

Duration of exposure Short term

Route of exposure Dermal exposure

Mode of action Specific effects

Concentration 11 mg/kg/d

#### **Hydrocarbons, C9, aromatics**

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure Oral exposure

Mode of action Systemic effects

Concentration 11 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure Long-term

Route of exposure Dermal exposure

Mode of action Systemic effects

Concentration 25 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Consumer

Duration of exposure Long-term

Route of exposure Dermal exposure

Mode of action Systemic effects

Concentration 11 mg/kg

Type of value Derived No Effect Level (DNEL)

Reference group Workers (professional)

Duration of exposure Long-term

Route of exposure inhalative

Mode of action Systemic effects

Concentration 150 mg/kg

Type of value Derived No Effect Level (DNEL)



Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Reference group	Consumer	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	32	mg/kg

Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	11	mg/kg

### Predicted No Effect Concentration (PNEC)

#### 2-methoxy-1-methylethyl acetate

Type of value	PNEC	
Type	Freshwater	
Concentration	0,635	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,0635	mg/l

Type of value	PNEC	
Conditions	sporadic release	
Concentration	6,35	mg/l

Type of value	PNEC	
Type	Fresh water sediment	
Concentration	3,29	mg/kg

Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,329	mg/kg

Type of value	PNEC	
Type	Soil	
Concentration	0,29	mg/kg

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	100	mg/l

#### n-butyl acetate

Type of value	PNEC	
Type	Freshwater	
Concentration	0,18	mg/l

Type of value	PNEC	
Type	Saltwater	
Concentration	0,018	mg/l

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Type of value	PNEC	
Type	Sewage treatment plant (STP)	
Concentration	35,6	mg/l
Type of value	PNEC	
Type	Water	
Conditions	sporadic release	
Concentration	0,36	mg/l
Type of value	PNEC	
Type	Fresh water sediment	
Concentration	0,981	mg/kg
Type of value	PNEC	
Type	saltwater sediment	
Concentration	0,0981	mg/l
Type of value	PNEC	
Type	Soil	
Concentration	0,0903	mg/kg

## 8.2. Exposure controls

### Exposure controls

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol. Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7 mm

Breakthrough time  $\geq$  30 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	liquid
<b>Colour</b>	coloured
<b>Odour</b>	solvent-like
<b>Melting point</b>	
Remarks	not determined
<b>Freezing point</b>	
Remarks	not determined
<b>Boiling point or initial boiling point and boiling range</b>	
Value	114 to 214 °C
<b>Flammability</b>	
Remarks	not determined
<b>Upper and lower explosive limits</b>	
Remarks	not determined
<b>Flash point</b>	
Value	25,0 °C
<b>Auto-ignition temperature</b>	
Remarks	not determined
<b>Decomposition temperature</b>	
Remarks	not determined
<b>pH value</b>	
Remarks	Not applicable
<b>Viscosity</b>	
Remarks	not determined
<b>Solubility(ies)</b>	
Remarks	not determined
<b>Partition coefficient n-octanol/water (log value)</b>	
Remarks	not determined
<b>Vapour pressure</b>	
Remarks	not determined
<b>Density and/or relative density</b>	
Value	appr. 1,12 kg/l
Temperature	20 °C
<b>Relative vapour density</b>	
Remarks	not determined
<b>Particle characteristics</b>	
Remarks	not determined
<b>9.2. Other information</b>	
<b>Odour threshold</b>	
Remarks	not determined

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

#### Evaporation rate

Remarks not determined

#### Solubility in water

Remarks not determined

#### Efflux time

Value 27 to 63 s  
Temperature 20 °C  
Method DIN 53211 4 mm

#### Explosive properties

evaluation not determined

#### Oxidising properties

Remarks not determined

#### Non-volatile content

Value 34 %

#### Other information

This information is not available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

#### 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

#### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute oral toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

##### Acute dermal toxicity

Method Calculation method (Regulation (EC) No. 1272/2008)  
Remarks Based on available data, the classification criteria are not met.

##### Acute inhalational toxicity

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Sensitization

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Mutagenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Carcinogenicity

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity (STOT)

##### Single exposure

Method	Calculation method (Regulation (EC) No. 1272/2008)
Remarks	The classification criteria are met.
evaluation	May cause drowsiness or dizziness.

##### Repeated exposure

Remarks	Based on available data, the classification criteria are not met.
---------	---

#### Specific Target Organ Toxicity (STOT) (Components)

##### n-butyl acetate

##### Specific target organ toxicity - repeated exposure

Remarks	Organs: Nervous system Possible narcotic effects (drowsiness, dizziness).
---------	--

##### Hydrocarbons, C9, aromatics

##### Specific target organ toxicity - single exposure

Remarks	Route of exposure inhalative Possible narcotic effects (drowsiness, dizziness).
---------	--

##### Hydrocarbons, C9, aromatics

##### Specific target organ toxicity - single exposure

Remarks	Possible narcotic effects (drowsiness, dizziness).
---------	--

##### 2-methoxy-1-methylethyl acetate

##### Specific target organ toxicity - repeated exposure

evaluation	May cause drowsiness or dizziness. Organs: Nervous system
------------	--

#### Aspiration hazard

Based on available data, the classification criteria are not met.

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

## 11.2. Information on other hazards

### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

### Other information

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### Hydrocarbons, C9, aromatics

Species	Oncorhynchus mykiss (rainbow trout)	
LC50	9,2	mg/l
Duration of exposure	96	h

#### Daphnia toxicity (Components)

##### Hydrocarbons, C9, aromatics

Species	Daphnia magna (Water flea)	
EC50	3,2	mg/l
Duration of exposure	48	h

##### Hydrocarbons, C9, aromatics

Species	Daphnia magna (Water flea)	
NOEC	2,14	mg/l
Duration of exposure	21	d

#### Algae toxicity (Components)

##### Hydrocarbons, C9, aromatics

Species	Pseudokirchneriella subcapitata (green algae)	
EC50	2,6 to 2,9	mg/l
Duration of exposure	72	h

### 12.2. Persistence and degradability

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Biodegradability (Components)

##### Hydrocarbons, C9, aromatics

evaluation	Readily biodegradable.
------------	------------------------

### 12.3. Bioaccumulative potential

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Partition coefficient n-octanol/water (log value)

Remarks	not determined
---------	----------------

### 12.4. Mobility in soil

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

### **Mobility in soil**

no data available

## **12.5. Results of PBT and vPvB assessment**

### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

### **Results of PBT and vPvB assessment**

The product contains no PBT substances

The product contains no vPvB substances.

## **12.6 Endocrine disrupting properties**

### **Endocrine disrupting properties with respect to the environment**

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## **12.7. Other adverse effects**

### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

### **General information / ecology**

For this subsection there is no ecotoxicological data available on the product as such.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Disposal recommendations for the product**

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### **Disposal recommendations for packaging**

Completely emptied packagings can be given for recycling.

## **SECTION 14: Transport information**






Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
Tunnel restriction code	D/E		
14.1. UN number	1263	1263	1263
14.2. UN proper shipping name	PAINT	PAINT	PAINT
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	III	III	III
Limited Quantity	5 l		
Transport category	3		
14.5. Environmental hazards	-		

## Information for all modes of transport

### 14.6. Special precautions for user

See Sections 6 to 8

## Other information

### 14.7. Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Major-accident categories acc. 2012/18/EU

Category P5c FLAMMABLE LIQUID 5.000.000 kg 50.000.000 kg

#### VOC

VOC (EU) 66 % 661 g/l

#### Restriction according to annex XVII to regulation (EU) No 1907/2006

The product is subject to restrictions according to Annex XVII Regulation (EU) No. 1907/2006: Entry No. 3.

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

## 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

### CLP categories listed in Chapter 3

Aquatic Chronic 2	Hazardous to the aquatic environment, chronic, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 3	Flammable liquid, Category 3
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

Changes since the last version are highlighted in the margin (\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

## Annex to the extended Safety Data Sheet (eSDS)

### Short title of the exposure scenario

ES002 - Industrial applications: rolling, dipping, pouring and other processing without aerosol formation (inside)

### Use of the substance/preparation

Surface treatment of wood and other materials

### Use

SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
ERC5	Industrial use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROCh02	roller coating industrial
PROC13	Treatment of articles by dipping and pouring

## Contributing exposure scenario controlling environmental exposure

### Use

ERC4	Industrial use of processing aids in processes and products, not becoming part of articles
------	--

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

ERC5 Industrial use resulting in inclusion into or onto a matrix

**Physical form** liquid

**Maximum amount used per time or activity**

Emission days per site: <= 300

**Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter soil, waterways or waste water canal.

Dispose of rinse water in accordance with local and national regulations.

**Waste water**

Do not discharge into the drains/surface waters/groundwater.

**Exhaust air**

Keep container closed. Avoid release to the environment.

**Soil**

Floors should be impervious, resistant to liquids and easy to clean.

**Disposal recommendations for the product**

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

**Disposal recommendations for packaging**

Completely emptied packagings can be given for recycling.

**Contributing exposure scenario controlling worker exposure**

**Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

PROCh01 Other processing without aerosol formation

PROCh02 roller coating industrial

PROC13 Treatment of articles by dipping and pouring

**Physical form** liquid

**Maximum amount used per time or activity**

Duration of exposure <= 8 h/d

Frequency of exposure <= 220 d/a

**Other relevant operational conditions**

Use: Room temperature

Drying and through-curing takes place at ambient temperature or at higher temperatures.

Read attached instructions before use.

**Product substance and product safety related measures**

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.

Recommended Filter type: Respiratory protection mask with combination filter A/P2

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

## Hand protection

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

Material thickness  $\geq$  0,7

Breakthrough time  $\geq$  30

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

## Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## Exposure estimation and reference to its source

### Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	27,54 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,1
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC7
Assessment method	dermal, long-term - local and systemic
Exposure assessment	2,14 mg/kg/d
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,01
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	inhalation, long-term - local and systemic
Exposure assessment	55,08 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,2
Lead substance	2-methoxy-1-methylethyl acetate

### Workers (industrial)

SU	SU3
PROC	PROC10
Assessment method	dermal, long-term - local and systemic
Exposure assessment	27,43 mg/kg/d
Exposure assessment (method)	ECETOC TRA

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

Risk characterisation ratio (RCR)

0,18

Lead substance

2-methoxy-1-methylethyl acetate

**Workers (industrial)**

SU

SU3

PROC

PROC13

Assessment method

inhalation, long-term - local and systemic

Exposure assessment

55,08 mg/m<sup>3</sup>

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,2

Lead substance

2-methoxy-1-methylethyl acetate

**Workers (industrial)**

SU

SU3

PROC

PROC13

Assessment method

dermal, long-term - local and systemic

Exposure assessment

13,71 mg/kg/d

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,09

Lead substance

2-methoxy-1-methylethyl acetate

**Workers (industrial)**

PROC

PROC7

Assessment method

inhalation, long-term - local and systemic

Exposure assessment

60,5 mg/m<sup>3</sup>

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,126

Lead substance

n-butyl acetate

**Workers (industrial)**

PROC

PROC10

Assessment method

inhalation, long-term - systemic

Exposure assessment

242 mg/m<sup>3</sup>

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,504

Lead substance

n-butyl acetate

**Workers (industrial)**

PROC

PROC10

Assessment method

inhalation, long-term - systemic

Exposure assessment

242 mg/m<sup>3</sup>

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,504

Lead substance

n-butyl acetate

**Workers (industrial)**

PROC

PROC13

Assessment method

inhalation, long-term - systemic

Exposure assessment

242 mg/m<sup>3</sup>

Exposure assessment (method)

ECETOC TRA

Risk characterisation ratio (RCR)

0,504

Lead substance

n-butyl acetate

Trade name: Hesse PU TINT-AID PEX LPM 10-FT

Version: 14 / ZA

Revision: 30.03.2025

Replaces Version: 13 / ZA

Print date: 01.12.25

#### **Workers (industrial)**

PROC	PROC13
Assessment method	inhalation, long-term - systemic
	Outdoor use
Exposure assessment	242 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,504
Lead substance	n-butyl acetate

#### **Workers (industrial)**

SU	SU3
PROC	PROC7
Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene

#### **Workers (industrial)**

SU	SU3
PROC	PROC10
Assessment method	inhalative
	Indoor use
Exposure assessment	0,05 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,172
Lead substance	xylene

#### **Workers (industrial)**

SU	SU3
PROC	PROC13
Assessment method	inhalative
	Indoor use
Exposure assessment	0,1 mg/m <sup>3</sup>
Exposure assessment (method)	ECETOC TRA
Risk characterisation ratio (RCR)	0,34
Lead substance	xylene

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.