



Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Hesse PORECOLOR PEX TPC 800-FT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

|        |  |
|--------|--|
|        | REACHSET 1000  |
| SU3    | Industrial uses: Uses of substances as such or in preparations at industrial sites               |
| ERC4   | Industrial use of processing aids in processes and products, not becoming part of articles       |
| ERC5   | Industrial use resulting in inclusion into or onto a matrix                                      |
| PROC7  | Industrial spraying  |
|        | REACHSET 2001  |
| SU22   | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a  | Wide dispersive indoor use of processing aids in open systems                                    |
| ERC8c  | Wide dispersive indoor use resulting in inclusion into or onto a matrix                          |
| PROC11 | Non industrial spraying  |

### 1.3. Details of the supplier of the safety data sheet

#### Manufacturer

Hesse GmbH & Co. KG  
Warendorfer Strasse 21  
59075 Hamm (Germany)  
Telephone no. +49 (0) 2381 963-00  
Fax no. +49 (0) 2381 963-849  
E-mail address ps@hesse-lignal.de

### 1.4. Emergency telephone number

Germany: +49 (0) 2381 788-612

## SECTION 2: Hazards identification \*\*\*

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)  
Skin Sens. 1 H317

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

### Hazard pictograms \*\*\*



### Signal word \*\*\*

Warning

### Hazard statements \*\*\*

H317 May cause an allergic skin reaction.

### Precautionary statements \*\*\*

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.  
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 Take off contaminated clothing and wash it before reuse.

### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains \*\*\* 1,2-benzisothiazol-3(2H)-one

## 2.3. Other hazards

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

## SECTION 3: Composition/information on ingredients \*\*\*

### Hazardous ingredients \*\*\*

#### 1,2-benzisothiazol-3(2H)-one

|  |                  |
|--|------------------|
| CAS No.  | 2634-33-5        |
| EINECS no.                                     | 220-120-9        |
| Registration no.                               | 01-2120761540-60 |
| Concentration                                  | >= 0,036 < 0,1 % |
| Classification (Regulation (EC) No. 1272/2008) |                  |
| Acute Tox. 4                                   | H302             |
| Skin Irrit. 2                                  | H315             |
| Eye Dam. 1                                     | H318             |
| Skin Sens. 1                                   | H317             |
| Aquatic Acute 1                                | H400             |
| Aquatic Chronic 1                              | H410             |
| Acute Tox. 2                                   | H330             |

Concentration limits (Regulation (EC) No. 1272/2008)

Skin Sens. 1 H317 >= 0,036 %

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

Remove affected person from danger area, lay him down. In all cases of doubt, or when symptoms persist, seek medical attention. Get medical advice/attention if you feel unwell. First aider: Pay attention to self-protection!

**After inhalation**

When spray fog inhaled, seek medical aid.

**After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners. Consult a doctor if skin irritation persists.

**After eye contact**

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice. Take medical treatment.

**After ingestion**

Do not induce vomiting. Take medical treatment.

**4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Hints for the physician / treatment**

Treat symptomatically.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Recommended: alcohol resistant foam, CO<sub>2</sub>, powders, water spray/mist

**Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

**5.2. Special hazards arising from the substance or mixture**

Fire will produce dense black smoke. In a fire, hazardous decomposition products may be produced. Exposure to decomposition products may cause a health hazard.

**5.3. Advice for firefighters**

**Special protective equipment for fire-fighting**

In case of combustion evolution of dangerous gases possible. Use self-contained breathing apparatus.

**Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water. Standard procedure for chemical fires.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Do not inhale vapours. Do not inhale gases. Do not inhale mist.

**6.2. Environmental precautions**

Do not allow to enter drains or waterways. Do not allow to enter soil, waterways or waste water canal. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Do NOT use solvents or thinners. Send in suitable containers for recovery or disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 7 and 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed and dry in a cool, well-ventilated place. Avoid contact with skin and eyes. Avoid inhalation of vapour and spray mist. Do not eat, drink or smoke when using this product. Use personal protective clothing. For personal protection see Section 8.

#### Advice on protection against fire and explosion

Fight fire with normal precautions from a reasonable distance.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage stability

Protect from frost.

#### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Storage classes

Storage class according to TRGS 510      10      Flammable liquids

#### Further information on storage conditions

Keep away from heat. Protect from sunlight. Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### 1,2-benzisothiazol-3(2H)-one

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Worker                         |                   |
| Duration of exposure | Long term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 6,81                           | mg/m <sup>3</sup> |

|               |                                |
|---------------|--------------------------------|
| Type of value | Derived No Effect Level (DNEL) |
|---------------|--------------------------------|



Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

|                      |                  |       |
|----------------------|------------------|-------|
| Reference group      | Worker           |       |
| Duration of exposure | Long term        |       |
| Route of exposure    | dermal           |       |
| Mode of action       | Systemic effects |       |
| Concentration        | 0,966            | mg/kg |

|                      |                                |                   |
|----------------------|--------------------------------|-------------------|
| Type of value        | Derived No Effect Level (DNEL) |                   |
| Reference group      | Consumer                       |                   |
| Duration of exposure | Long term                      |                   |
| Route of exposure    | inhalative                     |                   |
| Mode of action       | Systemic effects               |                   |
| Concentration        | 1,2                            | mg/m <sup>3</sup> |

|                      |                                |       |
|----------------------|--------------------------------|-------|
| Type of value        | Derived No Effect Level (DNEL) |       |
| Reference group      | Consumer                       |       |
| Duration of exposure | Long term                      |       |
| Route of exposure    | dermal                         |       |
| Mode of action       | Systemic effects               |       |
| Concentration        | 0,345                          | mg/kg |

### **Predicted No Effect Concentration (PNEC)**

#### **1,2-benzisothiazol-3(2H)-one**

|               |            |      |
|---------------|------------|------|
| Type of value | PNEC       |      |
| Type          | Freshwater |      |
| Concentration | 4,03       | µg/l |

|               |           |      |
|---------------|-----------|------|
| Type of value | PNEC      |      |
| Type          | Saltwater |      |
| Concentration | 0,403     | µg/l |

|               |                              |      |
|---------------|------------------------------|------|
| Type of value | PNEC                         |      |
| Type          | Sewage treatment plant (STP) |      |
| Concentration | 1,03                         | mg/l |

|               |                     |       |
|---------------|---------------------|-------|
| Type of value | PNEC                |       |
| Type          | Freshwater sediment |       |
| Concentration | 0,0499              | mg/kg |

|               |                 |       |
|---------------|-----------------|-------|
| Type of value | PNEC            |       |
| Type          | Marine sediment |       |
| Concentration | 0,00499         | mg/kg |

|               |      |       |
|---------------|------|-------|
| Type of value | PNEC |       |
| Type          | Soil |       |
| Concentration | 3    | mg/kg |

## **8.2. Exposure controls**

### **Exposure controls**

Users are advised to consider national Occupational Exposure Limits or other equivalent values. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

### Hand protection

Glove material  
Appropriate Material butyl-rubber  
Material thickness  $\geq$  0,5 mm  
Breakthrough time  $\geq$  120 min

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|   |                |
|---|----------------|
| <b>Physical state</b>   | liquid         |
| <b>Colour</b>   | colourless     |
| <b>Odour</b>  | characteristic |
| <b>Melting point</b>  |                |
| Remarks   | not determined |
| <b>Freezing point</b>   |                |
| Remarks   | not determined |
| <b>Boiling point or initial boiling point and boiling range</b> |                |
| Value   | 100 to 184 °C  |
| <b>Flammability</b>   |                |
| not determined  |                |
| <b>Upper and lower explosive limits</b>                         |                |
| Remarks   | not determined |
| <b>Flash point</b>  |                |
| Value   | $>$ 60 °C      |
| <b>Auto-ignition temperature</b>                                |                |
| Remarks   | not determined |
| <b>Decomposition temperature</b>                                |                |
| Remarks   | not determined |

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

#### pH value

|                                |                |
|--------------------------------|----------------|
| Value                          | 7,5            |
| Concentration/H <sub>2</sub> O | 100            |
| Remarks                        | Not applicable |

#### Viscosity

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Solubility(ies)

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Partition coefficient n-octanol/water (log value)

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Vapour pressure

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Density and/or relative density

|             |             |    |      |
|-------------|-------------|----|------|
| Value       | appr. 1,074 |    | kg/l |
| Temperature | 20          | °C |      |

#### Relative vapour density

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Particle characteristics

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

### 9.2. Other information

#### Odour threshold

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Solubility in water

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Efflux time

|             |                        |    |     |   |
|-------------|------------------------|----|-----|---|
| Value       | 20                     | to | 100 | s |
| Temperature | 20                     | °C |     |   |
| Method      | DIN EN ISO 2431 - 3 mm |    |     |   |

#### Explosive properties

|            |                |
|------------|----------------|
| evaluation | not determined |
|------------|----------------|

#### Oxidising properties

|         |                |
|---------|----------------|
| Remarks | not determined |
|---------|----------------|

#### Non-volatile content

|        |                  |   |
|--------|------------------|---|
| Value  | 19,8             | % |
| Method | calculated value |   |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under recommended storage and handling conditions (see section 7).

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

To avoid thermal decomposition, do not overheat.

#### 10.4. Conditions to avoid

Isolate from sources of heat, sparks and open flame.

#### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide, nitrous oxides (NO<sub>x</sub>), dense black smoke, No decomposition if used as prescribed.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute oral toxicity

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

##### Acute oral toxicity (Components)

###### 1,2-benzisothiazol-3(2H)-one

|         |                              |       |
|---------|------------------------------|-------|
| Species | rat                          |       |
| LD50    | 450                          | mg/kg |
| Source  | Annex VI Hazardous Substance |       |

##### Acute dermal toxicity

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

##### Acute inhalational toxicity

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

##### Skin corrosion/irritation

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

##### Skin corrosion/irritation (Components)

###### 1,2-benzisothiazol-3(2H)-one

|            |                     |
|------------|---------------------|
| evaluation | Irritating to skin. |
|------------|---------------------|

##### Serious eye damage/irritation

|         |   |
|---------|---|
| Method  | Calculation method (Regulation (EC) No. 1272/2008)                |
| Remarks | Based on available data, the classification criteria are not met. |

##### Serious eye damage/irritation (Components)

###### 1,2-benzisothiazol-3(2H)-one

|            |                     |
|------------|---------------------|
| evaluation | Irritating to eyes. |
|------------|---------------------|

##### Sensitization

|            |  |
|------------|--|
| evaluation | May cause sensitization by skin contact.           |
| Method     | Calculation method (Regulation (EC) No. 1272/2008) |
| Remarks    | The classification criteria are met.               |

##### Sensitization (Components)

###### 1,2-benzisothiazol-3(2H)-one



Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

Reference substance evaluation      1,2-benzisothiazol-3(2H)-one  
May cause sensitization by skin contact.

#### Mutagenicity

Method      Calculation method (Regulation (EC) No. 1272/2008)  
Remarks      Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Method      Calculation method (Regulation (EC) No. 1272/2008)  
Remarks      Based on available data, the classification criteria are not met.

#### Carcinogenicity

Method      Calculation method (Regulation (EC) No. 1272/2008)  
Remarks      Based on available data, the classification criteria are not met.

#### Specific Target Organ Toxicity (STOT)

**Single exposure**  
Method      Calculation method (Regulation (EC) No. 1272/2008)  
Remarks      Based on available data, the classification criteria are not met.

**Repeated exposure**  
Remarks      Based on available data, the classification criteria are not met.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties with respect to humans

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

#### Other information

No toxicological data are available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

#### Fish toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

|                      |                                     |      |
|----------------------|-------------------------------------|------|
| Species              | Oncorhynchus mykiss (rainbow trout) |      |
| LC50                 | 2,18                                | mg/l |
| Duration of exposure | 96                                  | h    |

#### Daphnia toxicity (Components)

##### 1,2-benzisothiazol-3(2H)-one

|                      |                            |      |
|----------------------|----------------------------|------|
| Species              | Daphnia magna (Water flea) |      |
| EC50                 | 2,94                       | mg/l |
| Duration of exposure | 48                         | h    |

### 12.2. Persistence and degradability

#### General information

For this subsection there is no ecotoxicological data available on the product as such.

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

### **Biodegradability (Components)**

#### **1,2-benzisothiazol-3(2H)-one**

evaluation

Not readily biodegradable.

### **12.3. Bioaccumulative potential**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Partition coefficient n-octanol/water (log value)**

Remarks

not determined

### **12.4. Mobility in soil**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Mobility in soil**

no data available

### **12.5. Results of PBT and vPvB assessment**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

#### **Results of PBT and vPvB assessment**

The product contains no PBT substances

The product contains no vPvB substances.

### **12.6 Endocrine disrupting properties**

#### **Endocrine disrupting properties with respect to the environment**

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

### **12.7. Other adverse effects**

#### **General information**

For this subsection there is no ecotoxicological data available on the product as such.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

#### **Disposal recommendations for the product**

Where possible recycling is preferred to disposal or incineration.

Do not allow to enter drains or waterways.

#### **Disposal recommendations for packaging**

Completely emptied packagings can be given for recycling.

## **SECTION 14: Transport information**

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

|                        | Land transport ADR/RID   | Marine transport IMDG/GGVSee   | Air transport ICAO/IATA  |
|------------------------|--|--|--|
| <b>14.1. UN number</b> | Not classified as dangerous in the meaning of transport regulations. | Not classified as dangerous in the meaning of sea and air transport regulations. | Not a dangerous substance as defined in the above regulations. |

## Information for all modes of transport

### 14.6. Special precautions for user

See Sections 6 to 8

## Other information

### 14.7. Maritime transport in bulk according to IMO instruments

Not relevant

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU) 0,2 % 3 g/l

#### Restriction according to annex XVII to regulation (EU) No 1907/2006

The product is subject to restrictions according to Annex XVII Regulation (EU) No. 1907/2006: Entry No. 3.

## SECTION 16: Other information

### Hazard statements listed in Chapter 3

|      |   |
|------|---|
| H302 | Harmful if swallowed.                                 |
| H315 | Causes skin irritation.                               |
| H317 | May cause an allergic skin reaction.                  |
| H318 | Causes serious eye damage.                            |
| H330 | Fatal if inhaled.                                     |
| H400 | Very toxic to aquatic life.                           |
| H410 | Very toxic to aquatic life with long lasting effects. |

### CLP categories listed in Chapter 3

|                   |   |
|-------------------|---|
| Acute Tox. 2      | Acute toxicity, Category 2                                |
| Acute Tox. 4      | Acute toxicity, Category 4                                |
| Aquatic Acute 1   | Hazardous to the aquatic environment, acute, Category 1   |
| Aquatic Chronic 1 | Hazardous to the aquatic environment, chronic, Category 1 |
| Eye Dam. 1        | Serious eye damage, Category 1                            |
| Skin Irrit. 2     | Skin irritation, Category 2                               |
| Skin Sens. 1      | Skin sensitization, Category 1                            |

Changes since the last version are highlighted in the margin (\*\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information

Print date: 01.12.25

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

Completely emptied packagings can be given for recycling.

## **Contributing exposure scenario controlling worker exposure**

### **Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
PROC7 Industrial spraying

### **Physical form**

liquid

### **Maximum amount used per time or activity**

|                       |    |     |     |
|-----------------------|----|-----|-----|
| Duration of exposure  | <= | 8   | h/d |
| Frequency of exposure | <= | 220 | d/a |

### **Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Curing takes place through UV light exposure (only with UV light curing systems ).  
Read attached instructions before use.

### **Product substance and product safety related measures**

Mainly used in closed systems. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### **Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

### **Hand protection**

|                      |              |
|----------------------|--------------|
| Glove material       |              |
| Appropriate Material | butyl-rubber |
| Material thickness   | >= 0,5       |
| Breakthrough time    | >= 120       |

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

### **Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES019 - Professional uses: Non industrial spraying (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

|        |  |
|--------|--|
| SU22   | Professional uses: Public domain (administration, education, entertainment, services, craftsmen) |
| ERC8a  | Wide dispersive indoor use of processing aids in open systems                                    |
| ERC8c  | Wide dispersive indoor use resulting in inclusion into or onto a matrix                          |
| PROC11 | Non industrial spraying  |

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

|       |   |
|-------|---|
| ERC8a | Wide dispersive indoor use of processing aids in open systems           |
| ERC8c | Wide dispersive indoor use resulting in inclusion into or onto a matrix |

### **Physical form**

liquid

### **Maximum amount used per time or activity**

Emission days per site: <= 250

### **Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Curing takes place through UV light exposure (only with UV light curing systems ).  
Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter soil, waterways or waste water canal.  
Dispose of rinse water in accordance with local and national regulations.

### **Waste water**

Do not discharge into the drains/surface waters/groundwater.

### **Exhaust air**

Keep container closed. Avoid release to the environment.

### **Soil**

Floors should be impervious, resistant to liquids and easy to clean.

### **Disposal recommendations for the product**

Where possible recycling is preferred to disposal or incineration.  
Do not allow to enter drains or waterways.

### **Disposal recommendations for packaging**

Completely emptied packagings can be given for recycling.

## **Contributing exposure scenario controlling worker exposure (professional)**

### **Short title of the exposure scenario**

Substance number:CES038

### **Use**

|      |   |
|------|---|
| SU22 | Professional uses: Public domain (administration, education, entertainment, |
|------|---|

Trade name: Hesse PORECOLOR PEX TPC 800-FT

Version: 3 / ZA

Revision: 22.10.2025

Replaces Version: 2 / ZA

Print date: 01.12.25

PROC11 services, craftsmen)  
Non industrial spraying  
**Physical form** liquid  
**Maximum amount used per time or activity**

|                       |    |     |     |
|-----------------------|----|-----|-----|
| Duration of exposure  | <= | 8   | h/d |
| Frequency of exposure | <= | 220 | d/a |

**Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Curing takes place through UV light exposure (only with UV light curing systems ).  
Read attached instructions before use.

**Product substance and product safety related measures**

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

**Respiratory protection**

Avoid inhalation of vapour and spray mist. Use breathing apparatus if exposed to vapours/dust/aerosol.  
Recommended Filter type: Respiratory protection mask with combination filter A/P2

**Hand protection**

|                      |              |
|----------------------|--------------|
| Glove material       |              |
| Appropriate Material | butyl-rubber |
| Material thickness   | >= 0,5       |
| Breakthrough time    | >= 120       |

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

The breakthrough time must be greater than the end use time of the product.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

**Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

**Information on estimated exposure and downstream-user guidance**

**Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.